Tràddel

Tràddel

Architectural Lighting


?
PRODUCT REQUEST
KNOW HOW
CONCEPT
Finishes
Dissipator
LED
Optics
DRAWING
ANALISYS


IP
IK
fire resistance
photometry
TEST
PRODUCTION
PROTOTYPE
Electronic
ECO
ON/OFF
DALI
DEVELOPMENT
Your Light | Future Proof

Four different interpretations. Product collections designed to “build up” spaces and make them richer through light, the fundamental element that Linea Light Group has masterfully developed in over thirty years of activity. This collection features

architectural lighting

Light requires a high level of precision. Particularly in the field of architectural lighting, where it becomes an essential element that requires close attention. Without light, all environments are uninhabitable; without light, no architectural feature can emerge from darkness; a landscape cannot find full expression if it isn’t properly illuminated. Today, lighting must blend in with the environment and become an added value, never play the lead. Like a good costume designer who, from behind the scenes, dresses up the actors and helps set the scene to fit any historical period, so is lighting in the architectural field. This is precisely what Linea Light Group’s new 2017 Tràddel Architectural Lighting Collection does.

Let the show begin.



Perfect symbiosis with the surrounding space, blending in with the elements of the landscape. The Tràddel Architectural Lighting collection includes innovative products, designed to genuinely

engage with the environment.

Each lighting solution has a style that can suit any environment, from ancient historical buildings to the most modern interiors. Their formal and technological innovations are the result of Linea Light Group's know-how and passion for light and design. This is what allows us to propose truly architectural solutions devised to shape interiors and the architectural landscape with sheer light. In our collections particular emphasis is given to seamless integration with ceilings and walls, so as to make visible the most important feature of lighting:

light itself.

We often test new materials, inspired by trends deriving from the fields of Architecture, Landscape and Interior Design. Maximum attention is devoted to the constant

study of materials

and to the care in the design of surface treatments for our fittings. Indoor luminaires are available in various colours with a matt embossed or plaster finish to offer the best interpretation of contemporary trends in interior design. For the outdoor lighting fixtures, much attention has gone into protection against corrosion. The anodizing pre-treatment ensures maximum protection on aluminium parts: polyester powder coating with excellent weather resistant properties is carried out within a specific time frame before installing in order to guarantee maximum protection. What drives us to analyse, test, and research, is our

inexhaustible passion.



Our optics department works tirelessly in the development of lenses and reflectors integrated in the body of the luminaires. Our lab technicians collaborate with the designers so that lighting research is an integral part of the final product, contributing to its shape and materials.

Optics design

for us means light quality and performance, and the ability to offer ever new, state-of-the-art lighting solutions to satisfy the needs and requirements of project designers. When the quality of lighting is paramount, emission must be extremely pure, and studied to ensure

the best visual comfort.

The Gypsum and Fylo range allow you to fully conceal the lighting fixture and admire lighting effects that draw shapes and environments and become an integral part of the architecture.

LED lighting technology allows us to ensure unique lighting in terms of quality, combining Linea Light Group's expertise with the extreme stylistic synthesis of a collection that has at its core the seamless integration in the architecture.

reddot award 2015
winner

DESIGN AWARD 2017

Formal aesthetic is essential in the design of a lighting fixture. Attention to detail is acknowledged as synonymous with quality, as amply demonstrated by the Fylo and Joe range which were awarded the RedDot Award 2015 in the Product Design category, or the new Dirigo, awarded with the IF Design Award 2017.

The registered patents for some of the products contained in this catalogue prove our total commitment to the creation of functional and innovative solutions.

Linea Light Group's commitment to research allows us to adopt technological solutions like OptiLight™ providing for smart control of light emission and avoiding light spill.





1

FYLO+
Integrated Lighting

We made a restyling of a unique product, awarded with the RedDot Award in 2015, making it more durable, powerful and adaptable.
Fylo+ represents the perfect synthesis between light and architecture. A complete range of indoor and outdoor profiles declined in recessed and surface solutions.
Graphic and defined light or soft luminous effects able to enhance every spaces.
A solution patented for architecture of today and tomorrow.

2

CELL
Comfort and Elegance

This new range of ultra-compact downlight offers total integration with the architectural space.
Available in the Frame and Gypsum models, Cell is extremely versatile and efficient.
The specially designed optical compartment boasts the precision of micro reflectors made from metallised polycarbonate with convex facets combined with cut-off individual cells that provide exceptional glare control.

3

TOUR
Timeless Design

A new round suspension lighting fixture with a minimalist and sleek silhouette. The extra-slim profile is designed to provide three types of emission: direct, indirect or internal.
Four different diameters characterize the range offering elegant and highly efficient solutions that can fit any environment.

4

RADA
Performance and Innovation

The precision of the circle is juxtaposed to the modularity of the rectangle creating a comprehensive range of downlights and offering a new lighting approach for the general illumination of walkways and spacious environments.
Extremely broad and diffuse lighting effects combined with the visual comfort of the indirect emission aesthetic that characterizes this range.

reddot award 2015
winner

5

PEAK

Solutions on an urban scale

An entire program dedicated to outdoor lighting designed to meet all the requirements of a complete lighting project.
With their streamlined and compact design, these fixtures can be seamlessly integrated in any context.
The different solutions available can handle lumens ranging from 1000lm to 5000lm with absolute control of light emission toward the pavement.

6

VUELTA

Control and Precision

A professional projector designed for maximum installation flexibility with precise and efficient light emission. It is available in two sizes, both characterized by a compact design with an extra-slim profile.
The Vuelta range includes two finishes, two colour temperatures and differentiated lumen packages. Rated output power up to 30W and emissions up to 4000lm.
Thanks to a special integrated optical unit, this fixture handles different light emissions (Asymmetric, 10 degree narrow spot, 30 degree flood and wide flood).
Optical accessories and a dedicated installation kit were developed specifically for this range.

7

CEM

Quality Lighting

The reliability and durability of concrete reinterpreted in the design of new compact forms with no sharp edges. Cem exploits the potential offered by latest generation LEDs technology to create grazing light effects, diffuse lighting and dedicated accent lighting solutions for walkways, allowing you to customize your outdoor space with a contemporary and unique touch.
This comprehensive and coordinated range offers wall, ceiling and recessed mounting models.

8

DIRIGO

Simply Unique

A subtle interplay of juxtaposed surfaces creates a precise and balanced linear emission eminently suited for illuminating walkways. Dirigo is a new lighting concept for a fresh interpretation of outdoor spaces. The quality of 316L stainless steel enhances the value of this fixture making it also ideal for high salinity environments.
Aluminium models feature high quality finishes such as the Cor-ten effect, perfect for landscape and historical contexts.

iF DESIGN AWARD 2017

5

Linea Light Group offers a 5-year warranty on its products against manufacturing defects, subject to filling in the activation form available at www. linealight.com. In the absence of activation, the statutory warranty remains valid.

All power supply, wiring and accessories used for product installation shall be original Linea Light Group parts or approved by the company.
The warranty will become void if non original or non approved parts are used.

For more information, please visit our website
www.linealight.com

Tràddel

ARCHITECTURAL
LIGHTING

Indoor

Integrated. lighting

Fylo+ 14 new
Fylo Curved 50
Gypsum 56

Lighting. system

Mini-Outline 138 new
Shore 156 new
Outline_MF 180 upgrade

Wall + Ceiling

Cell 194 new
Rada 200 new
Pool 210
Plik 228 new
Outline_F 236 upgrade
Mini-Outline 240 upgrade
Orient_S 246
Hive_W 250 upgrade
Linear 254
Dual 258
Mini-Dual 260
Point_S 262
Wall_W 264

Floor + Suspension

Tour 274 new
Pool_P 288
Baton 296 new
Shore 304 upgrade
Mini-Outline 306 upgrade
Hive 308 upgrade
Neox_P 316
Matrix_P 320

Cable System

300 System 328 new
150 System 342 new
Mono System 356

Outdoor

Integrated. lighting

Fylo+ Out

372 new

Accent

Vuelta

394 new

Vision

406

Khono

414

Texo

418

Bollard + Poles

Bob18

430 new

Ryo

438 new

Peak

448 new

Peak Maxi

458

Dirigo

464 new

Joe

476 upgrade

Puro

484 new

Pilos

488

Stalk

496

Twig

510

Stick

520

Ciclop

526

I-Cube

532

Rock

536

D-Retta

544

Cu-Flex

548 upgrade

Wall + Ceiling

Cem

558 new

Peak-Maxi

570 new

Stalk_W

574

Stick

576

Dual Out

578

I-Cube

582

Rock

584

Vision

590

LED Strips

LED Strips

Ribbon

596

Dropper

598

Silicone

599

EMergency

EMergency

Escape Route

622

Escape Signals

626

Electronics

Electronics

C.C.

605

C.V.

611

Power Switching

616

Integrated.lighting

Integrated.lighting

Fylo+

Fylo+ Direct_1 26
Fylo+ Direct_2 30
Fylo+ Direct_3 34

Fylo+ Recessed_1 38
Fylo+ Recessed_2 38
Fylo+ Recessed_3 38
Fylo+ Recessed_4 40
Fylo+ Recessed_5 40

Fylo+ Surface_1 46
Fylo+ Surface_2 46
Fylo+ Surface_3 46
Fylo+ Surface_4 48
Fylo Curved 54

Gypsum

Gypsum_Cell1 66
Gypsum_Cell2 66
Gypsum_Cell3 66

Gypsum_R1 70
Gypsum_R2 70
Gypsum_R3 70

Gypsum_O1 76
Gypsum_O2 76
Gypsum_O3 76
Gypsum_O4 76

Gypsum_Eye1 84
Gypsum_Eye2 84
Gypsum_Eye3 84
Gypsum_Eye4 84
Gypsum_EyeJ 85

Gypsum_Ill1 90
Gypsum_Ill2 90
Gypsum_Ill3 90
Illuminator_1 91
Illuminator_2 91
Illuminator_3 91

Gypsum

Gypsum_QC1 94
Gypsum_QC2 94
Gypsum_QC3 95
Gypsum_QC4 96
Gypsum_QCY 96

Gypsum_QD1 100
Gypsum_QD2 100

Gypsum_QRD 104

Gypsum_D1 108
Gypsum_D2 108
Gypsum_D3 108
Gypsum_DX 108

Gypsum_SR 114
Gypsum_SQ 114

Gypsum_W1 118
Gypsum_W2 118
Gypsum_W3 118
Gypsum_WX 118

Gypsum_WR1 122
Gypsum_WR2 122
Gypsum_WRQ 122
Gypsum_WR3 123
Gypsum_WRX 123

Gypsum_WF1 128
Gypsum_WF2 128
Gypsum_WF3 128
Gypsum_WF4 128

Integrated lighting in architecture

Graphic.

Integrated lighting allows to use lighting units as if they were a customized graphic element.
It means communication, it passes through the volumes by digging them up, breaking them or joining them together. It allows to discretely customize rooms, without being overly intrusive.

Creative.

Linear profiles as well as curved or circular elements allow to free the designer's creativity in a space, thus creating unlimited combinations. Each place can have a new appeal and a timeless charm.

Elegant.

A detail that can be perfectly integrated with any style. Gypsum blends in with the existing structure, thus changing the space perception and enhancing the room with elegant light and shade contrasts. A functional, yet sophisticated lighting that can surely generate emotions.

Integrated.lighting

A solution to design every space with lighting

Passages and reception spaces are defined by lines and wall mounted details of light, deriving from sources perfectly integrated with architecture. Wall flush recessed and chalk smooth shapes are the best solutions to have innovative lighting settings. Walls, linkage and entrances are embellished by dedicated lighting, enhancing and underlining all details. Last generation LED technology provides to sources best efficiency and optimized visual comfort, also providing high level performance thanks to lighting output control and management. Thanks to fixtures' best integration in every architectural space and detail a brand new relationship with lighting is fixed.







Graphic. Versatile. Fylo+

Fylo+

reddot award 2015
winner

New lighting source

The new lighting source can be installed directly in the profile, also working as a heatsink; installation must be completed with a dedicated diffuser, with a double function: protect Led sources and level out the lighting emission into the living space.

Fylo+ is compatible with Led strip lighting units available in the catalogue.

26

More light / more efficiency.

A lightened aluminum, with a specific design developed for the profile section, allows the use of module's surface as a heatsink, increasing entire range luminous performance.



Fast installation

Profiles installation occurs by a simple snap over its dedicated brackets. Special plastic elements have been introduced on the back of the profiles, inside linear guides in which they flow. Fixing is not bound to a predetermined point, but following the installer needs.

Fylo+ Surface



Place the profile near the brackets

Push it with your fingers to snap it in

Fylo+ Recessed

Fylo+ is fitted to be installed into plasterboard walls. To install it on already existing walls, simply remove the side wings included in the profile.



Unchanged aesthetic

Compared to the previous version, new Fylo modules maintain its aesthetic unchanged. When fully installed, profiles disappear by merging with the surrounding architecture; integrated light concept allows space customization with unusual and precious lighting details.

Pre-treated aluminum profile.

Quartz powder resin.

Mixed building material resin applied with several coats granting a homogeneous and thick surface, ready to be sanded and serving as a support for the final coat of paint.

Final paint. Application of primer as if it was on plasterboard.

Graphic light to customize any environment.

Fylo+ is extremely versatile and it features a broad selection of shapes and sections, which are suitable for both recessed and surface mounting. It creates a fine light that allows to draw new paths, highlight volumes or generate a visual guide to find the right direction.







Fylo+ Direct



* Art. 65000
Art. 65001



Art. 65042W
Art. 65043W



Art. 63605
Art. 63615
Art. 63625
Art. 63635
Art. 63645

Modules

2000 mm

1000 mm

1100 ->1900 mm 100 *

*** Custom lenghts**
All Fylo+ modules can be supplied precutted on demand, in 10 cm modules, adapting the system in fast and precise way, following single project needs.

Electrification

Top LED

Stripled

Electronics

ON / OFF

DALI

Fylo+ Recessed



* Art. 65006
Art. 65007



* Art. 65003
Art. 65004



* Art. 65027
Art. 65028



* Art. 65009
Art. 65010



* Art. 65012
Art. 65013

Modules

2000 mm

1000 mm

1100 ->1900 mm 100 *

*** Custom lenghts**
All Fylo+ modules can be supplied precutted on demand, in 10 cm modules, adapting the system in fast and precise way, following single project needs.

Electrification

Top LED

Stripled

Electronics

ON / OFF

DALI

Fylo+ Surface

* Art. 65015
Art. 65016



* Art. 65018
Art. 65019

* Art. 65021
Art. 65022



* Art. 65024
Art. 65025

Modules

2000 mm

1000 mm

1100 ->1900 mm 100 *

*** Custom lenghts**
All Fylo+ modules can be supplied precutted on demand, in 10 cm modules, adapting the system in fast and precise way, following single project needs.

Electrification

Top LED

Stripled

Electronics

ON / OFF

DALI



Art. 65000
Art. 65001

Art. 65042W
Art. 65043W

Art. 63605
Art. 63615
Art. 63625
Art. 63635
Art. 63645



Art. 65006
Art. 65007



Art. 65003
Art. 65004



Art. 65027
Art. 65028

Art. 65009
Art. 65010



Art. 65012
Art. 65013



Art. 65015
Art. 65016



Art. 65018
Art. 65019



Art. 65021
Art. 65022



Art. 65024
Art. 65025

Installation

Wall or ceiling mounting

The profiles used for the installation on walls and ceiling made of plasterboard, bricks or other materials enhance the lighting role in interior design, both in terms of aesthetics and functionality.

- Fasten the support brackets onto the wall.

- Insert the plastic fittings in the profile.

- Place the item onto the wall and fasten it with the brackets.
- Insert the sealing plugs.



- Apply two or three coats of plaster.
- Place the gauze by the joints.
- Sand and paint.

Recessed mounting on false ceilings

The shape of the profiles allows for recessed mounting on 12.5/15mm false ceilings to create lighting effects that make places look more spacious.

- Drill the hole.

- House the item in the hole and fasten it with screws inside the false ceiling.
- Place the following profiles in sequence.



- Apply two or three coats of plaster.
- Place the gauze by the joints.
- Sand.



- Paint.

Recessed or semi-recessed mounting on existing partitions

The design of the profiles allows recessed mounting with 12.5mm-thick double-layer plasterboard partitions to create light effects that expand the perception of space.



- Drill the hole.
- Remove the brackets from the profile.



- Place the element in the hole and secure it with glue to the metal structure in the partition.

- Place the following profiles sequentially.

- Fill in with two or three layers of plaster.
- Apply the gauze over the joints.
- Sand and paint.

Recessed or semi-recessed mounting on partitions during construction

The design of the profiles allows recessed mounting with 12.5mm-thick double-layer plasterboard partitions to create light effects that expand the perception of space.

- Fix the element to the metallic structure with the screws.



- Place the following profiles sequentially.

- Position the plasterboard panels.

- Apply two or three coats of plaster.
- Apply the gauze over the joints.
- Sand and paint.

The profiles come with an internal protection film to be removed during installation.

Top LED Modules



- Put the Master circuit in the dedicated space in the profile and connect the Slave circuits.
- Install the protection screen.

LED Strip

- Put the LED strip inside the profile.
- Install the protection screen.

new

Fylo+ Direct

Designed for offices and environments where there is a need for high-performance light

Direct light pathways integrated into the structure of the ceiling and walls. Fylo+ direct is the modular solution for innovative architectural lighting. State-of-the-art LED technology gives light increased efficiency and visual charm. Staircases, hallways, kitchens and other rooms of a building: there exists no architectural space that does not find in Fylo+ direct inspiration for a new relationship with light. Fylo+ direct enhances quality of life and the value of any interiors.





Fylo+ Direct_1 | Recessed linear light



type	L mm	
White	1000	**65000**
White	2000	**65001**
White	custom	**65029***

Suggested accessories



65054
Opal Diffuser L1000 mm 1pc

65055
Opal Diffusers L1000 mm 5pcs

62900
Recessed outer-casing

All modules must be completed with light units and driver.

See bottom page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65029.

Fylo+ | Light units - Inflex | TopLED 7W

III C.V. IP20

type				colour			optics
Master+Slave	CRI 80	**65050W**	L 2x500 mm	3000 K	2x650 lm	2 pcs	diffused
Slave	CRI 80	**65052W**	L 2x500 mm	3000 K	2x650 lm	2 pcs	diffused
Slave	CRI 80	**65051W**	L 10x500 mm	3000 K	10x650 lm	10 pcs	diffused

LED bars section
For a total amount under a 500 mm multiple, it is possible to cut with a hacksaw the LED bar in sizes multiples of 100 mm, making sure to position the blade at the point shown in the figure. Incorrect sizing affects the operation of the bar.

Suggested electronics



62870
ON/OFF 2,5 mt

62880
ON/OFF 4 mt

62890
ON/OFF 10 mt

99332
1-10V 10 mt

84702
Switching

99074
DALI/1-10V Controller 10 mt

99077
PUSH Controller

Fylo+ | Light units-LED Strips

	type
598	**Ribbon**
596	**Dropper**

Suggested electronics



62870
ON/OFF 2,5 mt

62880
ON/OFF 4 mt

62890
ON/OFF 10 mt

99332
1-10V 10 mt

84702
Switching

99074
DALI/1-10V Controller 10 mt

99077
PUSH Controller

Fylo+ Direct_2 | Recessed linear light | 100-264 V | topLED 14,5 W 350 mA

C.C. IP40



type		colour			optics	
Anod. Al.	**65042**	3000 K	2020 lm	**W**	diffused	**00**

All modules come complete with light units and driver.

Suggested accessories



65056	**65057**	**65044**	**60127**	**62180**
Opal Diffuser L1000 mm 1pc	Opal Diffuser L2000 mm 1pc	End caps 2 pcs	Electrical connector 3 poles	Junction

Fylo+ Direct_2 | Recessed linear light | 198-264 V | topLED 29 W 700 mA

IP40



type		colour			optics	
Anod. Al.	**65043**	3000 K	4040 lm	**W**	diffused	**00**

All modules come complete with light units and driver.

Suggested accessories



65056	**65057**	**65044**	**60127**	**62180**
Opal Diffuser L1000 mm 1pc	Opal Diffuser L2000 mm 1pc	End caps 2 pcs	Electrical connector 3 poles	Junction

Fylo+ Direct_3 | Recessed linear light | 100-264 V | topLED 21,5 W 500 mA

All modules come complete with light units and driver.



type		colour			optics	
Anod. Al.	**63605**	3000 K	2020 lm	**W**	diffused	**00**

Suggested accessories

63601	**62180**	**60127**
Closing cap	Junction	Electrical connector 3 poles

Fylo+ Direct_3 | Recessed linear light | 198-264 V | topLED 29 W 700 mA

All modules come complete with light units and driver.



type		colour			optics	
Anod. Al.	**63615**	3000 K	3030 lm	**W**	diffused	**00**

Suggested accessories

63601	**62180**	**60127**
Closing cap	Junction	Electrical connector 3 poles

Fylo+ Direct_3 | Recessed linear light | 198-264 V | topLED 43,5 W 1050 mA

All modules come complete with light units and driver.



type		colour			optics	
Anod. Al.	**63625**	3000 K	4040 lm	**W**	diffused	**00**

Suggested accessories



63601	**62180**	**60127**
Closing cap	Junction	Electrical connector 3 poles

Fylo+ Direct_3 left corner | Recessed linear light | 100-264 V | topLED 21,5 W 500 mA

All modules come complete with light units and driver.



type		colour			optics	
Anod. Al.	**63645**	3000 K	2020 lm	**W**	diffused	**00**

Suggested accessories



63601	**62180**	**60127**
Closing cap	Junction	Electrical connector 3 poles

Fylo+ Direct_3 right corner | Recessed linear light | 100-264 V | topLED 21,5 W 500 mA

IP40

All modules come complete with light units and driver.



43 x 531 x 531

type		colour			optics	
Anod. Al.	**63635**	3000 K	2020 lm	**W**	diffused	**00**

Suggested accessories

63601
Closing cap

62180
Junction

60127
Electrical connector 3 poles

ACCESSORIES AND LAYOUT

Maximum length for single supply 50 mt

63601
Closing cap

62180
Junction

60127
Electrical connector 3 poles



new

Fylo+ Recessed

Ideal for creating a soft light effect

An indirect LED light blended into the building structure.
A resistant profile with which to create original shapes and silhouettes and give new life to architecture. Fylo+ Recessed deepens your perception of space and transforms interiors with the seduction of light. Light pours from the profiles and falls on surfaces like a waterfall, making the surrounding environment soft and all-enveloping.
The semi-recessed version enhances the magic of this fixture by hiding the source of light.



Fylo+ Recessed_1 | Recessed linear light body



type	L mm	
White	1000	**65027**
White	2000	**65028**
White	custom	**65032***

Suggested accessories



65054	**65055**	**62900**
Opal Diffuser L1000 mm 1pc	Opal Diffusers L1000 mm 5pcs	Recessed outer-casing

All modules must be completed with light units and driver.

See next page.

* By selecting the “Custom” code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65032.

Fylo+ Recessed_2 | Recessed linear light body



type	L mm	
White	1000	**65006**
White	2000	**65007**
White	custom	**65045***

Suggested accessories



65054	**65055**	**62900**
Opal Diffuser L1000 mm 1pc	Opal Diffusers L1000 mm 5pcs	Recessed outer-casing

All modules must be completed with light units and driver.

See next page.

* By selecting the “Custom” code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65045.

Fylo+ Recessed_3 | Recessed linear light body



type	L mm	
White	1000	**65003**
White	2000	**65004**
White	custom	**65046***

Suggested accessories



65054	**65055**	**62900**
Opal Diffuser L1000 mm 1pc	Opal Diffusers L1000 mm 5pcs	Recessed outer-casing

All modules must be completed with light units and driver.

See next page.

* By selecting the “Custom” code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65046.

Fylo+ Recessed_4 | Recessed linear light body





type	L mm	
White	1000	**65009**
White	2000	**65010**
White	custom	**65047***

Suggested accessories



62900 Recessed outer-casing

65054 Opal Diffuser L1000 mm 1pc

65055 Opal Diffusers L1000 mm 5pcs

All modules must be completed with light units and driver.

See bottom page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65047.

Fylo+ Recessed_5 | Recessed linear light body





type	L mm	
White	1000	**65012**
White	2000	**65013**
White	custom	**65048***

Suggested accessories

62900 Recessed outer-casing

All modules must be completed with light units and driver.

See bottom page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65048.

Fylo+ | Light units - Inflex | TopLED 7W

III C.V. IP20



type				colour			optics
Master+Slave	CRI 80	**65050W**	L 2x500 mm	3000 K	2x650 lm	2 pcs	diffused
Slave	CRI 80	**65052W**	L 2x500 mm	3000 K	2x650 lm	2 pcs	diffused
Slave	CRI 80	**65051W**	L 10x500 mm	3000 K	10x650 lm	10 pcs	diffused

LED bars section
For a total amount under a 500 mm multiple, it is possible to cut with a hacksaw the LED bar in sizes multiples of 100 mm, making sure to position the blade at the point shown in the figure. Incorrect sizing affects the operation of the bar.

Suggested electronics



62870 ON/OFF 2,5 mt

62880 ON/OFF 4 mt

62890 ON/OFF 10 mt

99332 1-10V 10 mt

84702 Switching

99074 DALI/1-10V Controller 10 mt

99077 PUSH Controller 10 mt

Fylo+ | Light units-LED Strips

	type
598	**Ribbon**
596	**Dropper**

Suggested electronics



62870 ON/OFF

62880 ON/OFF

62890 ON/OFF

99332 1-10V

84702 Switching

99074 DALI/1-10V Controller

99077 PUSH Controller

new

Fylo+ Surface

Surface installed solutions of great effect

Grazing light to emphasize the surface of the walls. Shaped elements bringing light everywhere, seamlessly complementing the building structure. Fylo+ Surface is the lighting fixture that makes interiors special. Lines crossing the surface of your walls. Shaded spaces that reacquire light. Important parts of a room are emphasized. Fylo+ Surface traces on your walls the magic of light. Technology meets aesthetics and functionality in architectural design.

Essential details allow to completely renovate any environment.

Light details to renovate any environment.

Fylo+ Surface can be applied on any type of support to enhance any environment by means of a fine chiaroscuro effect.
At day time the profile is invisible and fully blended in with the structure it is installed in. Light appears unexpectedly inside the profile, also softly wrapping the surfaces and the volumes around it.

Fylo+ Surface_1 | Surface light body



type	L mm	
White	1000	**65015**
White	2000	**65016**
White	custom	**65049***

Suggested accessories



65054	65055	62900	65008
Opal Diffuser L1000 mm 1pc	Opal Diffusers L1000 mm 5pcs	Recessed outer-casing	End caps 2 pcs

All modules must be completed with light units and driver.

See next page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65049.

Fylo+ Surface_2 | Surface light body



type	L mm	
White	1000	**65018**
White	2000	**65019**
White	custom	**65053***

Suggested accessories



65054	65055	62900	65011
Opal Diffuser L1000 mm 1pc	Opal Diffusers L1000 mm 5pcs	Recessed outer-casing	End caps 2 pcs

All modules must be completed with light units and driver.

See next page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65053.

Fylo+ Surface_3 | Surface light body



type	L mm	
White	1000	**65021**
White	2000	**65022**
White	custom	**65058***

Suggested accessories



65054	65055	62900	65014
Opal Diffuser L1000 mm 1pc	Opal Diffusers L1000 mm 5pcs	Recessed outer-casing	End caps 2 pcs

All modules must be completed with light units and driver.

See next page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65058.

Fylo+ Surface_4 | Angolare light body



type	L mm	
White	1000	**65024**
White	2000	**65025**
White	custom	**65059***

Suggested accessories



65054
Opal Diffuser L1000 mm 1pc

65055
Opal Diffusers L1000 mm 5pcs

62900
Recessed outer-casing

All modules must be completed with light units and driver.

See bottom page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65059.

Fylo+ | Light units - Inflex | TopLED 7W

III C.V. IP20

LED bars section
For a total amount under a 500 mm multiple, it is possible to cut with a hacksaw the LED bar in sizes multiples of 100 mm, making sure to position the blade at the point shown in the figure. Incorrect sizing affects the operation of the bar.

type				colour			optics
Master+Slave	CRI 80	**65050W**	L 2x500 mm	3000 K	2x650 lm	2 pcs	diffused
Slave	CRI 80	**65052W**	L 2x500 mm	3000 K	2x650 lm	2 pcs	diffused
Slave	CRI 80	**65051W**	L 10x500 mm	3000 K	10x650 lm	10 pcs	diffused

Suggested electronics



62870
ON/OFF 2,5 mt

62880
ON/OFF 4 mt

62890
ON/OFF 10 mt

99332
1-10V 10 mt

84702
Switching

99074
DALI/1-10V Controller 10 mt

99077
PUSH Controller 10 mt

Fylo+ | Light units-LED Strips

	type
598	**Ribbon**
596	**Dropper**

Suggested electronics



62870
ON/OFF

62880
ON/OFF

62890
ON/OFF

99332
1-10V

84702
Switching

99074
DALI/1-10V Controller

99077
PUSH Controller

Rounded. Integrated. **Fylo curved**

Fylo curved

An expression of elegance

The elegance and simplicity of a modular range that allows the creation of new lighting concepts through its curved elements. Light seamlessly blends in with the ceiling through soft shapes.

Installation example

Composition
art. 62706-1 pz.4

STRIP L. 4000mm

Curved element
62706-1



Fylo curved | Recessed light



All modules must completed with light units and driver.

See bottom page.

type

White	**60841**

Suggested accessories

62900

Recessed outer-casing

Fylo curved | Recessed circular light body



All modules must completed with light units and driver.

See bottom page.

type

White	**62706-1**

Suggested accessories

62900

Recessed outer-casing

Fylo+ | Light units-LED Strips

type

596 **Dropper**

Suggested electronics

62870

ON/OFF

62880

ON/OFF

62890

ON/OFF

99332

1-10V

84702

Switching

99074

DALI/1-10V Controller

99077

PUSH Controller



Invisible. Smooth. **Gypsum**

Downlight

Gypsum_Cell


Gypsum_R

Gypsum_O

Gypsum_Eye

Gypsum_III

Gypsum_Q

Gypsum_D


Gypsum_S

ON / OFF

DALI

Wall light

Gypsum_W

ON / OFF

DALI

Pathmarker

Gypsum_WR

Gypsum_WR


Gypsum_WR

Gypsum_WR

Gypsum_WF

ON / OFF

DALI

Emission







new

Gypsum_Cell

Comfort and elegance

Flush recessed adjustable spot, available in three direct light options: rectangular 3 or 6 spots, squared 9 spots.
Chalk invisible frame, customizable finishes.
Perfect for accent lighting. Magnetic locking, set back and shade LED source.

+ invisible recessed
+ modular and adjustable light
+ LED source





Frame version

194

Product plus

Integration with the space

Cell suggests a total integration with architectural space. All Gypsum versions allows fixture's ceiling perfect merging, making it almost invisible. Special metallized polycarbonate optic uses micro reflector high accuracy, with convex facets single cylindric cut-off cells, to guarantee the highest glare control. The fixture when working seems off and the light springs magically from architecture.

1:1 Scale



Black finish

Colour rendering

CRI > 90



White finish

Semi-glossy moulded polycarbonate cut-off cells

Micro-optics in metallized polycarbonate with convex facets

Range

Available in "Frame" version with visible border and "Gypsum" version with chalk frame for a complete ceiling integration. Cell is available in three options: 3Leds (6W), 6Leds (12W) and 9Leds (18W).

Frame version



Gypsum version



Gypsum_Cell

CELL micro-optics

The new high-reflectance metallic polycarbonate optic manages lighting in an extraordinary way, the effects distribution is soft and smooth and direct glare is almost nonexistent. A particular square mesh convex facets define the micro reflectors surface, controlling every single light beam, and defining a 10° and 30° emission.





Visual comfort

The circular cross section cut-off cells are the interface between the optical unit and the ceiling. Thanks to their peculiar gradient they control the device luminance in combination with the reflectors ensuring professional results.



Fast installation

Gypsum_Cell versions defined by fast magnet hooking system, providing optics' easier installation.



Gypsum_Cell1 | Downlights | 3 x powerLEDs 2 W | 6 W 700 mA

III C.C. IP20



type		colour				optics	
White	**64547**	CRI 90	3000 K	747 lm	**W**	15°	**15**
Black	**64546**	CRI 80	4000 K	795 lm	**N**	30°	**30**

Suggested electronics

62437	62439	99115	99114	99344
ON/OFF 1 art.	ON/OFF 3-4 art.	1-10V/PUSH 1-3 art.	DALI/PUSH 1-3 art.	DALI/PUSH 1-4 art.

Suggested accessories

60830
Shim

Gypsum_Cell2 | Downlights | 6 x powerLEDs 2 W | 12 W 700 mA

III C.C. IP20







type		colour				optics	
White	**64549**	CRI 90	3000 K	1494 lm	**W**	15°	**15**
Black	**64548**	CRI 80	4000 K	1590 lm	**N**	30°	**30**

Suggested electronics

62438	62439	99115	99114	99344
ON/OFF 1 art.	ON/OFF 1-2 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.	DALI/PUSH 1-2 art.

Suggested accessories

60830
Shim

Gypsum_Cell3 | Downlights | 9 x powerLEDs 2 W | 18 W 700 mA

III C.C. IP20







type		colour				optics	
White	**64551**	CRI 90	3000 K	2241 lm	**W**	15°	**15**
Black	**64550**	CRI 80	4000 K	2385 lm	**N**	30°	**30**

Suggested electronics



62439	99115	99114
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830
Shim

Gypsum_R

Integrated light

Defined by a circular essential shape, three diameters available for every designer's or lighting feeling needed. The source disappears completely, just a wide beam light emerges.

+ integrated light
+ invisible frame
+ LED source



Gypsum_R1 | Downlights | arrayLED 7,5 W 200 mA

III C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**61350**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	62431	62432
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories



60830	61360
Shim	Outer casing

Gypsum_R2 | Downlights | arrayLED 7,5 W 200 mA

III C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**61330**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	62431	62432
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories



60830	60860
Shim	Glass

Gypsum_R3 | Downlights | arrayLED 18 W 500 mA

III C.C. IP20



type			colour			optics	
White	CRI 80	**62660**	3000 K	2611 lm	**W**	diffused	**00**
			4000 K	2697 lm	**N**		

Suggested electronics



99106	99115	99114
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830
Shim

Gypsum_R1 | Downlights | 1xGU10

IP40 O.C. IP20



LED

type		source	optics
White	**61250**	1xGU10 35W Max	variable

Suggested accessories



60830 Shim

61360 Outer casing

Gypsum_R2 | Downlights | 1xGU10

IP40 O.C. IP20



LED

type		source	optics
White	**61230**	1xGU10 35W Max	variable

Suggested accessories



60830 Shim

60860 Glass

Gypsum_O

Organic design

Defined by an organic shape, a light crater available in two heights. Discreet and soft shapes merge with the living space, the large chalk frame disappears, and just light is visible.

+ two heights invisible frame
+ merge with wall finishes
+ organic design

Gypsum_O

Matter and colour

The plasticity of gypsum blends the lighting fixture with the construction elements that define the space. Light, matter and colour become a whole that can be radically renovated thanks to the paintable surface of Gypsum. A real white canvas that you can customize based on your own taste.

Stucco

Luxury

Black and White

LUDOTECA

Gypsum_O1 | Downlights | arrayLED 7,5 W 200 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60801**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	62431	62432
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830
Shim

Gypsum_O2 | Downlights | arrayLED 7,5 W 200 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60821**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	62431	62432
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830
Shim

Gypsum_O3 | Downlights | arrayLED 18 W 500 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60824**	3000 K	2611 lm	**W**	45°	**45**
			4000 K	2697 lm	**N**		

Suggested electronics



99106	99115	99114
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830
Shim

Gypsum_O4 | Downlights | arrayLED 18 W 500 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60827**	3000 K	2611 lm	**W**	45°	**45**
			4000 K	2697 lm	**N**		

Suggested electronics



99106	99115	99114
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830
Shim

Gypsum_O1 | Downlights | 1xGU10

IP40 O.C. IP20



LED

type	source	optics
White **60802**	1xGU10 35W Max	variable

Suggested accessories

60830

Shim

Gypsum_O2 | Downlights | 1xGU10

IP40 O.C. IP20



LED

type	source	optics
White **60822**	1xGU10 35W Max	variable

Suggested accessories

60830

Shim



Gypsum_Eye

Scenographic light

Downlights with great performance, the concave chalk surface cloaks light source and soften the light. Available with special lens for special lighting effects, diffusive or concentrate.

+ LED source
+ organic and customizable design
+ captivating light effects

Fast installation

Once chalk frame is fixed on installation plan, it's enough entering the fixture with a single snap inside the dedicated compartment. Electrical connection is provided by a fast connector prepared on fixture.



Quality materials

Chalk frame wraps the fixture's technological heart, perfectly merging with the living space.
During the day the fixture disappears and during the night creates charming lighting scenes.



Plaster frame available with different sections

Convex lens made of extra-clear glass

arrayLED Technology

On request the internal part of the optic group, made of sandblasted aluminium, can be personalized with other finishes



Effect light

A special convex integrated lens, in extra clear glass, creates a stylish luminous effect defining every living space. The arrayLED technology guarantees elevated output related to reduced comsumption, with high level lighting performance.

Gypsum_Eye1 | Downlights | arrayLED 7,5 W 200 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**61340**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	**62431**	**62432**
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830
Shim

Gypsum_Eye2 | Downlights | arrayLED 12,5 W 350 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60852**	3000 K	1876 lm	**W**	50°	**50**
			4000 K	1938 lm	**N**		

Suggested electronics



99126	**99115**	**99114**
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830
Shim

Gypsum_Eye3 | Downlights | arrayLED 12,5 W 350 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60853**	3000 K	1876 lm	**W**	50°	**50**
			4000 K	1938 lm	**N**		

Suggested electronics



99126	**99115**	**99114**
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830
Shim

Gypsum_Eye4 | Downlights | 110-240 V | topLED 21 W

IP40



type			colour			optics	
White	CRI 80	**60828**	3000 K	2180 lm	**W**	diffused	**00**
			4000 K	2304 lm	**N**		

Suggested accessories

60830
Shim

Gypsum_Eye1 | Downlights | 1xGU10



LED

type	source	optics
White **60980**	1xGU10 35W Max	variable

Suggested accessories

60830

Shim

Gypsum_EyeJ | Downlights | 1xG53



Adjustable optics

type	source	optics
White **61370**	1xG53 65W Max	diffused

Suggested electronics



57350

ON/OFF
1 art.

Suggested accessories

60830

Shim

Gypsum_Ill

Modular light

Available in three flush versions: organic, square and rectangular module. The suggested options guarantee highest flexibility for a better lighting effects management.

+ modular and invisible frame light
+ LED source
+ highest flexibility and custom finishes

Gypsum_Ill

High performance

Illuminator modules provide a high performance with a low consumption (max 30W), also granting intensities of 28000cd along the axis. An efficiency higher than 100lm/W and the possibility to choose among three different beam openings make this product a striking lighting solution for retail and hospitality.

Optics



* Indicative lux values Illuminator_3 (H 3mt)

Fast installation

Once chalk frame is fixed on installation plan, it's enough entering the fixture with a single snap inside the dedicated compartment. Electrical connection is provided by a fast connector prepared on fixture.

Gypsum_III1 | Downlights |



type

White	**60843**

Suggested accessories

Illuminator **60830**

Shim

Gypsum_III2 | Downlights |



type

White	**60844**

Suggested accessories

Illuminator **60830**

Shim

Gypsum_III3 | Downlights |



type

White	**60845**

Suggested accessories

Illuminator **60830**

Shim

Illuminator_1 | Downlights | arrayLED 15 W 400 mA

C.C. IP20



type			colour			optics	
White	CRI 95	**97476**	3000 K	1414 lm	**W**	30°	**30**
			4000 K	1522 lm	**N**	60°	**60**
White	CRI 80	**97482**	3000 K	1875 lm	**W**	30°	**30**
			4000 K	2013 lm	**N**	60°	**60**

Suggested electronics

99113	99116	99131
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

98071	98072
30° Optics	60° Optics

Illuminator_2 | Downlights | arrayLED 25 W 720 mA

C.C. IP20



type			colour			optics	
White	CRI 95	**97485**	3000 K	2511 lm	**W**	30°	**30**
			4000 K	2695 lm	**N**	60°	**60**
White	CRI 80	**97491**	3000 K	3321 lm	**W**	30°	**30**
			4000 K	3568 lm	**N**	60°	**60**

Suggested electronics



99112	99188	99330
ON/OFF 1 art.	1-10V, DALI PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

98071	98072
30° Optics	60° Optics

Illuminator_3 | Downlights | arrayLED 30 W 840 mA

C.C. IP20



type			colour			optics	
White	CRI 95	**91229**	3000 K	2839 lm	**W**	15°	**15**
			4000 K	3261 lm	**N**	30°	**30**
						60°	**60**
White	CRI 80	**91232**	3000 K	3945 lm	**W**	15°	**15**
			4000 K	3945 lm	**N**	30°	**30**
						60°	**60**

Suggested electronics

99093	99187	99330
ON/OFF 1 art.	1-10V, DALI PUSH 1 art.	DALI 1 art.

Suggested accessories

98507	98508	98509
15° Optics	30° Optics	60° Optics

Gypsum_QC

Versatile light

Defined by archetypal shape, available in two dimensions, versatile for all designers and spaces lighting needs.

+ versatile light
+ LED source
+ invisible frame
+ symmetric and asymmetric beam





Gypsum_QC1 | Downlights | 1 x powerLED 1,5 W 500 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**64500**	3000 K	144 lm	**W**	60°	**60**
			4000 K	180 lm	**N**		

Suggested electronics

99195	99128	99114	99115
ON/OFF 1-2 art.	ON/OFF 3-6 art.	1-10V/PUSH 1-12 art.	1-10V, DALI 1-12 art.

Suggested accessories

60830
Shim

Gypsum_QC2 | Downlights | arrayLED 7,5 W 200 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60990**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	62431	62432
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories



60830	60840
Shim	Glass *

*** The accessory glass 60840 cannot be installed on wall mounted Gypsum**

Gypsum_QC2 | Downlights | 1xGU10

IP40 O.C. IP20



LED

type		source	optics
White	**61210**	1xGU10 35W Max	variable

Suggested accessories



60830	60840
Shim	Glass *

*** The accessory glass 60840 cannot be installed on wall mounted Gypsum**

Gypsum_QC3 | Downlights | 2 x arrayLED 7,5 W 200 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**61800**	3000 K	2x1117 lm	**W**	70°	**70**
			4000 K	2x1153 lm	**N**		

Suggested electronics
2 driver per article



62423	62431	62432
ON/OFF 2 x 62423	1-10V/PUSH 2 x 62431	DALI/PUSH 2 x 62432

Suggested accessories



60830	60840
Shim	Glass *

*** The accessory glass 60840 cannot be installed on wall mounted Gypsum**

Gypsum_QC3 | Downlights | 2xGU10

□ IP40 O.C. IP20



LED

type		source	optics
White	**62480**	2xGU10 35W Max	variable

Suggested accessories



60830	60840
Shim	Glass *

*** The accessory glass 60840 cannot be installed on wall mounted Gypsum**

Gypsum_QC4 | Downlights | arrayLED 7,5 W 200 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60595**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	62431	62432
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830

Shim

Gypsum_QCY | Downlights | arrayLED 7,5 W 200 mA

C.C. IP40 O.C. IP20



Asymmetric

type			colour			optics	
White	CRI 80	**61410**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	62431	62432
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830

Shim

Gypsum_QC4 | Downlights | 1xGU10

IP40 O.C. IP20

LED



type		source	optics
White	**62430**	1xGU10 35W Max	variable

Suggested accessories

60830

Shim

Gypsum_QCY | Downlights | 1xGU10

IP40 O.C. IP20

LED Asymmetric



type		source	optics
White	**61320**	1xGU10 35W Max	variable

Suggested accessories

60830

Shim

Gypsum_QD

Diffused light

Square compact shapes fitted with a sandblasted opaline screen, which allows to control the emission and soften the shades. A quality detail with a timeless design.

+ square section
+ LED source
+ soft and wrapping light
+ integrated opaline diffuser



Gypsum_QD1 | Downlights | arrayLED 9,3 W 250 mA

III C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**63830**	3000 K	1364 lm	**W**	diffused	**00**
			4000 K	1408 lm	**N**		

Suggested electronics



62424	62431	62432
ON/OFF 1 art.	1 art.	1 art.

Suggested accessories

60830
Shim

Gypsum_QD2 | Downlights | arrayLED 12,5 W 350 mA

III C.C. IP20



type			colour			optics	
White	CRI 80	**63820**	3000 K	1876 lm	**W**	diffused	**00**
			4000 K	1938 lm	**N**		

Suggested electronics



99126	99114	99115
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories

60830
Shim

Gypsum_QRD

Contemporary design

An ultra compact casing wraps the source light through an original union between the perfection of the square and the absence of sharp edges, which blend the gypsum body with the installation surface.

+ absence of sharp edges
+ LED source
+ customizable finishes



Gypsum_QRD | Downlights | arrayLED 7,5 W 200 mA

III C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**61450**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	62431	62432
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Suggested accessories



60840	60830
Glass	Shim

Gypsum_QRD | Downlights | 1xGU10

IP40 O.C. IP20

LED



type			source	optics
White		**61430**	1xGU10 35W Max	variable

Suggested accessories



60840	60830
Glass	Shim

Gypsum_D

Light geometries

Light figure available in many options: squared and rectangular. Combinable in free and mixed geometry, ideal for illuminating path and passages, with a soft and without contrasts light. Invisible frame and source, the light flows directly from the surface.

+ four formal options
+ LED source

Gypsum_D1 | Downlights | 220-240 V | topLED 13 W 350 mA

IP40



type			colour			optics	
White	CRI 80	**64501**	3000 K	1610 lm	**W**	diffused	**00**

Suggested accessories

60830

Shim

Gypsum_D2 | Downlights | 198-264 V | topLED 32 W 900 mA

IP40



type			colour			optics	
White	CRI 80	**64502**	3000 K	4140 lm	**W**	diffused	**00**

Suggested accessories

60830

Shim

Gypsum_D3 | Downlights | 198-264 V | topLED 26 W 700 mA

IP20



type			colour			optics	
White	CRI 80	**64504**	3000 K	3220 lm	**W**	diffused	**00**

Suggested accessories

60830

Shim

Gypsum_DX | Downlights | 198-264 V | topLED 51 W 1400 mA

IP20



type			colour			optics	
White	CRI 80	**64503**	3000 K	6440 lm	**W**	diffused	**00**

Suggested accessories

60830

Shim

DX modules installation

Besides standard installation on plasterboard ceilings, the article is dimensionally suitable for 600x600 metal grid ceilings.



Gypsum_S

Semi-recessed

Two complementary shapes, easily combinable, minimum dimensions. Semi recessed solution allows products concealing in the living space. The chalk frame, allows a perfect integration with the installing and finish surface, and lighting source shielding to maximize the visual comfort, hiding the lamp.

+ customizable finishes
+ LED source
+ excellent visual comfort



Gypsum_SR | Downlights | arrayLED 7,5 W 200 mA

III C.C. IP40 O.C. IP20





type			colour			optics	
White	CRI 80	**60851**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	**62431**	**62432**
ON/OFF	1-10V/PUSH	DALI/PUSH
1 art.	1 art.	1 art.

Gypsum_SQ | Downlights | arrayLED 7,5 W 200 mA

III C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60848**	3000 K	1117 lm	**W**	70°	**70**
			4000 K	1153 lm	**N**		

Suggested electronics



62423	**62431**	**62432**
ON/OFF	1-10V/PUSH	DALI/PUSH
1 art.	1 art.	1 art.

Gypsum_W

Essential shapes

Essential and minimal rectangular shapes define grazing and soft light beams. The Gypsum series is a traditional material with LED technology combination.

+ essential shapes
+ customizable finishes
+ LED source



Gypsum_W1 | Wall Lights | 220-240 V | topLED 7,5 W 200 mA

IP40



type			colour			optics	
White	CRI 80	**60834**	3000 K	1104 lm	**W**	diffused	**00**
			4000 K	1170 lm	**N**		

Gypsum_W2 | Wall Lights | 198-264 V | topLED 15 W 350 mA

IP40



type			colour			optics	
White	CRI 80	**60817**	3000 K	1927 lm	**W**	diffused	**00**
			4000 K	2044 lm	**N**		

Gypsum_W3 | Wall Lights | 220-240 V | topLED 25 W 600 mA

IP40



type			colour			optics	
White	CRI 80	**60819**	3000 K	3315 lm	**W**	diffused	**00**
			4000 K	3510 lm	**N**		

Gypsum_WX | Wall Lights | 220-240 V | topLED 10 W 500 mA

IP20



type			colour			optics	
White	CRI 80	**60816**	3000 K	990 lm	**W**	diffused	**00**
			4000 K	1050 lm	**N**		

Suggested accessories

60830
Shim

60839
Outer casing

Gypsum_WR

Total invisibility

The invisible takes shape, becoming a light source.
The invisible frame follows the contemporary architecture needs. This model represents light essence, gathered around a single point.
On demand, version with golden or silver leaf inside.

+ total invisibility
+ luxury finishes
+ LED source



Gypsum_WR1 | Recessed lights | 1 x powerLED 1 W 350 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60813**	3000 K	130 lm	**W**	diffused	**00**
			4000 K	140 lm	**N**		

Suggested electronics

89144	89145	99115	99114
ON/OFF 1 - 2 art.	ON/OFF 3 - 6 art.	1-10V/PUSH 1-15 art.	DALI/PUSH 1-15 art.

Suggested accessories



60830	60837
Shim	Outer casing

Gypsum_WR2 | Recessed lights | 1 x powerLED 1 W 350 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60815**	3000 K	130 lm	**W**	diffused	**00**
			4000 K	140 lm	**N**		

Suggested electronics

89144	89145	99115	99114
ON/OFF 1 - 2 art.	ON/OFF 3 - 6 art.	1-10V/PUSH 1-15 art.	DALI/PUSH 1-15 art.

Suggested accessories



60830	60837
Shim	Outer casing

Gypsum_WRQ | Recessed lights | 1 x powerLED 1 W 350 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60814**	3000 K	130 lm	**W**	diffused	**00**
			4000 K	140 lm	**N**		

Suggested electronics

89144	89145	99115	99114
ON/OFF 1 - 2 art.	ON/OFF 3 - 6 art.	1-10V/PUSH 1-15 art.	DALI/PUSH 1-15 art.

Suggested accessories



60830	60837
Shim	Outer casing

Gypsum_WRX | Recessed lights | 1 x powerLED 1 W 350 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60910**	3000 K	130 lm	**W**	diffused	**00**
			4000 K	140 lm	**N**		

Suggested electronics

89144	89145	99115	99114
ON/OFF 1 - 2 art.	ON/OFF 3 - 6 art.	1-10V/PUSH 1-15 art.	DALI/PUSH 1-15 art.

Suggested accessories



60830	60837
Shim	Outer casing

Gypsum_WR3 | Recessed lights | 1 x powerLED 1 W 350 mA

C.C. IP40 O.C. IP20



type			colour			optics	
White	CRI 80	**60811**	3000 K	130 lm	**W**	diffused	**00**
			4000 K	140 lm	**N**		

Suggested electronics

89144	89145	99115	99114
ON/OFF 1 - 2 art.	ON/OFF 3 - 6 art.	1-10V/PUSH 1-15 art.	DALI/PUSH 1-15 art.

Suggested accessories



60830	60837
Shim	Outer casing



Gypsum_WF

Invisible step light

Wall lighting cuts, available in three dimensions, to illuminate passages. Chalk flush frame with recessed fixed optics allows to have fascinating light effects.

+ light cuts
+ three formal options
+ LED source



Gypsum_WF1 | Recessed lights | 1 x powerLED 1 W 350 mA

C.C. IP40 O.C. IP20



For masonry installation you must purchase the recessed outer casing in addition to the lamp.

type			colour			optics	
White	CRI 80	**60920**	3000 K	130 lm	**W**	**70°**	**70**
			4000 K	140 lm	**N**		

Suggested electronics

89144	89145	99115	99114
ON/OFF 1 - 2 art.	ON/OFF 3 - 6 art.	1-10V/PUSH 1-15 art.	DALI/PUSH 1-15 art.

Suggested accessories



60830	61270
Shim	Outer casing

Gypsum_WF2 | Recessed lights | 1 x powerLED 1 W 350 mA

C.C. IP40 O.C. IP20



For masonry installation you must purchase the recessed outer casing in addition to the lamp.

type			colour			optics	
White	CRI 80	**60930**	3000 K	130 lm	**W**	**70°**	**70**
			4000 K	140 lm	**N**		

Suggested electronics

89144	89145	99115	99114
ON/OFF 1 - 2 art.	ON/OFF 3 - 6 art.	1-10V/PUSH 1-15 art.	DALI/PUSH 1-15 art.

Suggested accessories



60830	61280
Shim	Outer casing

Gypsum_WF3 | Recessed lights | 220-240 V | 1 x powerLED 2 W 500 mA

IP40 O.C. IP20



For masonry installation you must purchase the recessed outer casing in addition to the lamp.

type			colour			optics	
White	CRI 80	**60680**	3000 K	170 lm	**W**	**70°**	**70**
			4000 K	180 lm	**N**		

Suggested accessories



60830	64180
Shim	Outer casing

Gypsum_WF4 | Recessed lights | 220-240 V | 4 x powerLED 8 W 500 mA



For masonry installation you must purchase the recessed outer casing in addition to the lamp.

type			colour			optics	
White	CRI 80	**61390**	3000 K	576 lm	**W**	diffused	**00**
			4000 K	720 lm	**N**		

Suggested accessories

60830
Shim

61290
Outer casing

Gypsum_WF4 | Recessed lights | 220-240 V | 1xGx24q-3



For masonry installation you must purchase the recessed outer casing in addition to the lamp.

type			source	optics
White		**60940**	1xGx24q-3 32W Max	diffused

Suggested accessories

60830
Shim

61290
Outer casing

Lighting.system

Lighting.system

Mini-Outline

Mini-Outline_MP



146

Mini-Outline_MS

146

Mini-Outline_MF

152

Mini-Outline_MFY

154

Shore

Shore _MP
mono-emission



166

Shore _MP
bi-emission

170

Shore _MS



176

Outline_MF

Outline_MF

184

Lighting.system

High performance for offices and operative spaces

Continuous and modular lighting lines, flush recessed and linear suspensions are the best fixtures for contemporary and minimal operative spaces projects. Thanks to their essential esthetic presence, they represent the ideal lighting system to create geometrical luminous games or very functional continuous compositions. These fixtures are defined by a great versatility and adaptability to every workspace and total integration with the architecture. These elements are suitable to light up, without leaks, the worktop surface, light is just where needed. Coordinated and completed series is available, flush recessed, ceiling or suspension.

Range	Size (mm)	Modules (mm)	Electronics
Mini-Outline	 	2005 mm 40,5 / 45 mm 1505 mm 40,5 / 45 mm 1005 mm 40,5 / 45 mm 140/532 mm 45 mm	ON / OFF DALI
Shore		2005 mm 60 mm 1505 mm 60 mm 1005 mm 60 mm 540 mm 60 mm	ON / OFF DALI
Outline		2005 mm 91 mm 1505 mm 91 mm 1005 mm 91 mm 555 mm 91 mm	ON / OFF DALI

Emission


Diffused light
(Opaline)
Diffused light
(Opaline)
Diffused light
(Opaline)


Controlled light
(Microprisms)
Diffused light
(Opaline)
Controlled light
(Microprisms)
Diffused light
(Opaline)
Controlled light
(Microprisms)
Diffused light
(Opaline)

Diffused light
(Opaline)

Modular. Light. **Mini-Outline**

new

Mini-Outline

Complete range
(recessed, surface or suspension)

A complete range answers all installations' range. Mini-Outline is available: recessed, surface or suspension installation.



On measure lighting

We can provide special length modules to satisfy all the specific project needs.
For each module the cuts may be required both linear (10 cm intervals) or with variable angle.

Suspension

Ceiling light

Recessed



Visual comfort

The linear structure defines the fixture, provides two lateral items' integration, coated in a special "optical black" finish, ensuring a perfect luminous control. The fixture's diffuser is set back, inside the case to emphasize user's visual comfort. Attention to details defines our market approach.

Asymmetric emission

A special cover fitted on the diffusing screen of the recessed profile allows to direct the light beam towards the walls, thus creating an asymmetric distribution that uniformly wraps the surface, while reducing contrasts and enhancing the width of the rooms.



The simplicity of this system allows you to add easily in any context.

A diffused light combined with a compact profile section is the ideal solution to enhance passageway areas and meeting rooms or to give a contemporary touch to residential settings and retail spaces.

new

Mini-Outline_M

Surface and suspension modules

A complete system fitted to be installed on the surface or suspended.
Simply select a starting “master” module, either a suspension or a surface version; the configuration can then be completed with “slave” modules, which are available in three standard lengths: 1005 / 1505 / 2005mm.
Anodized or painted extruded aluminum profile with sealing plugs. Opaline PMMA diffuser.
High performance topLED wiring. Drivers included.
End caps, junction kit and suspension cables are available as accessories.



Complete element version

240 / 306

Mini-Outline_MP MASTER | Lines | 198-264 V | topLED 21,5 W 700 mA

IP40



Master

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**64765**	3000 K	3030 lm	**W**	diffused	**00**

DIMMABLE

type			colour			optics	
White	CRI 80	**64766**	3000 K	3030 lm	**W**	diffused	**00**

DALI Push DIM

Mini-Outline_MS MASTER | Lines | 198-264 V | topLED 21,5 W 700 mA

IP40



Master

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**64767**	3000 K	3030 lm	**W**	diffused	**00**

DIMMABLE

type			colour			optics	
White	CRI 80	**64768**	3000 K	3030 lm	**W**	diffused	**00**

DALI Push DIM

Mini-Outline_MPS SLAVE | Lines | 100-264 V | topLED 14,5 W 500 mA

IP40



Slave

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**64769**	3000 K	2020 lm	**W**	diffused	**00**

DIMMABLE

type			colour			optics	
White	CRI 80	**64772**	3000 K	2020 lm	**W**	diffused	**00**

DALI Push DIM

Mini-Outline_MPS SLAVE | Lines | 198-264 V | topLED 21,5 W 700 mA

IP40



Slave

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**64770**	3000 K	3030 lm	**W**	diffused	**00**

DIMMABLE

type			colour			optics	
White	CRI 80	**64773**	3000 K	3030 lm	**W**	diffused	**00**

DALI Push DIM

Mini-Outline_MPS SLAVE | Lines | 198-264 V | topLED 29 W 1050 mA

IP40



Slave

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**64771**	3000 K	4040 lm	**W**	diffused	**00**

DIMMABLE

type			colour			optics	
White	CRI 80	**64774**	3000 K	4040 lm	**W**	diffused	**00**

DALI Push DIM

Blind corner



type	L mm	
White	140	**64775**

ACCESSORIES AND LAYOUT

Maximum length for single supply 50 mt



64776
Suspension
L 2000 mm
1 pc

64777
End caps
2 pcs



new

Mini-Outline_MF

Recessed modules

The modular versions for recessed housing allow to create continuous light lines with an extremely low impact. The series includes two lighting curves for ceiling/wall and ceiling/ceiling mounting. A special module with asymmetric emission completes the range and gives the possibility to accurately manage the lighting of vertical surfaces.

Complete element version

240

Mini-Outline_MF | Lines | 100-264 V | topLED 14,5 W 500 mA

IP40





ON / OFF

type			colour		optics	
White	CRI 80	**59464**	3000 K	2020 lm **W**	diffused	**00**

DIMMABLE

type			colour		optics	
White	CRI 80	**59460**	3000 K	2020 lm **W**	diffused	**00**

DALI Push DIM

To be completed with dedicated installation accessories

Mini-Outline_MF | Lines | 198-264 V | topLED 21,5 W 700 mA

IP40



ON / OFF

type			colour		optics	
White	CRI 80	**59394**	3000 K	3030 lm **W**	diffused	**00**

DIMMABLE

type			colour		optics	
White	CRI 80	**59461**	3000 K	3030 lm **W**	diffused	**00**

DALI Push DIM

To be completed with dedicated installation accessories

Mini-Outline_MF | Lines | 198-264 V | topLED 29 W 1050 mA

IP40





ON / OFF

type			colour		optics	
White	CRI 80	**59474**	3000 K	4040 lm **W**	diffused	**00**

DIMMABLE

type			colour		optics	
White	CRI 80	**59462**	3000 K	4040 lm **W**	diffused	**00**

DALI Push DIM

To be completed with dedicated installation accessories

Mini-Outline_MF vertical corner | Lines | 100-264 V | topLED 14,5 W 500 mA

IP40



ON / OFF

type			colour		optics	
White	CRI 80	**59494**	3000 K	2020 lm **W**	diffused	**00**

DIMMABLE

type			colour		optics	
White	CRI 80	**59463**	3000 K	2020 lm **W**	diffused	**00**

DALI Push DIM

To be completed with dedicated installation accessories

Mini-Outline_MF left corner | Lines | 100-264 V | topLED 14,5 W 500 mA

IP40



41 x 530 x 530

ON / OFF

type			colour		optics	
White	CRI 80	**59094**	3000 K	2020 lm **W**	diffused	**00**

DIMMABLE

type			colour		optics	
White	CRI 80	**59466**	3000 K	2020 lm **W**	diffused	**00**

DALI Push DIM

To be completed with dedicated installation accessories

Mini-Outline_MF right corner | Lines | 100-264 V | topLED 14,5 W 500 mA

IP40



41 x 530 x 530

ON / OFF

type			colour		optics	
White	CRI 80	**59484**	3000 K	2020 lm **W**	diffused	**00**

DIMMABLE

type			colour		optics	
White	CRI 80	**59467**	3000 K	2020 lm **W**	diffused	**00**

DALI Push DIM

To be completed with dedicated installation accessories

ACCESSORIES AND LAYOUT

Maximum length for single supply 50 mt

62180
Junction
2 pcs



62160
End caps + 3
poles connector
2 pcs



62161
End caps + 5
poles connector
2 pcs



Mini-Outline_MFY | Lines | 100-264 V | topLED 14,5 W 350 mA

IP40



Asymmetric

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**64004**	3000 K	2020 lm	**W**	Asym.	**07**

DIMMABLE

type			colour			optics	
White	CRI 80	**64001**	3000 K	2020 lm	**W**	Asym.	**07**

DALI Push DIM

Mini-Outline_MFY | Lines | 198-264 V | topLED 21,5 W 500 mA

IP40





Asymmetric

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**64014**	3000 K	3030 lm	**W**	Asym.	**07**

DIMMABLE

type			colour			optics	
White	CRI 80	**64002**	3000 K	3030 lm	**W**	Asym.	**07**

DALI Push DIM

Mini-Outline_MFY | Lines | 198-264 V | topLED 29 W 700 mA

IP40



Asymmetric

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**64024**	3000 K	4040 lm	**W**	Asym.	**07**

DIMMABLE

type			colour			optics	
White	CRI 80	**64003**	3000 K	4040 lm	**W**	Asym.	**07**

DALI Push DIM

Light. Line. Shore

new

Shore

Range

A lighting system must guaratees the best application versatility. Shore is now available in two coordinated versions prepared for ceiling or suspension installation.



On measure lighting

We can provide special length modules to satisfy all the specific project needs.
For each module the cuts may be required both linear (10 cm intervals) or with variable angle.

Suspension

Mono emission

Dual emission

Ceiling light



Different emissions based on the visual task required

Three different light effects create countless combinations, the ideal solution for all project needs. Direct light version ensures minimal visual impact combined with high-level performance.
The integrated reflector, in extra pure polished aluminum, captures all the light emitted by LED sources. These are in-house developed by our laboratories, maximizing fixture's emissions.



Visual comfort

Two different screens (opal or micro-prismatic) define the possibility of a custom-made lighting emission. On demand, a special accessory integrated inside the fixture, allows to reduce the UGR value below 19, respecting the EN12646-1 current law





The values shown are approximate and refer to a typical installation with integrated microprismatic screen.



Light details

The dual-emission versions have a double lighting room; the integrated wiring is prepared to separate the two ignitions control and management.
The upper compartment takes advantage from the Lambertian emission obtaining a soft indirect lighting, emphasizing the living space and ensuring user's greater visual comfort. The opal screen is defined by a thin luminous line creating a pleasant visual effect, embellishing installation.

Suggested Admission
The amount you pay is up to you.
Adults $25
Seniors (65 and over) $17
Students $12
Members Join Today! Free
Children (under 12) Free
Please be as generous as you can.
Special exhibitions included.
Audio Guide
Rent here, save time.
Sales Tax included.
Regular $7
Members $6
Children (under 12) $5
Supported by
Bloomberg
Philanthropies
What's On The Met Breuer
2nd Floor
In the arbus
in the beginning
What's On The Met Fifth Avenue & Cloisters
Exhibitions
Events
MANUS×MACHINA
Fashion in an Age of Technology
Now open late on
Friday and Saturday
evenings until 9 pm

Custom made.

On request we can provide the lighting system with special versions tailored on the project needs.

new

Shore_MP

Suspension modules

Suspension versions allow to be extremely flexible when it comes to manage room lighting. Available in two alternative lighting layouts (mono and dual-emission), modules create versatile and highly functional lighting settings. The aesthetics of the double emission versions features a lighting detail along the upper wall, which draws a fine lighting path in the space.

The dual-emission versions incorporate a singular switching control: maximum emission control, maximum consumption savings.

Complete element version

304

Shore_MP MASTER | Lines | 198-264 V | topLED 28 W 700 mA

IP40



Master

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**63106**	3000 K	4210 lm	**W**	diffused	**00**
			4000 K	4600 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63107**	3000 K	4210 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	4600 lm	**N**		

Shore_MP SLAVE | Lines | 198-264 V | topLED 20 W 500 mA

IP40



Slave

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**63120**	3000 K	2885 lm	**W**	diffused	**00**
			4000 K	3145 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63121**	3000 K	2885 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	3145 lm	**N**		

Shore_MP SLAVE | Lines | 198-264 V | topLED 28 W 700 mA

IP40



Slave

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**63136**	3000 K	4210 lm	**W**	diffused	**00**
			4000 K	4600 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63137**	3000 K	4210 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	4600 lm	**N**		

Shore_MP SLAVE | Lines | 198-264 V | topLED 42,5 W 1050 mA

IP40



Slave

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**63150**	3000 K	5770 lm	**W**	diffused	**00**
			4000 K	6290 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63151**	3000 K	5770 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	6290 lm	**N**		

Shore_MP SLAVE left corner | Lines | 198-264 V | topLED 20 W 500 mA

IP40



Slave

ON / OFF

type			colour			optics	
White	CRI 80	**63180**	3000 K	2885 lm	**W**	diffused	**00**
			4000 K	3145 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63181**	3000 K	2885 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	3145 lm	**N**		

To be completed with dedicated installation accessories

Shore_MP SLAVE right corner | Lines | 198-264 V | topLED 20 W 500 mA

IP40



Slave

ON / OFF

type			colour			optics	
White	CRI 80	**63166**	3000 K	2885 lm	**W**	diffused	**00**
			4000 K	3145 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63167**	3000 K	2885 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	3145 lm	**N**		

To be completed with dedicated installation accessories

ACCESSORIES AND LAYOUT

Maximum length for single supply 50 mt

64776
Suspension
L 2000 mm
1 pc



63199
Junction
2 pcs



63198
End caps
2 pcs



Linear Opal Diffusers

L mm	
1005	**63100**
1505	**63101**
2005	**63102**
2510	**63103**
3010	**63112**

Angular Opal Diffusers

L mm	
538	**63113**



Linear Microprismatic Diffusers

L mm	
1005	**63123**
1505	**63132**
2005	**63133**
2510	**63142**
3010	**63143**

Angular Microprismatic Diffusers

L mm	
538	**63122**

UGR Filter

L mm	
1505	**63128**



Shore_MP MASTER bi-emission | Lines | 198-264 V | topLED 14 W 500 mA UP + topLED 28 W 700 mA DOWN



Master

ON / OFF

type			colour			optics	
White	CRI 80	**63116**	3000 K	6050 lm	**W**	diffused	**00**
			4000 K	6610 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63117**	3000 K	6050 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	6610 lm	**N**		

To be completed with dedicated installation accessories

Shore_MP SLAVE bi-emission | Lines | 198-264 V | topLED 10 W 350 mA UP + topLED 20 W 500 mA DOWN



Slave

ON / OFF

type			colour			optics	
White	CRI 80	**63130**	3000 K	4145 lm	**W**	diffused	**00**
			4000 K	4515 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63131**	3000 K	4145 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	4515 lm	**N**		

To be completed with dedicated installation accessories

Shore_MP SLAVE bi-emission | Lines | 198-264 V | topLED 14 W 500 mA UP + topLED 28 W 700 mA DOWN



Slave

ON / OFF

type			colour			optics	
White	CRI 80	**63146**	3000 K	6050 lm	**W**	diffused	**00**
			4000 K	6610 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63147**	3000 K	6050 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	6610 lm	**N**		

To be completed with dedicated installation accessories

Shore_MP SLAVE bi-emission | Lines | 198-264 V | topLED 19,5 W 700 mA UP + topLED 42,5 W 1050 mA DOWN



Slave

ON / OFF

type			colour			optics	
White	CRI 80	**63160**	3000 K	8285 lm	**W**	diffused	**00**
			4000 K	9035 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63161**	3000 K	8285 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	9035 lm	**N**		

To be completed with dedicated installation accessories

Shore_MP SLAVE bi-emission left corner | Lines | 198-264 V | topLED 10 W 350 mA UP + topLED 20 W 500 mA DOWN



Slave

ON / OFF

type			colour			optics	
White	CRI 80	**63190**	3000 K	4145 lm	**W**	diffused	**00**
			4000 K	4515 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63191**	3000 K	4145 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	4515 lm	**N**		

To be completed with dedicated installation accessories

Shore_MP SLAVE bi-emission right corner | Lines | 198-264 V | topLED 10 W 350 mA UP + topLED 20 W 500 mA DOWN



Slave

ON / OFF

type			colour			optics	
White	CRI 80	**63176**	3000 K	4145 lm	**W**	diffused	**00**
			4000 K	4515 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63177**	3000 K	4145 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	4515 lm	**N**		

To be completed with dedicated installation accessories

* ACCESSORIES AND LAYOUT

Maximum length for single supply 50 mt

64776
Suspension
L 2000 mm
1 pc



63199
Junction
2 pcs

63197
End caps
2 pcs



Linear Opal Diffusers

L mm	
1005	**63100**
1505	**63101**
2005	**63102**
2510	**63103**
3010	**63112**

Angular Opal Diffusers

L mm	
538	**63113**



Linear Microprismatic Diffusers

L mm	
1005	**63123**
1505	**63132**
2005	**63133**
2510	**63142**
3010	**63143**

Angular Microprismatic Diffusers

L mm	
538	**63122**

UGR Filter

L mm	
1505	**63128**



new

Shore_MS

Ceiling/wall mounted modules

The versions for surface installation offer high flux performance and efficiency. They can be installed using specific brackets that allow to obtain continuous lighting configurations both on the ceiling and on the wall. A special flexible template (available as an accessory) simplifies the installation in a continuous row, thus optimizing the mounting time of the system.

Shore_MS MASTER | Lines | 198-264 V | topLED 28 W 700 mA

IP40



Master

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**63110**	3000 K	4210 lm	**W**	diffused	**00**
			4000 K	4600 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63111**	3000 K	4210 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	4600 lm	**N**		

Shore_MS SLAVE | Lines | 198-264 V | topLED 20 W 500 mA

IP40



Slave

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**63126**	3000 K	2885 lm	**W**	diffused	**00**
			4000 K	3145 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63127**	3000 K	2885 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	3145 lm	**N**		

Shore_MS SLAVE | Lines | 198-264 V | topLED 28 W 700 mA

IP40



Slave

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**63140**	3000 K	4210 lm	**W**	diffused	**00**
			4000 K	4600 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63141**	3000 K	4210 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	4600 lm	**N**		

Shore_MS SLAVE | Lines | 198-264 V | topLED 42,5W 1050 mA

IP40



Slave

To be completed with dedicated installation accessories

ON / OFF

type			colour			optics	
White	CRI 80	**63156**	3000 K	5770 lm	**W**	diffused	**00**
			4000 K	6290 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63157**	3000 K	5770 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	6290 lm	**N**		

Shore_MS SLAVE Left Corner | Lines | 198-264 V | topLED 20 W 500 mA

IP40



Slave

ON / OFF

type			colour			optics	
White	CRI 80	**63186**	3000 K	2885 lm	**W**	diffused	**00**
			4000 K	3145 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63187**	3000 K	2885 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	3145 lm	**N**		

To be completed with dedicated installation accessories

Shore_MS SLAVE right corner | Lines | 198-264 V | topLED 20 W 500 mA

IP40



Slave

ON / OFF

type			colour			optics	
White	CRI 80	**63170**	3000 K	2885 lm	**W**	diffused	**00**
			4000 K	3145 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**63171**	3000 K	2885 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	3145 lm	**N**		

To be completed with dedicated installation accessories

ACCESSORIES AND LAYOUT

Maximum length for single supply 50 mt

63153
Fixing kit
1 pc



63196
Fixing base
1 pc



63199
Junction
2 pcs



63198
End caps
2 pcs



Linear Opal Diffusers

L mm	
1005	**63100**
1505	**63101**
2005	**63102**
2510	**63103**
3010	**63112**

Angular Opal Diffusers

L mm	
538	**63113**



Linear Microprismatic Diffusers

L mm	
1005	**63123**
1505	**63132**
2005	**63133**
2510	**63142**
3010	**63143**

Angular Microprismatic Diffusers

L mm	
538	**63122**

UGR Filter

L mm	
1505	**63128**



The versatility of a system allows to enhance any project.

The installation of the modules in a continuous row together with the single modules creates a certain rhythm in the room and makes it easy to customize also the simplest spaces.

Outline_MF

Linear light

Linear lighting elements with unlimited composition solutions to create continuous lines and corners. Anodized or coated extruded aluminium casing and polycarbonate diffusers. Wiring included with LED source.

Complete element version

236

Outline_MF

New version

The whole Outline range has been upgraded with new lighting units and new lengths. Opaline screens matching the profiles are available with lengths up to 3 metres, this highlights the perception of a seamless lighting line that can outline the space with a diffused and performing emission.



On measure lighting

We can provide special length modules to satisfy all the specific project needs.
For each module the cuts may be required both linear (10 cm intervals) or with variable angle.


Linear recessed
module 1505 mm
Diffusing opaline
screen 2005 mm

Outline_MF | Lines | 198-264 V | topLED 20 W 500 mA

IP40



ON / OFF

type			colour			optics	
White	CRI 80	**60100**	3000 K	2885 lm	**W**	diffused	**00**
			4000 K	3145 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**60101**	3000 K	2885 lm	**W**	diffused	**00**
DALI, Push to DIM			4000 K	3145 lm	**N**		

To be completed with dedicated installation accessories

Outline_MF | Lines | 198-264 V | topLED 28 W 700 mA

IP40

ON / OFF

type			colour			optics	
White	CRI 80	**60102**	3000 K	4210 lm	**W**	diffused	**00**
			4000 K	4600 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**60103**	3000 K	4210 lm	**W**	diffused	**00**
DALI, Push to DIM			4000 K	4600 lm	**N**		

To be completed with dedicated installation accessories

Outline_MF | Lines | 198-264 V | topLED 42,5 W 1050 mA

IP40



ON / OFF

type			colour			optics	
White	CRI 80	**60110**	3000 K	5770 lm	**W**	diffused	**00**
			4000 K	6290 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**60111**	3000 K	5770 lm	**W**	diffused	**00**
DALI, Push to DIM			4000 K	6290 lm	**N**		

To be completed with dedicated installation accessories

Outline_MF left corner | Lines | 198-264 V | topLED 20 W 500 mA

IP40



ON / OFF

type			colour			optics	
White	CRI 80	**60120**	3000 K	2885 lm	**W**	diffused	**00**
			4000 K	3145 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**60121**	3000 K	2885 lm	**W**	diffused	**00**
DALI, Push to DIM			4000 K	3145 lm	**N**		

To be completed with dedicated installation accessories

Outline_MF right corner | Lines | 198-264 V | topLED 20 W 500 mA

IP40



ON / OFF

type			colour			optics	
White	CRI 80	**60112**	3000 K	2885 lm	**W**	diffused	**00**
			4000 K	3145 lm	**N**		

DIMMABLE

type			colour			optics	
White	CRI 80	**60113**	3000 K	2885 lm	**W**	diffused	**00**
DALI Push DIM			4000 K	3145 lm	**N**		

To be completed with dedicated installation accessories

ACCESSORIES AND LAYOUT

Maximum length for single supply 50 mt

60164
End caps
2pcs



63199
Junction
2 pcs



60127
Electrical connector (on-off)



60128
Electrical connector (DALI)



Straight Opal Diffusers

L mm	
1005	**60107**
1505	**60108**
2005	**60109**
2510	**60117**
3010	**60118**

Angular Opal Diffusers

L mm	
555	**60119**



Wall + Ceiling

Wall + Ceiling

Cell

Cell_1 198

Cell_2 198

Cell_3 198

Rada

Rada_R1 206

Rada_R2 206

Rada_R3 206

Rada_R4 206

Rada_R5 207

Rada_R6 207

Rada_RO1 207

Rada_RO2 207

Rada_R03 208

Rada_R04 208

Rada_Q1 208

Rada_Q2 208

Pool

Pool_C1 218

Pool_C2 218

Pool_C3 219

Pool_CR1 222

Pool_CR2 222

Pool_S1 224

Pool_S2 224

Pool_S3 225

Plik

Plik_R1 232

Plik_R2 232

Plik_RX 232

Plik_Q1 233

Plik_Q2 233

Plik_QX 233

Outline_F

Outline_F 237

Mini-Outline

Mini-Outline_F 243

Mini-Outline_S 243

Orient

Orient_S



249

Hive_W

Hive_W

253

Linear

Linear_1

255

Linear_2

255

Linear_3

255

Linear_4

255

Dual

Dual_W1



259

Dual_W2

259

Mini-Dual

Mini-Dual



261

Point

Point_S1

263

Point_S2

263

Wall

Wall_1

266

Wall_2

266

Wall_3

266

Wall + Ceiling

Coordinated light

Perfect for living or hospitality lighting projects, centered on diffusive and ambience lighting over walls or ceiling. Dimensions and shapes options allow a light, permeating the place, that captures details and gives depth to materials designing the architectural space. Suspension or ceiling lighting is defined in different customized options creating functional and elegant luminous compositions.





Invisible. Smart. **Cell**

new

Cell

Invisible light

Multi-optical spotlight to be installed in false ceilings and available in three direct light versions: rectangular with 3 and 6 spots, square with 9 spots. Matt white painted aluminum frame. Suitable for accent lighting.
Special cut-off cells grant an extreme visual comfort for users. Magnetic fastening, recessed and screened LED source.

+ super compact recessed
+ controlled luminance
+ LED source
+ double finish of the optical compartment



Gypsum version

60

Cell_1 | Downlights | 3 x powerLEDs 2 W | 6 W 700 mA

C.C. IP20



type			colour			optics	
White	CRI 90	**64541**	3000 K	747 lm	**W**	15°	**15**
Black	CRI 80	**64540**	4000 K	795 lm	**N**	30°	**30**

Suggested electronics

62437	62439	99115	99114	99344
ON/OFF 1 art.	ON/OFF 2-4 art.	1-10V/PUSH 1-3 art.	DALI/PUSH 1-3 art.	DALI/PUSH 1-4 art.

Cell_2 | Downlights | 6 x powerLEDs 2 W | 12 W 700 mA

C.C. IP20



type			colour			optics	
White	CRI 90	**64543**	3000 K	1494 lm	**W**	15°	**15**
Black	CRI 80	**64542**	4000 K	1590 lm	**N**	30°	**30**

Suggested electronics



62438	62439	99115	99114	99344
ON/OFF 1 art.	ON/OFF 1-2 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.	DALI/PUSH 1-2 art.

Cell_3 | Downlights | 9 x powerLEDs 2 W | 18 W 700 mA

C.C. IP20



type			colour			optics	
White	CRI 90	**64545**	3000 K	2241 lm	**W**	15°	**15**
Black	CRI 80	**64544**	4000 K	2385 lm	**N**	30°	**30**

Suggested electronics

62439	99115	99114
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Antiglare. Innovative. **Rada**

new

Rada

Concept

The round shape precision contrasts with the square modularity, creating a downlight complete range, proposing a new lighting approach for passages and large spaces

+ indirect emission
+ ceiling or wall mounted
+ LED source



Rada

Visual comfort

Rada ensures a total direct glare absence. The light emitted by the special LED round board is reflected by domed diffuser, defining the fixture and spreads around the space. Look up isn't a problem with this technology, perfect for all the spaces in which the user is forced to look up to the ceiling (hospital, wellness centre or gym).



Range

The round shape precision contrasts with the square modularity, creating a downlight complete range, proposing a new lighting approach for passages and large spaces.

Rada_RO

Rada_R



Rada_Q

L 212 L 362

Ø 116 Ø 177 Ø 233 Ø 310 Ø 600 Ø 800

Emission control

Distribution largeness and control are the undisputed downlight strengths. The emission opening more than 100° providing vertical planes flood, with its diffused, perfectly uniform and homogeneous lighting. The different configurations available provide a “round” or a “stronger” distribution, both designed to increase passages illuminance values.





The emission opening more than 100° providing vertical planes flood, with its diffused, perfectly uniform and homogeneous lighting.



α > 100°

Shadows control

The indirect lighting principle guarantees a perfect shadow control inside the living spaces. Multiple and clear projections vanish, replaced by smooth and diffusive shadows.

Rada_R1 | Downlights | topLED 8W 220 mA

C.C. IP40



type			colour			optics	
White	CRI 80	**91992**	2700 K	955 lm	**M**	diffused	**00**
Black	CRI 80	**91993**	3000 K	1022 lm	**W**		
			4000 K	1070 lm	**N**		

Suggested electronics



99368	**99116**	**99131**
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Rada_R2 | Downlights | topLED 12W 350 mA

C.C. IP40



type			colour			optics	
White	CRI 80	**91996**	2700 K	1642 lm	**M**	diffused	**00**
Black	CRI 80	**91997**	3000 K	1680 lm	**W**		
			4000 K	1795 lm	**N**		

Suggested electronics



99260	**99262**	**99163**
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Rada_R3 | Downlights | topLED 18W 500 mA

C.C. IP40



type			colour			optics	
White	CRI 80	**92000**	2700 K	2462 lm	**M**	diffused	**00**
Black	CRI 80	**92001**	3000 K	2520 lm	**W**		
			4000 K	2693 lm	**N**		

Suggested electronics



99162	**99262**	**99163**
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Rada_R4 | Downlights | topLED 25W 720 mA

C.C. IP40



type			colour			optics	
White	CRI 80	**92004**	2700 K	3283 lm	**M**	diffused	**00**
Black	CRI 80	**92005**	3000 K	3360 lm	**W**		
			4000 K	3590 lm	**N**		

Suggested electronics

99112	**99188**	**99330**
ON/OFF 1 art.	1-10V, DALI PUSH 1 art.	DALI/PUSH 1 art.

Rada_R5 | Downlights | topLED 70 W 1950 mA

C.C. IP40



107

type			colour			optics	
White	CRI 80	**93854**	2700 K	9101 lm	**M**	diffused	**00**
Black	CRI 80	**93855**	3000 K	9754 lm	**W**		
			4000 K	10214 lm	**N**		

Suggested electronics

99099

ON/OFF
1 art.

Rada_R6 | Downlights | topLED 100 W 2600 mA

C.C. IP40



169

type			colour			optics	
White	CRI 80	**93862**	2700 K	13200 lm	**M**	diffused	**00**
Black	CRI 80	**93863**	3000 K	14064 lm	**W**		
			4000 K	14688 lm	**N**		

Suggested electronics



99101

ON/OFF
1 art.

Rada_RO1 | Downlights | topLED 8W 220 mA

C.C. IP40



107

type			colour			optics	
White	CRI 80	**91990**	2700 K	955 lm	**M**	diffused	**00**
Black	CRI 80	**91991**	3000 K	1022 lm	**W**		
			4000 K	1070 lm	**N**		

Suggested electronics

99368

ON/OFF
1 art.



99116

1-10V/PUSH
1 art.



99131

DALI/PUSH
1 art.

Rada_RO2 | Downlights | topLED 12W 350 mA

C.C. IP40



169

type			colour			optics	
White	CRI 80	**91994**	2700 K	1642 lm	**M**	diffused	**00**
Black	CRI 80	**91995**	3000 K	1680 lm	**W**		
			4000 K	1795 lm	**N**		

Suggested electronics

99260

ON/OFF
1 art.



99262

1-10V/PUSH
1 art.



99163

DALI/PUSH
1 art.

Rada_RO3 | Downlights | topLED 18W 500 mA

C.C. IP40



type			colour			optics	
White	CRI 80	**91998**	2700 K	2462 lm	**M**	diffused	**00**
Black	CRI 80	**91999**	3000 K	2520 lm	**W**		
			4000 K	2693 lm	**N**		

Suggested electronics



99260	**99262**	**99163**
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Rada_RO4 | Downlights | topLED 25W 720 mA

C.C. IP40



type			colour			optics	
White	CRI 80	**92002**	2700 K	3283 lm	**M**	diffused	**00**
Black	CRI 80	**92003**	3000 K	3360 lm	**W**		
			4000 K	3590 lm	**N**		

Suggested electronics



99112	**99188**	**99330**
ON/OFF 1 art.	1-10V, DALI PUSH 1 art.	DALI/PUSH 1 art.

Rada_Q1 | Downlights | topLED 12W 350 mA

C.C. IP40



type			colour			optics	
White	CRI 80	**92432**	2700 K	1706 lm	**M**	diffused	**00**
Black	CRI 80	**92433**	3000 K	1829 lm	**W**		
			4000 K	1915 lm	**N**		

Suggested electronics



99260	**99262**	**99163**
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Rada_Q2 | Downlights | topLED 23W 630 mA

C.C. IP40



type			colour			optics	
White	CRI 80	**92434**	2700 K	2866 lm	**M**	diffused	**00**
Black	CRI 80	**92435**	3000 K	3067 lm	**W**		
			4000 K	3211 lm	**N**		

Suggested electronics



99261	**99262**	**99163**
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

Circular. Comfortable. **Pool**

Pool

Design with light

Rigorous design circular lamps, flush mounted diffuser. LED source provides a direct lighting, available for recessed, ceiling or suspension installation. Perfect for ambient lighting, diffusive and comfortable. Available in two dimensions, for free disposition and arrangement.

+ rigorous and essential design
+ invisible ceiling recessed
+ emotional light

Suspended version

290

Effect light

Circular elements with diffusers that are perfectly flush with the casing. LED and fluorescent direct light to be fitted in the recessed, suspension or ceiling mounted versions. Pool offers optimum interior lighting with appealing light circles, comfortable and soft, for a better definition of space.



Complete range

Three different diameters allow to play with light and shapes, thus interpreting each time the style of the architectural space and granting unique matching aesthetics.



Multiple installation

Pool provides a solution for any project needs; it does not matter what kind of installation is required (recessed, surface or suspension), the body disappears from the sight, while the broad polycarbonate diffuser grants a low luminance, thus producing a soft and comfortable light; or it can also create a suggestive light circle thanks to the version with the perimeter circular diffuser.



Furnishing with light

Lighting technology meets the precision of design. Visual comfort finds its most rational form, creating spectacular effects with the simplicity of pure geometry.



Minimal design

A neat and minimal shape creates the typical light disks of Pool. Light conquers the space by enhancing its beauty and life and extending it to a modern view of the living style, where everything responds to a precise project inspired from innovation.

Pool_C1 | Recessed lights | 100-240 V | topLED 20 W 500 mA



type			colour			optics	
White	CRI 80	**62931**	3000 K	2730 lm	**W**	diffused	**00**
			4000 K	2925 lm	**N**		

Pool_C1 | Recessed lights | 99-264 V | topLED 20 W 500 mA



type			colour			optics	
White	CRI 80	**62934**	3000 K	2730 lm	**W**	diffused	**00**
			4000 K	2925 lm	**N**		

Pool_C2 | Recessed lights | 220-240 V | topLED 60 W 500 mA



type			colour			optics	
White	CRI 80	**62932**	3000 K	8190 lm	**W**	diffused	**00**
			4000 K	8775 lm	**N**		

Pool_C2 | Recessed lights | 220-240 V | topLED 60 W 500 mA



type			colour			optics	
White	CRI 80	**62935**	3000 K	8190 lm	**W**	diffused	**00**
			4000 K	8775 lm	**N**		

Pool_C3 | Recessed lights | 220-240 V | topLED 120 W 500 mA

IP20



type			colour			optics	
White	CRI 80	**62933**	3000 K	16380 lm	**W**	diffused	**00**
			4000 K	17550 lm	**N**		

Pool_C3 | Recessed lights | 220-240 V | topLED 120 W 500 mA

Push DIM DALI IP20



type			colour			optics	
White	CRI 80	**62936**	3000 K	16380 lm	**W**	diffused	**00**
			4000 K	17550 lm	**N**		

X1
BMW X1
BMW Auto Maro

Pool_CR1 | Recessed lights | 220-240 V | topLED 14 W 350 mA

IP20



type			colour			optics	
White	CRI 80	**62927**	3000 K	1820 lm	**W**	diffused	**00**
			4000 K	1980 lm	**N**		

Pool_CR2 | Recessed lights | 220-240 V | topLED 40 W 500 mA

IP20



type			colour			optics	
White	CRI 80	**62928**	3000 K	5460 lm	**W**	diffused	**00**
			4000 K	5850 lm	**N**		

Pool_S1 | Ceiling Lights | 100-240 V | topLED 20 W 500 mA



type			colour			optics	
White	CRI 80	**62911**	3000 K	2730 lm	**W**	diffused	**00**
			4000 K	2925 lm	**N**		

Pool_S1 | Ceiling Lights | 99-264 V | topLED 20 W 500 mA



type			colour			optics	
White	CRI 80	**62923**	3000 K	2730 lm	**W**	diffused	**00**
			4000 K	2925 lm	**N**		

Pool_S2 | Ceiling Lights | 220-240 V | topLED 60 W 500 mA



type			colour			optics	
White	CRI 80	**62912**	3000 K	8190 lm	**W**	diffused	**00**
			4000 K	8775 lm	**N**		

Pool_S2 | Ceiling Lights | 220-240 V | topLED 60 W 500 mA



type			colour			optics	
White	CRI 80	**62922**	3000 K	8190 lm	**W**	diffused	**00**
			4000 K	8775 lm	**N**		

Pool_S3 | Ceiling Lights | 220-240 V | topLED 120 W 500 mA



type			colour			optics	
White	CRI 80	**62915**	3000 K	16380 lm	**W**	diffused	**00**
			4000 K	17550 lm	**N**		

Pool_S3 | Ceiling Lights | 220-240 V | topLED 120 W 500 mA



type			colour			optics	
White	CRI 80	**62925**	3000 K	16380 lm	**W**	diffused	**00**
			4000 K	17550 lm	**N**		

Effect. Light. **Plik**

new

Plik

Precious details and essential shapes

A ceiling spotlight, with an essential and complementary shape, plus LED source. Optical unit with convex extra clear glass lens, this for smoothing the light beam. Aluminum lacquered case with high resistance varnish: colors are available in extra matte finish, perfect for all contemporary living spaces. Bicolor finish is for optical group and lamp.

+ optical convex lens
+ LED source
+ bicolor finishes



Plik_R1 | Ceiling Lights | 176-264 V | arrayLED 7,5 W 200 mA

IP40

Ø 80

120

type			colour			optics	
White	CRI 80	**64747**	3000 K	1117 lm	**W**	60°	**60**
White Bk	CRI 80	**64749**	4000 K	1153 lm	**N**		
White Au	CRI 80	**64738**					

Plik_R2 | Ceiling Lights | 176-264 V | arrayLED 7,5 W 200 mA

IP40

Ø 80

200

type			colour			optics	
White	CRI 80	**64748**	3000 K	1117 lm	**W**	60°	**60**
White Bk	CRI 80	**64750**	4000 K	1153 lm	**N**		
White Au	CRI 80	**64751**					

Plik_RX | Ceiling Lights | 220-240 V | 1xGU10

IP40

Ø 80

155

LED

type		source	optics
White	**59434**	1xGU10 35W Max	variable
Grey	**59435**		

Plik_Q1 | Ceiling Lights | 176-264 V | arrayLED 7,5 W 200 mA



type			colour			optics	
White	CRI 80	**64756**	3000 K	1117 lm	**W**	60°	**60**
White Bk	CRI 80	**64745**	4000 K	1153 lm	**N**		
White Au	CRI 80	**64739**					

Plik_Q2 | Ceiling Lights | 176-264 V | arrayLED 7,5 W 200 mA



type			colour			optics	
White	CRI 80	**64757**	3000 K	1117 lm	**W**	60°	**60**
White Bk	CRI 80	**64746**	4000 K	1153 lm	**N**		
White Au	CRI 80	**64740**					

Plik_QX | Ceiling Lights | 220-240 V | 1xGU10



type		source	optics
White	**59404**	1xGU10 35W Max	variable
Grey	**59405**		

LED

Outline_F

Minimal linear light

Linear lighting element with an extra thin frame, it is invisible when recessed on counter walls or counter ceilings. Extruded aluminum profile, painted or anodized, polycarbonate opal white diffuser. Equipped with topLED high efficiency sources. Drivers included.

Outline System

184

Outline_F | Lines | 198-264 V | topLED 28 W 700 mA

IP40



type			colour			optics	
White	CRI 80	**60122**	3000 K	4210 lm	**W**	diffused	**00**
			4000 K	4600 lm	**N**		

Outline_F | Lines | 198-264 V | topLED 28 W 700 mA

Push DIM DALI IP40



type			colour			optics	
White	CRI 80	**60123**	3000 K	4210 lm	**W**	diffused	**00**
			4000 K	4600 lm	**N**		

Lines. Installation. **Mini-Outline**

Mini-Outline

Minimal linear light

Linear lighting element with an extra thin frame, it is invisible when recessed on counter walls or counter ceilings. There are available horizontal or vertical installations. Extruded aluminum profile, painted or anodized, polycarbonate opal white diffuser. Equipped with topLED high efficiency sources. Drivers included.

+ minimum linear recessed
+ LED source

Mini-Outline System

144 / 150

Mini-Outline_F | Lines | 198-264 V | topLED 21,5 W 700 mA

IP40



type			colour			optics	
White	CRI 80	**59694**	3000 K	3030 lm	**W**	diffused	**00**

Mini-Outline_S | Lines | 198-264 V | topLED 21,5 W 700 mA

IP20



type			colour			optics	
White	CRI 80	**64780**	3000 K	3030 lm	**W**	diffused	**00**

Mini-Outline_S | Lines | 198-264 V | topLED 21,5 W 700 mA

Push to DIM DALI IP20



type			colour			optics	
White	CRI 80	**64781**	3000 K	3030 lm	**W**	diffused	**00**



Move. See. Orient

Orient

Adjustable bar

A dynamic and minimal lighting ceiling bar, it is adjustable on horizontal axis. Being a sectional series it allows free geometrical compositions and diffuse light spread. Linear fluorescent source with direct emission.

+ adjustable bar
+ minimum dimensions
+ LED source

Orient_S | Ceiling Lights | 220-240 V | topLED 27 W 700 mA

IP40





type			colour			optics	
White	CRI 80	**64234**	3000 K	3569 lm	**W**	diffused	**00**
Grey	CRI 80	**64235**	4000 K	3780 lm	**N**		

Square. Cell. **Hive**

Hive_W

Versatile lighting

Double emission wall lamp. The polycarbonate "cells" grid diffuser allows lower UGR values and a perfect antiglare control. Double emission with diversified light beams. Varnished aluminum case provided by last generation LED source.

+ double emission
+ antiglare control
+ slim design

Suspension/Free Standing

310

Hive_W | Wall Lights | 200-240 V | topLED 18W (down) + arrayLED 5W (up) 500 mA



type			colour			optics	
White	CRI 80	**63294**	4000 K	2751 lm	**N**	diffused	**00**

Linear

Grazing light

A wall lighting bar, aluminum brushed body and diffuser in antiglare PMMA - for a detailed and grazing lighting needs - is perfect for passages and corridors.
It's available for both vertical or horizontal installation.
Fluorescent T16 source and electronic adaptor are included.

+ grazing light
+ anodized aluminum



Linear_1 | Wall Lights | 220-240 V | 2xG5

type		source	optics
Anod. Al.	**4740**	2xG5 24W Max	diffused

Linear_2 | Wall Lights | 220-240 V | 2xG5



type		source	optics
Anod. Al.	**4741**	2xG5 39W Max	diffused

Linear_3 | Wall Lights | 220-240 V | 2xG5



type		source	optics
Anod. Al.	**4742**	2xG5 54W Max	diffused

Linear_4 | Wall Lights | 220-240 V | 2xG5



type		source	optics
Anod. Al.	**4743**	2xG5 80W Max	diffused

Bi-emission to highlight volumes.

The compact and slender shape allows to use Linear in any situation. Available with lengths up to 1.5 metres, this wall light is extremely versatile and functional.

Dual

Essential shape

Wall mounted luminaire characterized by a pure and essential shape, ideal for applications in hospitality and residential. Equipped with arrayLed sources, this product provides light graphics effects in dual emission.

+ decorative light
+ minimal design
+ arrayLED sources

Installation example



Dual_W1 | Wall Lights | 220-240V | 2 arrayLED 3W | 6W 350 mA



type			colour			optics	
White	CRI 80	**64511**	3000 K	810 lm	**W**	90°+24°	**94**
Grey	CRI 80	**64512**					

Dual_W2 | Wall Lights | 220-240V | 2 arrayLED 3W | 6W 350 mA



type			colour			optics	
White	CRI 80	**64598**	3000 K	810 lm	**W**	90°	**90**
Grey	CRI 80	**64599**					



Mini-Dual

Wall light adjustable

Modular, adjustable and turning wall lamps,
these are suitable for accent or detailed lighting.
Customizable aluminum rectangular extruded case
with minimum dimensions.

+ adjustable on its axis
+ minimum dimensions
+ LED source

Installation example

The body lamp can rotate by 180°
on the installation plan.



Mini-Dual | Wall Lights | 190-250 V | 2 x powerLED 4 W 500 mA

type			colour			optics	
White	CRI 80	**57154**	3000 K	360 lm	**W**	adjus.	**85**
Grey	CRI 80	**57155**					

Point

Adjustable accent light

A spot with independent, adjustable and flexible optical groups which follow all project requirement: it is ideal for efficient accent lighting in exhibition spaces, and wall or ceiling installation.
Aluminum case with lacquered or chromed steel details.
Electronic driver is included.

+ optical groups indipendent
+ adjustable and flexible



Point_S1 | Ceiling Lights | 220-240 V | 1xG53



type		source	optics
White	**59520**	1xG53 12W Max	variable
Grey	**59521**		

Article to be completed with pre-focused LED light sources.

Point_S2 | Ceiling Lights | 220-240 V | 2xG53



type		source	optics
White	**59522**	2xG53 12W Max	variable
Grey	**59523**		

Article to be completed with pre-focused LED light sources.

Wall

Floor washer

Recessed wall lamp with customizable finishes. It is available in four sizes which allow a higher flexibility of use.
The lamp is perfect as indirect decorative light or step light for passages or corridors. High efficiency LED source.

+ indirect light
+ wall recessed
+ LED source

Wall_1 | Wall Lights | 220-240 V | arrayLED 3,2 W 350 mA

IP20



type			colour			optics	
White	CRI 80	**63674**	3000 K	436 lm	**W**	diffused	**00**

Accessories suggested

51790

Outer casing

Wall_2 | Wall Lights | 220-240 V | topLED 5,5 W 150 mA

IP20



type			colour			optics	
White	CRI 80	**63684**	3000 K	839 lm	**W**	diffused	**00**

Accessories suggested

51780

Outer casing

Wall_3 | Wall Lights | 220-240 V | topLED 5,5 W 150 mA

IP20



type			colour			optics	
White	CRI 80	**63694**	3000 K	839 lm	**W**	diffused	**00**

Accessories suggested

51770

Outer casing

Floor + Suspension

Floor + Suspension

Tour

Tour_PD1

283

Tour_PD2

283

Tour_PD3

283

Tour_PD4

283

Tour_PI1

284

Tour_PI2

284

Tour_PI3

284

Tour_PU1

285

Tour_PU2

285

Tour_PU3

285

Tour_PU4

285

Pool_P

Pool_P1

292

Pool_P2

292

Baton

Baton_P1

300

Baton_P2

300

Baton_P3

300

Baton_P4

300

Shore

Shore_P

305

Mini-Outline

Mini-Outline_P

307

Hive

Hive_P

314

Hiv_FL

314

Neox

Neox_P

318

Neox_FL



318

Matrix

Matrix_P

320

Floor + Suspension

Functional and versatile lighting

Perfect lighting solution for contemporary offices, for double height volumes or spaces in which the cohesion between a great functionality and an efficient but simple decoration is needed. The architectural space enhances values thanks to a customized and adaptive lighting, answering to all designers' needs. Available suspension or floor versions, fixtures guarantee highest visual comfort and perfect luminance on worktop surfaces.

Circle. Round. **Tour**

new

Tour

Rigorous harmony

Circular suspension, severe and essential, aluminum body and opal diffuser, provided by topLED source internal power supply, warm and diffusive light. Three lighting options: direct, indirect and peripheral. Available in two installations option, parallel or stayed cables.

+ essential design
+ different lightin options
+ LED source

Construction details

Thanks to the latest generation machinery, we are able to control every minimum stretching sections' deformation due to the curvature. Tour's frame is composed by a calendered and powder coated extruded aluminum.
No power cable is visible, the topLEDs are powered by special extra thin steel suspension cables.
A special patented snap system provides installation of the opal polycarbonate screen along the profile, eliminating all visible joints.

Range

Four different diameters defined by an extra slim section, makes this suspension very light and neutral, a perfect solution when a wide and diffusive lighting is needed.



2450 mm 1470 mm 940 mm 740 mm

Emissions

Tour proposes three different emissions: direct, indirect and lateral. Three combinable lighting effects, able to transform spaces with a single minimal and contemporay sign of light.



Installation

Installation system provides different solutions for every application: Tour can be installed with convergent cable in a single central point or with customized tiege designed to maintain a perfect perpendicular cables' traction.
Ideal solution when multiple composition is needed.



Alimentazione speciale e Celiachia

@Mamma e bimbo
Biocalm
NOVARTIS

Configuration with central ceiling rose

Implementation of a Tour_PD layout with ON / OFF ceiling rose.

Tour model selection



Ceiling rose selection



Final outcome



Order example:

n.1 art. 64570W00 (Tour_PD1) **+** n.1 art. 64574 (ON/OFF)

Configuration with remote driver

Implementation of a Tour_PU layout with DALI remote driver.

Tour model selection



Suspension kit selection

Driver selection

Final outcome



Order example:

n.1 art. 64570W00 (Tour_PD1) **+** n.1 art. 64575 (Suspensions) **+** n.1 art. 84700 (driver ON/OFF)
n.1 art. 99074 (DALI/1-10V controller)

Tour_PD1 | Pendant Luminaires | topLED 36,5 W 24 V

C.V. IP40



type		colour			optics	
White	**64570**	3000 K	4678 lm	**W**	diffused	**00**
Black	**65112**					
Nickel	**65113**					
Concrete	**65114**					
Bronze	**65115**					
Rose gold	**65128**					

Direct emission

Pag. 286

Installation accessories

84700 Switching 24V ON/OFF

99074 DALI/1-10V controller

99077 PUSH controller

Tour_PD2 | Pendant Luminaires | topLED 45 W 24 V

C.V. IP40



type		colour			optics	
White	**64571**	3000 K	5847 lm	**W**	diffused	**00**
Black	**65116**					
Nickel	**65117**					
Concrete	**65118**					
Bronze	**65119**					
Rose gold	**65129**					

Direct emission

Pag. 286

Installation accessories

84700 Switching 24V ON/OFF

99074 DALI/1-10V controller

99077 PUSH controller

Tour_PD3 | Pendant Luminaires | topLED 70 W 24 V

C.V. IP40



type		colour			optics	
White	**64572**	3000 K	9355 lm	**W**	diffused	**00**
Black	**65120**					
Nickel	**65121**					
Concrete	**65122**					
Bronze	**65123**					
Rose gold	**65130**					

Direct emission

Pag. 286

Installation accessories

84700 Switching 24V ON/OFF

99074 DALI/1-10V controller

99077 PUSH controller

Tour_PD4 | Pendant Luminaires | topLED 114 W 24 V

C.V. IP40



type		colour			optics	
White	**64573**	3000 K	15588 lm	**W**	diffused	**00**
Black	**65124**					
Nickel	**65125**					
Concrete	**65126**					
Bronze	**65127**					
Rose gold	**65131**					

Direct emission

Pag. 286

Installation accessories



84701 Switching 24V ON/OFF

64576 DALI converter

99332 1-10V

Tour_PI1 | Pendant Luminaires | stripLED 29 W 24 V

III C.V. IP40



type		colour			optics	
White	**64577**	3000 K	3000 lm	**W**	diffused	**00**
Black	**65100**					
Nickel	**65101**					
Concrete	**65102**					
Bronze	**65103**					
Rose gold	**65132**					

Internal side emission

Pag. 286

Installation accessories

84700 Switching 24V ON/OFF

99074 DALI/1-10V controller

99077 PUSH controller

Tour_PI2 | Pendant Luminaires | stripLED 35,5 W 24 V

III C.V. IP40



type		colour			optics	
White	**64579**	3000 K	3785 lm	**W**	diffused	**00**
Black	**65104**					
Nickel	**65105**					
Concrete	**65106**					
Bronze	**65107**					
Rose gold	**65133**					

Internal side emission

Pag. 286

Installation accessories

84700 Switching 24V ON/OFF

99074 DALI/1-10V controller

99077 PUSH controller

Tour_PI3 | Pendant Luminaires | stripLED 57,5 W 24 V

III C.V. IP40



type		colour			optics	
White	**64581**	3000 K	6000 lm	**W**	diffused	**00**
Black	**65108**					
Nickel	**65109**					
Concrete	**65110**					
Bronze	**65111**					
Rose gold	**65134**					

Internal side emission

Pag. 286

Installation accessories

84700 Switching 24V ON/OFF

99074 DALI/1-10V controller

99077 PUSH controller

Tour_PU1 | Pendant Luminaires | topLED 36,5 W 24 V

III C.V. IP40



Indirect emission

type		colour			optics	
White	**64583**	3000 K	4678 lm	**W**	diffused	**00**
Black	**64682**					
Nickel	**64683**					
Concrete	**64684**					
Bronze	**64685**					
Rose gold	**65135**					

Pag. 286
Installation accessories

84700
Switching 24V ON/OFF

99074
DALI/1-10V controller

99077
PUSH controller

Tour_PU2 | Pendant Luminaires | topLED 45 W 24 V

III C.V. IP40



Indirect emission

type		colour			optics	
White	**64584**	3000 K	5847 lm	**W**	diffused	**00**
Black	**64686**					
Nickel	**64687**					
Concrete	**64688**					
Bronze	**64689**					
Rose gold	**65136**					

Pag. 286
Installation accessories

84700
Switching 24V ON/OFF

99074
DALI/1-10V controller

99077
PUSH controller

Tour_PU3 | Pendant Luminaires | topLED 70 W 24 V

III C.V. IP40



Indirect emission

type		colour			optics	
White	**64585**	3000 K	9355 lm	**W**	diffused	**00**
Black	**64690**					
Nickel	**64691**					
Concrete	**64692**					
Bronze	**64693**					
Rose gold	**65137**					

Pag. 286
Installation accessories

84700
Switching 24V ON/OFF

99074
DALI/1-10V controller

99077
PUSH controller

Tour_PU4 | Pendant Luminaires | topLED 114 W 24 V

III C.V. IP40



Indirect emission

type		colour			optics	
White	**64587**	3000 K	15588 lm	**W**	diffused	**00**
Black	**64694**					
Nickel	**64695**					
Concrete	**64696**					
Bronze	**64697**					
Rose gold	**65138**					

Pag. 286
Installation accessories

84701
Switching 24V ON/OFF



64576
DALI converter

99332
1-10V

Ceiling rose





type	suitable for PD1 - PI1 - PU1	ON/OFF	DALI 1-10 V
White	64570 - 64577 - 64583	**64574**	**64582**
Black	65112 - 65100 - 64682	**64674**	**64678**
Nickel	65113 - 65101 - 64683	**64675**	**64679**
Concrete	65114 - 65102 - 64684	**64676**	**64680**
Bronze	65115 - 65103 - 64685	**64677**	**64681**
Rosegold	65128 - 65132 - 65135	**65139**	**65140**

Ceiling rose





type	suitable for PD2 - PI2 - PU2 PD3 - PI3 - PU3	ON/OFF	DALI 1-10 V
White	64571 - 64572 - 64579 - 64581 - 64584 - 64585	**64578**	**64586**
Black	65116 - 65104 - 64686 - 65120 - 65108 - 64690	**65142**	**65143**
Nickel	65117 - 65105 - 64687 - 65121 - 65109 - 64691	**65144**	**65145**
Concrete	65118 - 65106 - 64688 - 65122 - 65110 - 64692	**65146**	**65147**
Bronze	65119 - 65107 - 64689 - 65123 - 65111 - 64693	**65148**	**65149**
Rosegold	65129 - 65133 - 65136 - 65130 - 65134 - 65137	**65150**	**65151**

Ceiling rose





type	suitable for PD4 - PI4 - PU4	ON/OFF	DALI 1-10 V
White	64573 - 64587	**64580**	**64588**
Black	65124 - 64694	**65152**	**65153**
Nickel	65125 - 64695	**65154**	**65155**
Concrete	65126 - 64696	**65156**	**65157**
Bronze	65127 - 64697	**65158**	**65159**
Rosegold	65131 - 65138	**65160**	**65161**

Fastening kit





type	
White	**64575**
Black	**64670**
Nickel	**64671**
Concrete	**64672**
Bronze	**64673**
Rosegold	**65141**



Circle. Round. **Pool**

Pool_P

Design with light

Rigorous design circular lamps, flush mounted diffuser. LED source provides a direct lighting, available for recessed, ceiling or suspension installation. Perfect for ambient lighting, diffusive and comfortable. Available in two dimensions, for free disposition and arrangement.

+ rigorous and essential design
+ LED source



Ceiling light version

212

Pool_P1 | Pendant Luminaires | 220-240 V | topLED 60 W 500 mA



type			colour			optics	
White	CRI 80	**62916**	3000 K	8190 lm	**W**	diffused	**00**
			4000 K	8775 lm	**N**		

Pool_P1 | Pendant Luminaires | 220-240 V | topLED 60 W 500 mA



type			colour			optics	
White	CRI 80	**62926**	3000 K	8190 lm	**W**	diffused	**00**
			4000 K	8775 lm	**N**		

Pool_P2 | Pendant Luminaires | 220-240 V | topLED 120 W 500 mA



type			colour			optics	
White	CRI 80	**62921**	3000 K	16380 lm	**W**	diffused	**00**
			4000 K	17550 lm	**N**		

Minimal design

A neat and minimal shape creates the typical light disks of Pool. Light conquers the space, by enhancing its beauty and life and extending it to a modern view of the living style, where everything responds to a precise project inspired from innovation.

Suspension. Metal. **Baton**

new

Baton

Fairly light

Lacquered aluminum cylindrical suspension, available in different diameter, length and finishes. Perfect as single lighting point creating sophisticated and refined atmospheres, also installed in compositions defined by different dimensions, finish or height. Lighting control is provided by a special integrated lens; the visual comfort is guaranteed by LED source set back.

+ visual comfort
+ finishes and dimensions variety
+ LED source

Range

Two sections of two different lengths feature the available versions of the range. Baton is extremely minimal if used on its own, but it can become extremely spectacular if combined in a multiple composition, playing with the various available shapes. Fastening is not limited to a pre-set point, but it can change according to the installer's needs.



Controlled emission

Baton creates highly contrasting lighting effects. The lens integrated in the light casing generates a light beam of about 50°, whose distinguishing feature is neat edges so it is possible to highlight any illuminated item. The recessed position of the LED makes this suspension extremely comfortable to the sight, that is why it is perfect, for example, to light up bar counters and tables.



Finishes

Aluminum bodies, which are powder coated with a matt white finish, blend in perfectly well with the architectural space. The inside of the optical unit gives a gentle touch of colour to the product, available in matt black and matt gold.



Matt white/black **exterior**
Optical black/matt **gold interior**





Baton_P1 | Pendant Luminaires | 220-240 V | arrayLED 7,3 W 200 mA

IP40



type			colour			optics	
White Bk	CRI 80	**64742**	3000 K	1117 lm	**W**	70°	**70**
White Au	CRI 80	**64741**	4000 K	1153 lm	**N**		
Black Au	CRI 80	**64754**					

Baton_P2 | Pendant Luminaires | 220-240 V | arrayLED 7,3 W 200 mA

IP40



type			colour			optics	
White Bk	CRI 80	**64744**	3000 K	1117 lm	**W**	70°	**70**
White Au	CRI 80	**64743**	4000 K	1153 lm	**N**		
Black Au	CRI 80	**64755**					

Baton_P3 | Pendant Luminaires | 220-240 V | arrayLED 3 W 250 mA

IP40



type			colour			optics	
White Bk	CRI 80	**64785**	3000 K	298 lm	**W**	50°	**50**
White Au	CRI 80	**64786**	4000 K	298 lm	**N**		
Black Au	CRI 80	**64787**					

Baton_P4 | Pendant Luminaires | 220-240 V | arrayLED 3 W 250 mA

IP40



type			colour			optics	
White Bk	CRI 80	**64782**	3000 K	298 lm	**W**	50°	**50**
White Au	CRI 80	**64783**	4000 K	298 lm	**N**		
Black Au	CRI 80	**64784**					

Shore

Dual emission light

Stand-alone suspension with dual emission equipped with LED sources. The lighting fixture is fitted with a differentiated switching system. Embossed white painted extruded aluminum profile, featuring sealing plugs and an opal PMMA diffuser.

+ LED source
+ dual emission
+ slim profile

Shore System

164

Shore_P | Pendant Luminaires | 198-264 V | topLED 14 W 500 mA UP + topLED 28 W 700 mA DOWN



type			colour			optics	
White	CRI 80	**63134**	3000 K	6050 lm	**W**	diffused	**00**
			4000 K	6610 lm	**N**		

Shore_P | Pendant Luminaires | 198-264 V | topLED 14 W 500 mA UP + topLED 28 W 700 mA DOWN



type			colour			optics	
White	CRI 80	**63144**	3000 K	6050 lm	**W**	diffused	**00**
			4000 K	6610 lm	**N**		

Mini-Outline

Linear light

Stand-alone suspension with direct emission equipped with LED sources. The lighting fixture features an extra-slim profile. Recessed opal PMMA diffuser. Embossed white painted extruded aluminum profile, featuring sealing plugs and suspension cables with micrometric adjustment.

+ LED source
+ recessed diffuser
+ slim profile

Mini-Outline System

144

Mini-Outline_P | Pendant Luminaires | 198-264 V | topLED 21,5 W 700 mA



type			colour			optics	
White	CRI 80	**64778**	3000 K	3030 lm	**W**	diffused	**00**

Mini-Outline_P | Pendant Luminaires | 198-264 V | topLED 21,5 W 700 mA



type			colour			optics	
White	CRI 80	**64779**	3000 K	3030 lm	**W**	diffused	**00**



Performing. Thin. **Hive**

Hive

Versatile lighting

Office and desk versatile lamps. The “cells” grid diffuser allows lower UGR values, with the possibility to have different versions, offers numbers of functional advantages. Available in three options: floor, suspension or wall. Double emission with diversified beams, higher one for the indirect light. All versions have an excellent balance between energy safe, operative performance and efficiency, due to last generation LED source.

+ auto dimmable
+ presence sensor
+ slim design

Wall light version

252

Controlled emission

In the floor versions, two elements grant the best control of the emission: integrated anti-glare grid with square-shaped cells made from glossy black printed polycarbonate for the control of direct light. Motion sensor and ambient light detector to optimize consumptions and correctly run the system.

Ultra thin design

The design of the optics is ultra thin.
Just 21mm of thickness make the lighting fixture almost invisible in an office.
Every detail of Hive has been developed to highlight the lightness of the product: the shapes of the base, the neat shaft and the special grid with square-shaped cells defining the emitting surface.



Designed for offices

A coordinated and complete range to perfectly meet any office needs.
Suspensions and wall versions are a great solution for the lighting of meeting rooms and shared areas, since they provide high comfort and efficiency. The stand alone floor versions allow to shift the lighting point at any time, following the actual arrangement of desks in an open space.



Reticular diffuser.
Motion sensor and ambient light detector.

Dual emission

All the available versions of the range match an excellent control of direct glare with an indirect light. The dual emission grants an outstanding visual comfort and affects users' psychophysical wellbeing.
The indirect light component is Lambertian, it evenly illuminates the ceiling, it contributes to smoothen the shades and it increases the perception of the spaces.





The values stated are approximate and refer to a typical installation with an integrated microprismatic screen.

Hive_P | Pendant Luminaires | 220-240 V | topLED 36 W (down) + arrayLED 9 W (up) 500 mA



type			colour			optics	
White	CRI 80	**63254**	4000 K	5430 lm	**N**	diffused	**00**

Hive_FL | Free Standing | 220-240 V | topLED 38 W (down) + arrayLED 18 W (up) 500 mA



type			colour			optics	
White	CRI 80	**63274**	4000 K	6330 lm	**N**	diffused	**00**

Motion sensor included

Hive_FL | Free Standing | 220-240 V | topLED 38 W (down) + arrayLED 18 W (up) 500 mA



type			colour			optics	
White	CRI 80	**63264**	4000 K	6330 lm	**N**	diffused	**00**

Henri Cartier Bresson
NEOCLASSICO

Neox

Light at work

Office sustainable, efficient and ergonomic light, thanks to LED or fluorescent last generation sources.
Available in two different options, floor or suspension, that one in two versions: diffuser flush or set back.
The large opal diffuser surface allows a homogenous light diffusion, antiglare maintaining complaint lighting levels.
Contemporary design shapes, finishes and materials, easily to fit in every operative space.

+ auto dimmable
+ presence sensor

Neox_P | Pendant Luminaires | 198-264 V | topLED 51 W 1400 mA



type			colour			optics	
White	CRI 80	**61814**	4000 K	8209 lm	**N**	diffused	**00**
Grey	CRI 80	**61815**					

Neox_FL | Free Standing | 99-264 V | topLED 45 W 1050 mA



type			colour			optics	
White	CRI 80	**61834**	4000 K	5720 lm	**N**	diffused	**00**
Grey	CRI 80	**61835**					

Neox_FL | Free Standing | 110-240 V | topLED 45 W 1050 mA



type			colour			optics	
White	CRI 80	**61824**	4000 K	5720 lm	**N**	diffused	**00**
Grey	CRI 80	**61825**					

Motion sensor included

Matrix

Minimum profile

Double emission suspension,
with LED source.
Extruded lacquered aluminum case.
Micro-prismatic PMMA diffuser or in
antiglare polycarbonate.

+ LED source
+ UGR <19
+ slim profile

Matrix_P | Pendant Luminaires | 220-240 V | topLED 56 W 700 mA



type			colour			optics	
White	CRI 80	**54274**	4000 K	5601 lm	**N**	diffused	**00**
Grey	CRI 80	**54275**					

Cable.system

Cable.system

300 System

Trix-C30

Trix-C30

332

Matrix-C30

Matrix-C30_1

334

Matrix-C30_2

334

Matrix-C30_3

334

Matrix-C30_4

334

Orion-C30

Orion-C30

335

Orion-C30J

335

Point-C30

Point-C30

335

Vega-C30

Vega-C30_1



336

Vega-C30_2



336

Vega-C30_3



366

Modular-C30

Modular-C30_4

336

150 System

Self-C15

Self-C15_RJ

346

Self-C15_R

346

Matrix-C15

Matrix-C15

348

Orion-C15

Orion-C15_Q

348

Orion-C15_J

348

Orion-C15_R

348

Point-C15

Point-C15

348

Halley-C15

Halley-C15_1

350

Halley-C15_2

350

Halley-C15_J1

350

Halley-C15_J2

350

Bell-15

Bell-C15

351

Mono System

Orient-C

Orient-C_1

358

Orient-C_2

358

Orient-C_3

358

Orient-C_4

358

Point-C

Point-C

359

Andromeda-C

Andromeda-C_1

360

Andromeda-C_2

360

Tek-C

Tek-C_1

360

Tek-C_2

360

Virgo-C

Virgo-C

361

Bell-C

Bell-C

361

300 System

Structural lightness

The 300 System wire track lighting system is the ideal solution to install lighting fixtures wherever the materials and the setting must remain unaltered. Two parallel tension wires, placed between two walls, 300 mm apart from each other, provide support and power to the lighting fixtures: they form an installation level from which both accent and ambient lighting can be created to meet any need, also using different light sources.
Moreover, it allows for the luminaires to be easily moved, added or removed. Flexibility, ease of installation, balanced aesthetic impact: these are the unrivalled advantages offered by 300 System.

new

Trix-C30



Innovative technology

Trix is an innovative on wires lighting system with 300 mm span. Minimal design, essential and refined shape with technological core OptiLight Technology™, defining a warm and comfortable light. Structurally composed by lacquered aluminum case, containing the LED circuit main grid voltage 220V operating, and a PMMA diffuser laser micro-engraved. The engraves allows indirect light, without leaks. Antiglare effect is provided by a polycarbonate frame sealing the lamp. Powered by cable system.

+ innovative on wires system
+ LED OptiLight Technology™
+ avoiding leaks and antiglare

Optical system

The magic of Trix results from the transformation of the transparent surface into a luminous surface. The incredibly transparent 4 mm thick panel in PMMA shows a special laser engraved texture on the upper surface, which optimises the conveyance and the distribution of the light emission. A soft light without glare, for a total perception of visual comfort.
Ideal for environments that require a high visual comfort (UGR <19), such as the offices where display screens are frequently used.

Optilight Technology ™

Efficient source

Printed circuit board with high-efficiency topLED, positioned for a longitudinal light emission.

OFF

ON

Trix-C30 | Cable System | 220-240 V | topLED 27 W



type			colour			optics	
White	CRI 80	**64733**	3000 K	3520 lm	**W**	diffused	**00**
Grey	CRI 80	**64713**					

Matrix-C30_1 | Cable System | 220-240 V | 2x2G10





type		source	optics
White	**51254**	2x2G10 36W	diffused
Grey	**51255**		

Matrix-C30_2 | Cable System | 220-240 V | topLED 52 W 650 mA



type			colour			optics	
White	CRI 80	**54284**	4000 K	5590 lm	**N**	diffused	**00**
Grey	CRI 80	**54285**					

Matrix-C30_3 | Cable System | 220-240 V | 2xG5



type		source	optics
White	**51234**	2xG5 39W	diffused
Grey	**51235**		

Matrix-C30_4 | Cable System | 220-240 V | 2xG5



type		source	optics
White	**51244**	2xG5 54W	diffused
Grey	**51245**		

Orion-C30 | Cable System | 220-240 V | 1xR7s (114,2mm)

IP40



type		source	optics
Grey	**51535**	1xR7s 200W Max	diffused

Orion-C30J | Cable System | 220-240 V | 1xE27

IP40



LED

type		source	optics
Grey	**51545**	1xE27 100W Max	variable

Point-C30 | Cable System | 220-240 V | 2xG53

IP20



type		source	optics
White	**59530**	2xG53 12W Max	variable
Grey	**59531**		

LED **Article to be completed with pre-focused LED light sources.**

Vega-C30_1 | Cable System | 220-240 V | 1xR7s (114,2mm)

IP40



type		source	optics
Grey	**TR4000-5**	1xR7s 200W Max	diffused
Rust	**TR4000-9**		
Chrome	**TR4000-3**		
Nickel	**TR4000-48**		

Vega-C30_2 | Cable System | 220-240 V | 1xE27

IP20



LED

type		source	optics
Grey	**TR4014-5**	1xE27 100W Max	variable
Chrome	**TR4014-3**		
Nickel	**TR4014-48**		

Vega-C30_3 | Cable System | 220-240 V | 1xE27

IP20



LED

type		source	optics
Rust	**51456**	1xE27 x75W Max	variable

Modular-C30_4 | Cable System | 220-240 V | 2xG5

IP40



type		source	optics
Grey	**TR4008-5**	2xG5 54W Max	diffused

fastening kit Ø 35





type

White	**TR4110-4**
Grey	**TR4110-5**
Rust	**TR4110-9**
Chrome	**TR4110-3**
Nickel	**TR4110-8**

Fastening kit (Ø 35).

fastening kit Ø 50





type

Grey	**TR4108-5**
Chrome	**TR4108-3**
Nickel	**TR4108-8**

Fastening kit (Ø 50).

fastening kit + ceiling rose Ø 35



type

White	**TR4109-4**
Grey	**TR4109-5**
Rust	**TR4109-9**
Chrome	**TR4109-3**
Nickel	**TR4109-8**

Fastening kit with power supply box (Ø 35).

fastening kit + ceiling rose Ø 50



type

Grey	**TR4100-5**
Chrome	**TR4100-3**
Nickel	**TR4100-8**

Fastening kit with power supply box (Ø 50).

R ceiling rose, one conductor



type	L mm	
Grey	1500	**TR4102-5**
Rust	1500	**TR4102-9**
Chrome	1500	**TR4102-3**
Nickel	1500	**TR4102-48**

Ceiling power supply kit, maximum length 150 cm (for one conductor cable).

R ceiling rose, two conductors



type	L mm	
Grey	1500	**TR4107-5**
Rust	1500	**TR4107-9**
Chrome	1500	**TR4107-3**
Nickel	1500	**TR4107-48**

Ceiling power supply kit, maximum length 150 cm (for two conductors cable).

Q ceiling rose, one conductor



type	L mm	
White	1500	**53204**
Grey	1500	**53205**

Ceiling power supply kit, maximum length 150 cm (for one conductor cable).

Q ceiling rose, two conductors



type	L mm	
White	1500	**53214**
Grey	1500	**53215**

Ceiling power supply kit, maximum length 150 cm (for two conductors cable).

couple of R connectors





type	
Chrome	**TR4106-3**
Nickel	**TR4106-48**
Grey	**TR4106-5**

Couple of connectors to power more lines.

couple of Q connectors





type	
Grey	**53225**

Couple of connectors to power more lines.

spacer



type	
White	**TR4101-4**
Grey	**TR4101-5**
Rust	**TR4101-9**
Chrome	**TR4101-3**
Nickel	**TR4101-8**

Linear spacer, height 30 cm (fastening and power supply kit excluded).

support kit



type	L mm	
White	2000	**TR4103-4**
Grey	2000	**TR4103-5**
Rust	2000	**TR4103-9**
Chrome	2000	**TR4103-3**
Nickel	2000	**TR4103-48**

Support kit for line H max 200 cm.

ceiling switch kit



type	L mm	
Grey	1500	**TR4105-5**
Chrome	1500	**TR4105-3**
Nickel	1500	**TR4105-8**

Ceiling switch kit, height 30 cm.

ceiling-wall switch kit



type	
Chrome	**TR4124-3**
Nickel	**TR4124-8**

Ceiling-wall switch kit.

wall switch kit

type	
Chrome	**TR4104-3**
Nickel	**TR4104-8**

Wall switch kit.

supporting cable, one conductor

L mm	
1000	**TR4150**
5000	**TR4150-5**
10000	**TR4150-10**
15000	**TR4150-15**
20000	**TR4150-20**
25000	**TR4150-25**
30000	**TR4150-30**
50000	**TR4150-50**

Supporting cable and one conductor, section 1 x 1,5 mm².

supporting cable, two conductors

L mm	
1000	**TR4151**
5000	**TR4151-5**
10000	**TR4151-10**
15000	**TR4151-15**
20000	**TR4151-20**
25000	**TR4151-25**
30000	**TR4151-30**
50000	**TR4151-50**

Supporting cable and two conductors, section 2 x 1,5 mm².

supporting cable, two copper conductors

L mm	
1000	**TR4152**
5000	**TR4152-5**
10000	**TR4152-10**
15000	**TR4152-15**
20000	**TR4152-20**
25000	**TR4152-25**
30000	**TR4152-30**
50000	**TR4152-50**

Supporting cable and two copper conductors, section 2 x 1,5 mm².

150 System

Structural lightness

The 150 System wire track lighting system is the ideal solution to install lighting fixtures wherever the materials and the setting must remain unaltered.
Two parallel tension wires, placed between two walls, 150 mm apart from each other, provide support and power to the lighting fixtures: they form an installation level from which both accent and ambient lighting can be created to meet any need, also using different light sources. Moreover, flexibility, ease of installation, balanced aesthetic impact: these are the unrivalled advantages offered by 150 System.

new

Self

Efficiency and lightness

Defined by aluminum and PMMA light case. Last generation LED source allows to operate on main grid voltage 220V. Self-RJ is defined by a 50° open optical group, adjustable for an efficient accent lighting. Self-R is perfect for a diffusive lighting solution, thanks to its PMMA micro-prismatic diffuser. Self is perfect for a direct lighting. Provided by a reflecting system generating a soft indirect lighting. Powered by cable system.

+ efficiency and lightness
+ adjustable or diffusive light
+ LED source

Lightweight, with simple lines and discrete proportions.

Self products take full advantage of the performance of the latest LED technology, powered directly by a 220V source for 150mm cable systems. Products from the Self line are characterised by their lightweight structure in polymethylmethacrylate and aluminium. Inside, a technological core enables the latest generation LEDs to be powered directly by a 220V source.



Self-R: an article characterised by a microprismatic PMMA central ring for a direct light, and a reflecting system for generating an ambient light upwards.

Self-RJ is a product with a 50° adjustable optics, for an efficient accent lighting.

Orientable sphere

The spherical section lighting element of the **Self-RJ** is orientable in all directions of 45°.





Self-C15_RJ | Cable System | 220-240 V | arrayLED 10 W



type			colour			optics	
White	CRI 80	**64732**	3000 K	777 lm	**W**	50°	**50**
Grey	CRI 80	**64710**					

Self-C15_R | Cable System | 220-240 V | topLED 13,5 W



type			colour			optics	
White	CRI 80	**64731**	3000 K	1313 lm	**W**	diffused	**00**
Grey	CRI 80	**64709**					

Matrix-C15 | Cable System | 220-240 V | 2xG5



type		source	optics
White	**59134**	2xG5 39W	diffused
Grey	**59135**		

Orion-C15_Q | Cable System | 220-240 V | 1xR7s (74,9 mm)



type		source	optics
Grey	**51635**	1xR7s (74,9 mm)100W Max	diffused

Orion-C15_J | Cable System | 220-240 V | 1xE27



LED

type		source	optics
White	**59114**	1xE27 100W Max	variable
Grey	**59115**		

Orion-C15_R | Cable System | 220-240 V | 1xE27



LED

type		source	optics
Grey	**51755**	1xE27 20W Max	diffused

Accessories

51745-TR

Diffuser

Point-C15 | Cable System | 220-240 V | 1xG53



LED **Article to be completed with pre-focused LED light sources.**

type		source	optics
White	**59532**	1xG53 12W Max	varaible
Grey	**59533**		

Halley-C15_1 | Cable System | 220-240 V | 1xR7s (74,9 mm)

IP20



type		source	optics
Chrome	**TR4200-3**	1xR7s 100W Max	diffused
Nickel	**TR4200-48**		
Rust	**TR4200-9**		

Halley-C15_2 | Cable System | 220-240 V | 1xE27

IP20



LED

type		source	optics
Chrome	**59223**	1xE27 20W Max	diffused
Nickel	**59228**		
Rust	**59229**		

Halley-C15_J1 | Cable System | 220-240 V | 1xGU10

IP20



LED

type		source	optics
Chrome	**TR4201-3**	1xGU10 50W Max	variable
Nickel	**TR4201-48**		
Rust	**TR4201-9**		

Halley-C15_J2 | Cable System | 220-240 V | 1xE27

IP20



LED

type		source	optics
Chrome	**TR4202-3**	1xE27 100W Max	diffused
Nickel	**TR4202-48**		
Rust	**TR4202-9**		

Bell-C15 | Cable System | 220-240 V | 1xE27

IP20



LED

type		source	optics
Rust	**TR4217-9**	1xE27 20W Max	diffused

fastening kit





type	
White	TR4110-4
Grey	TR4110-5
Rust	TR4110-9
Chrome	TR4110-3
Nickel	TR4110-8

Fastening kit.

fastening kit + ceiling rose



type	
White	TR4109-4
Grey	TR4109-5
Rust	TR4109-9
Chrome	TR4109-3
Nickel	TR4109-8

Fastening kit with power supply box.

R ceiling rose, one conductor



type	L mm	
Rust	1500	TR4115-9
Chrome	1500	TR4115-3
Nickel	1500	TR4115-48

Ceiling power supply kit, maximum length 150 cm (for one conductor cable).

R ceiling rose, two conductors



type	L mm	
Rust	1500	TR4116-9
Chrome	1500	TR4116-3
Nickel	1500	TR4116-48

Ceiling power supply kit, maximum length 150 cm (for two conductors cable).

Q ceiling rose, one conductor





type	L mm	
White	1500	53204
Grey	1500	53205

Ceiling power supply kit, maximum length 150 cm (for two conductor cable).

Q ceiling rose, two conductors



type	L mm	
White	1500	53214
Grey	1500	53215

Ceiling power supply kit, maximum length 150 cm (for two conductors cable).

couple of R connectors



type	
Chrome	TR4122-3
Nickel	TR4122-48

Couple of connectors to power more lines.

couple of Q connectors





type	L mm	
Grey	n.a.	53225

Couple of connectors to power more lines.

spacer





type	
White	TR4113-4
Grey	TR4113-5
Rust	TR4113-9
Chrome	TR4113-3
Nickel	TR4113-8

Linear spacer, height 20 cm (fastening and power supply kit excluded).

ceiling switch kit



type	L mm	
Grey	1500	TR4121-5
Rust	1500	TR4121-9
Chrome	1500	TR4121-3
Nickel	1500	TR4121-8

Ceiling switch kit, height 20 cm.

ceiling-wall switch kit



type	
Chrome	TR4124-3
Nickel	TR4124-8

Ceiling-wall switch kit.

wall switch kit

type	
Chrome	TR4104-3
Nickel	TR4104-8

Wall switch kit

support kit



type	L mm	
White	2000	**TR4103-4**
Grey	2000	**TR4103-5**
Rust	2000	**TR4103-9**
Chrome	2000	**TR4103-3**
Nickel	2000	**TR4103-48**

Support kit for line
H max 200 cm.

supporting cable, one conductor

L mm	
1000	**TR4150**
5000	**TR4150-5**
10000	**TR4150-10**
15000	**TR4150-15**
20000	**TR4150-20**
25000	**TR4150-25**
30000	**TR4150-30**
50000	**TR4150-50**

Supporting cable and one conductor, section 1 x 1,5 mm².

supporting cable, two conductors

L mm	
1000	**TR4151**
5000	**TR4151-5**
10000	**TR4151-10**
15000	**TR4151-15**
20000	**TR4151-20**
25000	**TR4151-25**
30000	**TR4151-30**
50000	**TR4151-50**

Supporting cable and two conductors, section 2 x 1,5 mm².

supporting cable, two copper conductors

L mm	
1000	**TR4152**
5000	**TR4152-5**
10000	**TR4152-10**
15000	**TR4152-15**
20000	**TR4152-20**
25000	**TR4152-25**
30000	**TR4152-30**
50000	**TR4152-50**

Supporting cable and two copper conductors, section 2 x 1,5 mm².

Mono System

Structural lightness

The Mono System wire lighting system is the ideal solution to install lighting fixtures wherever the materials and the setting must remain unaltered. A tension wire, placed between two walls, provides support and power to the lighting fixtures: it forms an installation level from which both accent and ambient lighting can be created to meet any need, also using different light sources. Flexibility, ease of installation, balanced aesthetic impact: these are the unrivalled advantages offered by Mono System.



Orient-C_1 | Cable System | 220-240 V | 2xG9

IP20



LED

type		source	optics
White	**59754**	2xG9 40W Max	diffused

Orient-C_2 | Cable System | 220-240 V | 1xGU10

IP20



LED

type		source	optics
White	**59744**	1xGU10 50W Max	variable
Grey	**59745**		

Orient-C_3 | Cable System | 220-240 V | topLED 30 W 700 mA

IP40



type			colour			optics	
White	CRI 80	**64244**	3000 K	3569 lm	**W**	diffused	**00**
Grey	CRI 80	**64245**	4000 K	3780 lm	**N**		

Orient-C_4 | Cable System | 220-240 V | 1xG5

IP40



type		source	optics
White	**59734**	1x54W	diffused
Grey	**59735**		

Point-C | Cable System | 220-240 V | 1xG53



type		source	optics
White	**59538**	1xG53 12W Max	variable
Grey	**59539**		

LED **Article to be completed with pre-focused LED light sources.**

Andromeda-C_1 | Cable System | 220-240 V | 1xGU10

IP20



LED

type		source	optics
Chrome	**TR4304-3**	1xGU10 50W Max	variable
Nickel	**TR4304-48**		
Rust	**TR4304-9**		

Andromeda-C_2 | Cable System | 220-240 V | 1xE27

IP20



LED

type		source	optics
Chrome	**TR4303-3**	1xE27 100W Max	variable
Nickel	**TR4303-48**		
Rust	**TR4303-9**		

Tek-C_1 | Cable System | 220-240 V | 2xG9

IP40



LED

type		source	optics
Chrome	**TR4302-3**	2xG9 40W Max	diffused
Nickel	**TR4302-48**		
Rust	**TR4302-9**		

Tek-C_2 | Cable System | 220-240 V | 1xR7s (114,2 mm)

IP40



type		source	optics
Chrome	**TR4307-3**	1xR7s200W Max	diffused
Nickel	**TR4307-48**		
Rust	**TR4307-9**		

Virgo-C | Cable System | 220-240 V | 1xE27

IP20



LED

type		source	optics
Chrome	**TR4310-3**	1xE27 20W Max	diffused
Nickel	**TR4310-48**		

Bell-C | Cable System | 220-240 V | 1xE27

IP20



LED

type		source	optics
Rust	**TR4317-9**	1xE27 20W Max	diffused

fastening kit + ceiling rose



type

White	**TR4111-4**
Grey	**TR4111-5**
Rust	**TR4111-9**
Chrome	**TR4111-3**
Nickel	**TR4111-8**

Fastening kit with power supply box.

fastening kit



type

White	**TR4112-4**
Grey	**TR4112-5**
Rust	**TR4112-9**
Chrome	**TR4112-3**
Nickel	**TR4112-8**

Fastening kit.

R ceiling rose, one conductor



type	L mm	
Rust	1500	**TR4118-9**
Chrome	1500	**TR4118-3**
Nickel	1500	**TR4118-48**

Ceiling power supply kit, maximum length 150 cm (for one conductor cable).

R ceiling rose, two conductors



type	L mm	
White	1500	**53234**
Grey	1500	**53235**

Ceiling power supply kit, maximum length 150 cm (for two conductors cable).

connector

type

White	**53034**
Grey	**53035**
Chrome	**53033**
Nickel	**53038**

Connector to power Tràddel suspensions of class II, through R4151/TR4152 cable.

couple of connectors



type	L mm	
Chrome	n.a.	**TR4123-3**
Nickel	n.a.	**TR4123-48**

Couple of connectors to power more lines.

spacer





type	
White	TR4114-4
Grey	TR4114-5
Rust	TR4114-9
Chrome	TR4114-3
Nickel	TR4114-8

Linear spacer, height 20 cm (fastening and power supply kit excluded).

wall switch kit

type	
Chrome	TR4120-3
Nickel	TR4120-8

Wall switch kit

ceiling switch kit



type	L mm	
Chrome	1500	TR4117-3
Nickel	1500	TR4117-8
Rust	1500	TR4117-9

Ceiling switch kit, height 20 cm.

support kit

type	L mm	
White	2000	TR4119-4
Grey	2000	TR4119-5
Rust	2000	TR4119-9
Chrome	2000	TR4119-3
Nickel	2000	TR4119-48

Support kit for line H max 200 cm.

supporting cable, two conductors

L mm	
1000	TR4151
5000	TR4151-5
10000	TR4151-10
15000	TR4151-15
20000	TR4151-20
25000	TR4151-25
30000	TR4151-30
50000	TR4151-50

Supporting cable and two conductors, section 2 x 1,5 mm².

supporting cable, two copper conductors

L mm	
1000	TR4152
5000	TR4152-5
10000	TR4152-10
15000	TR4152-15
20000	TR4152-20
25000	TR4152-25
30000	TR4152-30
50000	TR4152-50

Supporting cable and two copper conductors, section 2 x 1,5 mm².

Integrated.lighting

Integrated.lighting

Fylo+ Out

Fylo+ Out Recessed_S

380

Fylo+ Out Recessed_W

380

Fylo+ Out Surface_S



384

Fylo+ Out Surface_W

384

Outdoor architecture or landscape integrated lighting

Functional

Integrated lighting allows to customize outdoor architecture by blending in with it until it disappears. This is particularly immediate and functional for users, as they can easily go from one area to another; light is where it is required only, with a high control over luminance and consumptions.

Emotional

Invisible light cuts at day time are integrated into the architecture. Volumes vibrate and are enhanced by a soft, fine and emotional light.

Scenic

Lighting highlights and enhances the architectural space. A scenic lighting enhances the elements of architecture. The right colour of light optimizes architectural lines.

Integrated.lighting

A lighting signature that allows to customize any space

In the contemporary architecture the light is considered as a construction material, it must be perfectly integrated and completed with the others. Fylo+ Out answers to this necessity in the best way. It's functional and step-light alongside walkaways or horizontal linkage, it's decorative and rational under roof or porticoes. Lighting lines composing the façade enhances horizontality and essentiality. One of the best Fylo+ Out series' highpoint is its fairly good visibility during the day and its perfect functionality during the night. Recessed lights are able to underlines contemporary architecture volumes solidity and materials, adding a versatile and descriptive lighting values.



Elegance. Light. Fylo+ Out

Fylo+ Out Recessed



* Art. 65036
Art. 65037



* Art. 65039
Art. 65040

Modules (mm)

2000 mm

1000 mm

1100 ->1900 mm 100 *

*** Custom lenghts**
All Fylo+ modules can be supplied precutted on demand, in 10 cm modules, adapting the system in fast and precise way, following single project needs.

Electrification

Stripled

Electronics

ON / OFF

DALI

Fylo+ Out Surface



* Art. 65030
Art. 65031



* Art. 65033
Art. 65034

Modules

2000 mm

1000 mm

1100 ->1900 mm 100 *

*** Custom lenghts**
All Fylo+ modules can be supplied precutted on demand, in 10 cm modules, adapting the system in fast and precise way, following single project needs.

Electrification

Stripled

Electronics

ON / OFF

DALI



Art. 65036
Art. 65037



Art. 65039
Art. 65040

Art. 65030
Art. 65031



Art. 65033
Art. 65034

Light for architecture

Fylo+ outdoor allows to highlight volumes and outdoor areas thanks to light cuts that enhance any place. Recessed solutions are blended in with the structure and provide a functional lighting for large areas or areas of transit. Surface installation versions give a certain rhythm to the façades and enhance their texture thanks to a grazing and uniform emission.



new

Fylo+ Out SURFACE and RECESSED

Outdoor graphic light

Outdoor lighting completes building design. Fylo+ outdoor is the ideal solution to emphasize architectural features with graphic lighting signs, combining the simplicity of shapes with the maximum installation flexibility. Anodized aluminium profiles have been designed to integrate LED lighting units featuring special opal diffusers that control luminance and make lighting emission softer. All the elements are coated with a special finishing, which allows to treat them as if they were coated with a standard outdoor plaster. For a perfect integration in the building structure, Fylo+ outdoor can be installed in the insulation coating or in the walls.



Fylo+ Out Recessed_S | Recessed light body





type	L mm	
White	1000	**65036**
White	2000	**65037**
White	custom	**65090***

Suggested accessories



65094	62757	62758	65026	65035
Opal Diffuser L custom 1pc	Opal Diffuser L1000 mm 1pc	Opal Diffusers L2000 mm 1pc	End caps 2 pc	Recessed outer-casing

All modules must be completed with light units and driver.

See bottom page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65090.

Fylo+ Out Recessed_W | Recessed light body



type	L mm	
White	1000	**65039**
White	2000	**65040**
White	custom	**65093***

Suggested accessories



65094	62757	62758	65023	65038
Opal Diffuser L custom 1pc	Opal Diffuser L1000 mm 1pc	Opal Diffusers L2000 mm 1pc	End caps 2 pc	Recessed outer-casing

All modules must be completed with light units and driver.

See bottom page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65093.

LED Strips | Light units-LED Strips

type

Silicone_F 599

Suggested electronics



62870	62880	62890	99332	84702	
ON/OFF 2,5 mt	ON/OFF 4 mt	ON/OFF 10 mt	1-10V 10 mt	Switching	
				99074	**99077**
				DALI/1-10V Controller 10 mt	PUSH Controller

Fylo+ Out Surface_S | Surface light body

type	L mm	
White	1000	**65030**
White	2000	**65031**
White	custom	**65091***

Suggested accessories



65094	**62757**	**62758**	**65020**
Opal Diffuser L custom 1pc	Opal Diffuser L1000 mm 1pc	Opal Diffusers L2000 mm 1pc	End caps 2 pc

All modules must be completed with light units and driver.

See bottom page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65091.

Fylo+ Out Surface_W | Surface light body



type	L mm	
White	1000	**65033**
White	2000	**65034**
White	custom	**65092***

Suggested accessories



65094	**62757**	**62758**	**65017**
Opal Diffuser L custom 1pc	Opal Diffuser L1000 mm 1pc	Opal Diffusers L2000 mm 1pc	End caps 2 pc

All modules must be completed with light units and driver.

See bottom page.

* By selecting the "Custom" code you can order the desired length profile from a minimum of 10 cm to a maximum of 1,9 m.
For example, to request 1.3 m of Fylo+ you can order 1.3 x 65092.

LED Strips | Light units-LED Strips

type

Silicone_F 599

Suggested electronics



62870	**62880**	**62890**	**99332**	**84702**
ON/OFF 2,5 mt	ON/OFF 4 mt	ON/OFF 10 mt	1-10V 10 mt	Switching

99074	**99077**
DALI/1-10V Controller 10 mt	PUSH Controller

Installation

Its high resistance to weathering allows Filo+ outdoor to be installed in complete safety. It provides high reliability thanks to its materials and build quality.

Full integration in the masonry

1. Make recess in masonry wall.

2. Insert EPS outer casing.

3. Block EPS outer casing into place using cement-based plaster.

4. Remove outer casing and prepare power supply cable.

5. Insert profile in the seat previously created.

6. Complete installation applying several coats of plaster making sure that mesh tape adheres on first coat.
Carry out the electrical connection and insert the LED source.













Full integration in the insulation system

1. Cut external wall insulation in order to create profile seat.

2. Pass power supply cables, apply polyurethane adhesive on profile rear side and insert it in seat. Install end caps if necessary.

3. Apply adhesive first coat. Position mesh tape with the sole exception of the profile part in relief. Apply the other adhesive coats and then plaster.

4. After completing all required operations, insert LED source in the relevant optical compartment and carry out electrical connections.



Lighting units

Profiles feature an internal protective film that shall be removed during installation.

- Insert the Strip LED A22 inside the profile.
- Install the protective screen.

Accent

Accent

Vuelta

Vuelta_1 402

Vuelta_2 403

Vuelta_Y1 402

Vuelta_Y2 403

Vuelta_X1 402

Vision

Vision_1 409



Vision_2 411



Vision_3 411

Vision_X 411

Khono

Khono_1 415



Khono_2 415



Texo

Texo_R 420



Texo_RJ 420



Texo_Q 420

Texo_QJ 420

Accent

Accent lighting

In outdoor lighting the space perception is a lighting game, able to enhance and shape surfaces and green areas. An accent lighting is the perfect solution to create interesting evocative and scenographic contrasts with low energy consumption and an elevated emissions control. Uplight and projectors are the efficient and flexible right solution, able to provide grazing, diffusive, spot or asymmetric lighting effects. A wide range options variety is available to satisfy every lighting project.





Power. Control. **Vuelta**

new

Vuelta

Vuelta is a perfect synthesis between minimum dimensions, pure shapes and aesthetic and technic detail attention. It's a spot designed for maximum installation flexibility with a precise and controlled light emission. The integrated bracket assures a stable aiming and higher cable fixing. Available in two sizes and two emissions (symmetric wideflood, asymmetric, narrow spot 10° and flood 30°) and in three fixing modes: wall, floor and on pole. Antiglare grid optional.

+ **adjustable lighting**
+ **arrayLED source**
+ **minimal design**
+ **versatility**

Vuelta

Reduced overall dimensions, neat and essential shapes and extreme attention to aesthetic and technical details; Vuelta is the perfect combination of these elements, a projector designed to be particularly easy to install and with a focused and controlled lighting emission. The mounting base integrated in the unit makes pointing stable over time and allows to easily wire and fasten the appliance. The design of the optical unit, which is both slender and compact, allows to easily use it with the majority of the architectural styles.

Range

Available in two dimensions, defined by an extra flat profile compact design. Vuelta is available in two finishes, two colors temperature and different lumen package. Ad hoc optical accessories and installation mode have been defined. 40W maximum power with 4000lm emissions.



Narrow spot emission

Available only for the small version. This emission is perfect for particularly effectiveness lighting accent. Used for long distance (30 m) ensures high intensity values and a reduced energy consumption.



On demand, Vuelta NSP can be supplied with a special elliptical filter to ovalize the light beam, creating blade lighting effects, extremely precise and professional.

Asymmetric emission

perfect for indirect vault and ceiling lighting; this configuration is the result of a long optics research to optimize depth flux distribution, not "soiled" with spurious light, the installation plan is obscured.



Wideflood direct emission

Direct lighting illuminates objects frontally, reducing contrasts and maximizing volumes and textures' perception. It's a high performance configuration; arrayLED source uses the full emission and maximize lighting distribution, provided by aluminum high reflectance dedicated diffuser 120°.



Vuelta

Construction details

Diecasting aluminum case, oxidation treatment and polyester coating. Extra clear tempered glass 6 mm thickness with a black serigraphy used for diffuser. Silicone gasket and anticondensation valve guarantees long term protection against seepage and moisture. Integrated driver on/off DALI.

Technology
ArrayLED / PowerLED



Accessories range

Vuelta accessories range includes antiglare grids, holographic integrated filters, pole installation brackets and pegs. A dedicated corner bracket can be used to adapt the installation of the projector to every project need.

Lighting scheme

Each pole is pre-set for the installation of one projector but can be drilled on site to install further illuminating bodies. The combination of more fixtures allows to easily manage complex light scenes leveraging the different emissions available in the range.



Installation

Vuelta installation system was designed to be fast and safe. Just removing the cover put over the integrated bracket and proceed with the fixing on wall with screws and plugs. Wiring realized by waterproof connectors inside the fixture itself. A special bracket is available for installation on Ø60mm poles featured in the product range with the same finishes of the projectors.

Vuelta_1 | Outdoor spotlights | 100-264 V | arrayLED 13,5 W 350 mA

IK09 IP65



type			colour			optics	
Grey	CRI 80	**64520**	3000 K	1826 lm	**W**	120°	**12**
BK Grey	CRI 80	**64521**	4000 K	1886 lm	**N**		

Vuelta_Y1 | Outdoor spotlights | 100-264 V | arrayLED 13,5 W 350 mA

IK09 IP65



type			colour			optics	
Grey	CRI 80	**64522**	3000 K	1826 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**64523**	4000 K	1886 lm	**N**		

Asymmetric

Vuelta_X1 | Outdoor spotlights | 198-264 V | 4 powerLEDs 4 W | 16 W 350 mA

IK09 IP65



type			colour			optics	
Grey	CRI 80	**64524**	3000 K	2116 lm	**W**	10°	**10**
BK Grey	CRI 80	**64525**	4000 K	2272 lm	**N**	30°	**30**

Vuelta_2 | Outdoor spotlights | 220-240 V | arrayLED 30 W 800 mA

IK09 IP65



type			colour			optics	
Grey	CRI 80	**64528**	3000 K	4239 lm	**W**	120°	**12**
BK Grey	CRI 80	**64529**	4000 K	4369 lm	**N**		

Vuelta_Y2 | Outdoor spotlights | Pole-top | 220-240 V | arrayLED 30 W 800 mA

IK09 IP65



type			colour			optics	
Grey	CRI 80	**64530**	3000 K	4239 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**64531**	4000 K	4369 lm	**N**		

Asymmetric

* ACCESSORIES



Pegs

Black **14931**

Corner bracket

Grey **64538**

BK Grey **64539**

Grid

Black **64534**

POLE INSTALLATION

Pole

Grey **64536**

BK Grey **64537**



Kit pole-top

Grey **64532**

BK Grey **64533**



Vision

Modular and adjustable spot

Vision is a complete range of adjustable spots. New finishes, pole and peg applications, single or double spot in different height, free ground installations. Fluorescent or Led sources, for different light effects. A versatile solution suitable to design scenes and lighting background in gardens, path and planted areas.

+ prefocused source GU10
+ peg fixing
+ adjustable spot

Wall/Ceiling light version

590



Vision

Vision is a complete range of adjustable spots. New finishes, pole and peg applications, single or double spot in different height, free ground installations. Fluorescent or Led sources, for different light effects. A versatile solution suitable to design scenes and lighting background in gardens, path and planted areas.

+ prefocused source GU10
+ peg fixing
+ adjustable spot

Vision_1 | Outdoor spotlights | 220-240 V | 1xGU10



LED

type		source	optics
Grey	51585	1xGU10 35W Max	variable
Cor-Ten	51586		

Vision

Adjustable spot

Bollard with an adjustable optical unit. Pre-focused light sources for different lighting effects. A versatile solution to design both lighting scenes and lighting backstage settings in gardens, walkways and tree-lined areas.

+ prefocused source GU10
+ different heights
+ adjustable spot

Vision_2 | Outdoor spotlights | 220-240 V | 1xGU10



LED

type		source	optics
Grey	**51395**	1xGU10 50W Max	variable
Cor-Ten	**51396**		

Suggested accessories

50370

Peg

Vision_3 | Outdoor spotlights | 220-240 V | 1xGU10



LED

type		source	optics
Grey	**51405**	1xGU10 50W Max	variable

Suggested accessories

50370

Peg

Vision_X | Outdoor spotlights | 220-240 V | 2xGU10



LED

type		source	optics
Grey	**51475**	1xGU10 50W Max	variable

Suggested accessories

50370

Peg

Khono

Khono is available in four versions: floor or wall mounted, on peg or pole, for free ground compositions. The Led Array source is provided with an adjustable custom optical lens. Stainless steel structure with electropolishing finish for higher corrosion resistance ideal for areas with an elevated salinity. Minimal design, suitable for every landscape or architectural style.

+ stainless steel AISI 316
+ adjustable light
+ Led source

Khono_1 | Outdoor spotlights | 100-240 V | arrayLED 5 W 450 mA

2 m IK06 IP65



type			colour			optics	
Inox	CRI 80	**64251**	3000 K	544 lm	**W**	36°	**36**
			4000 K	562 lm	**N**		

Suggested accessories

14931

Pegs

Khono_2 | Outdoor spotlights | 100-240 V | arrayLED 5 W 450 mA

IK06 IP65



type			colour			optics	
Inox	CRI 80	**64261**	3000 K	544 lm	**W**	36°	**36**
			4000 K	562 lm	**N**		

Texo

Floor recessed downlights stainless steel frame, round or squared. Prepared for installation of prefocused source GU10 plug, satisfying all lighting needs and evaluating all architectural contexts. Tilting or fixed optics +/-20°, aluminum case protected by transparent high resistance finish, anticorrosion pretreatment. Extraclear glass diffuser not passable. Installation outercasing available as accessory.

+ prefocused source GU10
+ adjustable light
+ stainless steel frame

Texo_R | Uplights | 220-240 V | 1xGU10



LED

type	source	optics
Inox **52601**	1xGU10 35W Max	variable

Suggested accessories

52700	E41017	E41025
Outer casing	Terminal boxes	Resin-potted

Texo_RJ | Adjustable uplights | 220-240 V | 1xGU10



LED

type	source	optics
Inox **52901**	1xGU10 35W Max	variable

Suggested accessories

52700	E41017	E41025
Outer casing	Terminal boxes	Resin-potted

Texo_Q | Uplights | 220-240 V | 1xGU10



LED

type	source	optics
Inox **52671**	1xGU10 35W Max	variable

Suggested accessories

52700	E41017	E41025
Outer casing	Terminal boxes	Resin-potted

Texo_QJ | Adjustable uplights | 220-240 V | 1xGU10



LED

type	source	optics
Inox **52951**	1xGU10 35W Max	variable

Suggested accessories

52700	E41017	E41025
Outer casing	Terminal boxes	Resin-potted





20 cm of gravel for drainage is required. Use a H07RN-F cable only, other types of cable may compromise the IP67 protection degree. All the other items can be supplied with a 3-metre H07RN-F cable upon request.

Bollard + Poles

Bollard + Poles

Bob18

Bob18_1 436

Bob18_2 436

Ryo

Ryo_1 444

Ryo_1 444

Ryo_1 444

Ryo_2 446

Ryo_2 446

Ryo_2 446

Peak

Peak_1 454

Peak_2 454

Peak_L 454

Peak-Maxi_1 460

Peak-Maxi_L1 460

Peak-Maxi_L2 460

Peak-Maxi_D2 461

Peak-Maxi_FR 461

Dirigo

Dirigo_FL2 470

Dirigo_FL1 470

Dirigo_M2 472

Dirigo_M1 474

Joe

Joe_1 482

Joe_1 482

Joe_2 482

Puro

Puro 487

Pilos

Pilos_2 492

Pilos_2 492

Pilos_1 494

Pilos_1 494

Pilos_1 494

Pilos_X 495

Pilos_X 495

Stalk

Stalk_X 502

Stalk_1 502

Stalk_2 503

Stalk-One_1 506

Stalk-One_2 506

Twig

Twig_1

516

Twig_2

516

Twig_3

516

Stick

Stick_1

523

Stick_2

523

Stick_X1

524

Stick_X2

525

Ciclop

Ciclop_1

530

Ciclop_1

530

Ciclop_2

530

Ciclop_3

530

Ciclop_3

531

I-Cube

I-Cube_1

535

I-Cube_2

535

Rock

Rock_1

541

Rock_2

541

Rock_3

541

D-Retta

D-Retta_1

545

D-Retta_2

545

Cu-Flex

Cu-Flex_2

549

Cu-Flex_3

549

Cu-Flex_6

549

Cu-Flex_2 bright

550

Cu-Flex_3 bright

550

Cu-Flex_6 bright

550

Bollard + Poles

Urban proof

Coordinated and complete fixtures' series enhance the urban luminous environment, respecting the continuity between architecture, linkage and landscape. Dedicated optics solutions interpret outdoor spaces respecting the environment thanks to anti-luminous pollution integrated systems. Fixtures provide light only where needed, without leaks, concentrating functional lighting on paths and guaranteeing, at the same time, landscape's narration and safety. Bollards, in every context perfectly integrated, include roto-symmetric emissions option, perfect to enlarge distance between installed fixtures, completing the homogeneous and controlled light provided by highest poles







Strong. Glareless. **Bob18**

new

Bob18

Diecasting aluminum and stainless steel AISI 304 bollard.
Solid design especifically designed for the urban spaces.
Essential and sleek aesthetics with a high technological content.
Maximum glare control thanks to special reflector combined with an extra clear glass diffuser. Bob is available in two sizes and suitable for a variety of applications: bollard, ground and wall mounted.
Its particular light distribution ensures optimum visibility and excellent homogeneity in ground lighting. The "midi" version provide a grazing and comfortable lighting, ideal for walking trails and gardens.

+ Led source
+ 360° deep lighting
+ high visual comfort

Bob18

Concept

Bob was created to light up large urban spaces, as squares, public gardens or passages. It's defined by a characteristic shape, emitting a roto-symmetric lighting, able to reach 5 m interaxis distance.



***Example of installation with 10 metre centre distance**

Waterproof optics (IP66)

Pre-wired bollard head provided with a IP68 connector, allowing an easier installation and ensuring the maximum safe during electric connection.



Controlled emission

Extra pure aluminum internal diffuser was designed to maximize lighting uniformity and glare control; direct luminance is almost totally eliminated.



Applications

Landscape, urban.
Rotosymmetrical radial emission with high luminance control.



Bob18_1 | Bollards | 198-264 V | topLED 13 W 500 mA

IK09 IP66



type			colour			optics	
Grey	CRI 80	**64715**	3000 K	1941 lm	**W**	radial	**00**
BK Grey	CRI 80	**64716**	4000 K	2060 lm	**N**		

Bob18_2 | Bollards | 198-264 V | topLED 18 W 700 mA

IK09 IP66



type			colour			optics	
Grey	CRI 80	**64711**	3000 K	2673 lm	**W**	radial	**00**
BK Grey	CRI 80	**64712**	4000 K	2832 lm	**N**		

Range. Aesthetics. **Ryo**

new

Ryo

Minimal design pole, single or double emission per outdoor lighting. Available in three heights and two emissions. Ryo conveys Led source light, placed in the upper part, along its peculiar vertical groove. Emitting light with a 180° beam, without upward luminous pollution. Aluminum case polyester powder coating with surface protective pretreatment, for high outdoor resistance. Anticrash polycarbonate diffuser, stainless steel brackets and screws.

+ minimal design
+ single or double emission
+ coordinated range

Dark sky compliant

The Ryo optic group avoids lighting leaks over horizon. Bollard's emission is very comfortable and respect the current law against luminous pollution.

Ryo

Concept

The Ryo name indicates its peculiar character:
during the night the stem's concave profile comes
alive and flooded by decorative and functional light.
The vertical plan lighting provides a reference point during
the night, using coating surface fixture's luminance to reduce
consumptions. Light distribution on path results smooth
and deep, perfect for public and residential projects.



Unidirectional emission

Ideal for pathway lighting, this solution provides a great visual
orientation and creates a certain rhythm inside the pathways,
also outlining the walking areas through light and shade.



***Example of installation with
3 metre centre distance**

Bidirectional emission

This type of emission is particularly functional to light up large
areas or gardens, since they require a diffusive light coming
from both sides of the bollard.



***Example of installation with
4,5 metre centre distance**

Ryo_1 | Bollards | 190-250 V | arrayLED 4,2 W 120 mA

IK09 IP66



type			colour			optics	
Grey	CRI 80	**64761**	3000 K	697 lm	**W**	diffused	**00**
BK Grey	CRI 80	**64759**	4000 K	720 lm	**N**		
Cor-Ten	CRI 80	**64760**					

Suggested accessories

64758

Pegs

Ryo_1 | Bollards | 100-240 V | arrayLED 9 W 250 mA

IK09 IP66



type			colour			optics	
Grey	CRI 80	**64734**	3000 K	1364 lm	**W**	diffused	**00**
BK Grey	CRI 80	**64721**	4000 K	1408 lm	**N**		
Cor-Ten	CRI 80	**64726**					

Suggested accessories

64758

Pegs

Ryo_1 | Bollards | 100-240 V | arrayLED 9 W 250 mA

IK09 IP66



type			colour			optics	
Grey	CRI 80	**64736**	3000 K	1364 lm	**W**	diffused	**00**
BK Grey	CRI 80	**64723**	4000 K	1408 lm	**N**		
Cor-Ten	CRI 80	**64728**					

Suggested accessories

64758

Pegs

Ryo_2 | Bollards | 190-250 V | arrayLED 8,4 W 120 mA

IK09 IP66



type			colour			optics	
Grey	CRI 80	**64764**	3000 K	1394 lm	**W**	diffused	**00**
BK Grey	CRI 80	**64762**	4000 K	1440 lm	**N**		
Cor-Ten	CRI 80	**64763**					

Suggested accessories

64758

Pegs

Ryo_2 | Bollards | 100-240 V | arrayLED 18 W 250 mA

IK09 IP66



type			colour			optics	
Grey	CRI 80	**64735**	3000 K	2728 lm	**W**	diffused	**00**
BK Grey	CRI 80	**64722**	4000 K	2816 lm	**N**		
Cor-Ten	CRI 80	**64727**					

Suggested accessories

64758

Pegs

Ryo_2 | Bollards | 100-240 V | arrayLED 18 W 250 mA

IK09 IP66



type			colour			optics	
Grey	CRI 80	**64737**	3000 K	2728 lm	**W**	diffused	**00**
BK Grey	CRI 80	**64724**	4000 K	2816 lm	**N**		
Cor-Ten	CRI 80	**64729**					

Suggested accessories

64758

Pegs

Architectural. Pure. **Peak**

new

Peak

Urban solutions

Creating uniform light paths and coordinated with contemporary urban space, it is crucial to choose the right amount of light combined with a proper installation. The correct urban spaces lighting is a key point for the appropriation and sharing cities by citizens. PEAK interprets this need with a full range of solutions specially designed.



Wall light version

570

Peak

Concept

A simple and compact element, suitable for any context. Despite the small size, this mini bollard, available in different versions, provides high lumen packages with a perfect lighting emission control on floor and excellent visual comfort, thanks to its special optical group totally conceals light source.

Optics design

The peculiar optical group conformation provides a lighting emission only on bollard front, eliminating every secondary light dispersion on the back. The light emission is deep, clear and defined.

Compositions

The bollards are mainly composed by three elements. The body is composed by two parts in anodized extruded, welded and coated aluminum. The head, which includes the optical unit, is a die-cast aluminum part coated in high resistance polyester and the diffuser made in extra-clear etched and sealed glass (sp. 5mm).



Installation

Bollard's installation is provided by steel bracket fixing. This one is prepared with a Ø20 mm central hole, suitable for the standard corrugated tube.

Performance

"L" version is suitable for light up passages, for which a good deepth distribution is requested (5 m), without compromising lateral lighting distribution.



***Example of installation with 2,5 metre centre distance**

"Q" version is created for a deeper lighting, on the bollard's front, just with 9W providing good lighting distribution values up to 8 m.



***Example of installation with 2,5 metre centre distance**

Peak_L | Bollards | 100-240 V | arrayLED 9,5 W 250 mA

IK07 IP66



type			colour			optics	
Grey	CRI 80	**64788**	3000 K	1364 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**64789**	4000 K	1408 lm	**N**		
Cor-Ten	CRI 80	**64790**					

Suggested accessories

65082

Bracket

Peak_1 | Bollards | 100-240 V | arrayLED 6,5 W 180 mA

IK05 IP66



type			colour			optics	
Grey	CRI 80	**64794**	3000 K	1015 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**64795**	4000 K	1048 lm	**N**		
Cor-Ten	CRI 80	**64796**					

Suggested accessories

65082

Bracket

Peak_2 | Bollards | 100-240 V | arrayLED 9,5 W 250 mA

IK05 IP66



type			colour			optics	
Grey	CRI 80	**64791**	3000 K	1364 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**64792**	4000 K	1408 lm	**N**		
Cor-Ten	CRI 80	**64793**					

Suggested accessories

65082

Bracket

Peak-Maxi_FR

design: Marco Ciarlo Associati

Peak-Maxi

Every needs answer

Wall mounted version, different dimensions and power bollards, single or double architectural poles and the Arco peculiar version, ensures a solution for every installation needs. Peak provides easier installation also in the urban context, its great flexibility ensures a professional lighting and architecture project approach.



Control and performance

Luminous unit equipped with dedicated lens managing light distribution with maximum control. Asymmetric effects able to light up secondary roads, squares, parks and gardens.



***Example of installation with 15 metre centre distance**

Light portal: Peak-Maxi_FR
design: Marco Ciarlo associati

An innovative fixture, perfect to fit every outdoor space. This version provides a luminous "portal", defining squares and parks with a smooth and comfortable lighting effect. Almost non-existent glare makes it suitable to any situation.

Peak-Maxi_1 | Bollards | 100-240 V | PowerLED 12 W 350 mA

IK08 IP65



type			colour			optics	
Grey	CRI 80	**65061**	3000 K	1433 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**65062**	4000 K	1783 lm	**N**		
Cor-Ten	CRI 80	**65060**					

Peak-Maxi_L1 | Poles | 100-240 V | PowerLED 39 W 550 mA

IK08 IP65



type			colour			optics	
Grey	CRI 80	**65073**	3000 K	4280 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**65074**	4000 K	5323 lm	**N**		
Cor-Ten	CRI 80	**65072**					

Suggested accessories

65078
Bracket
1 pc

65076
Base
1 pc
Grey

65077
Base
1 pc
BK Grey

65075
Base
1 pc
Cor-Ten

Peak-Maxi_L2 | Poles | 100-240 V | PowerLED 59 W 550 mA

IK08 IP65



type			colour			optics	
Grey	CRI 80	**65064**	3000 K	6420 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**65065**	4000 K	7984 lm	**N**		
Cor-Ten	CRI 80	**65063**					

Suggested accessories

65078
Bracket
1 pc

65076
Base
1 pc
Grey

65077
Base
1 pc
BK Grey

65075
Base
1 pc
Cor-Ten

Peak-Maxi_D2 | Poles | 100-240 V | PowerLED 39 W 550mA + 59 W 550 mA

IK08 IP65



type			colour			optics	
Grey	CRI 80	**65067**	3000 K	10700 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**65068**	4000 K	13307 lm	**N**		
Cor-Ten	CRI 80	**65066**					

Suggested accessories

65078
Bracket
1 pc

65076
Base
1 pc
Grey

65077
Base
1 pc
BK Grey



65075
Base
1 pc
Cor-Ten

Peak_Maxi_FR | Poles | 100-240 V | PowerLED 50 W 1050 mA

IK08 IP65



type			colour			optics	
Grey	CRI 80	**65070**	3000 K	5650 lm	**W**	diffused	**00**
BK Grey	CRI 80	**65071**	4000 K	6000 lm	**N**		
Cor-Ten	CRI 80	**65069**					

Suggested accessories

65078
Bracket
1 pc

65076
Base
1 pc
Grey

65077
Base
1 pc
BK Grey



65075
Base
1 pc
Cor-Ten

ACCESSORIES INSTALLATION

A - Installation with bracket
B - Installation with base





Magic. Slim. Dirigo

new

Dirigo

design: RIGO

A stylish game of opposite plans define a linear and balanced emission, perfect for illuminating pathways. Dirigo is an innovative lighting concept, for a brand new outdoor space interpretation. The stainless steel AISI 316L quality increases the fixture's value, ideal for installation in high salinity environments.

+ registered design
+ AISI 316L stainless steel versions
+ grazing emission
+ controlled luminance

DESIGN AWARD 2017



Dirigo

Concept

Invisible during the day. Main actor during the night. Dirigo creates lighting paths through an elegant opposite plans game, hiding the source. Its peculiar profile's section makes the fixture compact and solid, perfectly integrated in all outdoor contexts.

Technology and materials

Dirigo series available in brushed stainless steel AISI 316L or anodyzed extruded aluminum with polyester powder pre-coating antioxide treatment.

Grazing light

The internal Led source gradient was studied for the best lighting distribution, along the pathways.



Range

Dirigo is available as single module or prepared for continuous line installation.

Single module (L. 1m)
Sealed and complete source profile, end caps, integrated driver 24V DCo.

Continuous line installation modules (L. 1m)
On measure cutting profiles, prepared for continuous line installation up to 5/10m. Led source available with a separated code and on measure cutting. Mechanical connection joints between profiles. Remote driver 24V DC.

Complete element version



System

Robust design

The opposing level structure of Dirigo's single profile makes this appliance particularly sturdy and resistant. The absence of raw edges makes it ideal for public and private outdoor applications. Dirigo can be walked on and is extremely safe for users.

Dirigo_FL2 Aluminium | Linear profiles | 100-264 V | stripLED 14,4 W



type			colour			optics	
BK Grey	CRI 80	**64643**	3000 K	900 lm	**W**	diffused	**00**
Grey	CRI 80	**64642**					
Cor-Ten	CRI 80	**64594**					

Dirigo_FL1 Steel | Linear profiles | 100-264 V | stripLED 14,4 W



type			colour			optics	
Inox	CRI 80	**64590**	3000 K	900 lm	**W**	diffused	**00**

Dirigo_M2 Aluminium MASTER | Linear profiles



Master

To be completed with dedicated installation accessories and light unit

type

BK Grey	**64645**	L1010 mm
Grey	**64644**	L1010 mm
Cor-Ten	**64595**	L1010 mm

Dirigo_M2 Aluminium SLAVE | Linear profiles



Slave

To be completed with dedicated installation accessories and light unit

type

BK Grey	**64647**	L2000 mm
Grey	**64646**	L2000 mm
Cor-Ten	**64597**	L2000 mm

Dirigo_M2 Aluminium IN-corner | Linear profiles





To be completed with dedicated installation accessories and light unit

type

BK Grey	**64664**	L500 mm
Grey	**64665**	L500 mm
Cor-Ten	**64666**	L500 mm

Dirigo_M2 Aluminium OUT-corner | Linear profiles



To be completed with dedicated installation accessories and light unit

type

BK Grey	**64667**	L500 mm
Grey	**64668**	L500 mm
Cor-Ten	**64669**	L500 mm

ACCESSORIES AND LAYOUT



Closing cap
Aluminium
2 pcs

BK Grey	**64641**
Grey	**64640**
Cor-Ten	**64589**



Junction cap
Aluminium
1 pc

BK Grey	**64661**
Grey	**64663**
Cor-Ten	**64662**

64569
Light unit
Led strip 14,4 W/m
3000 K
5 mt

89629
Connection cable
2 mt

99000
Extension cable
2 mt



99331
Driver ON/OFF
10 mt
IP 65



99332
Driver 1-10V
10 mt
IP 65



Dirigo_M1 Steel MASTER | Linear profiles



type

Inox	**64591**	L1010 mm

Master

To be completed with dedicated installation accessories and light unit

Dirigo_M1 Steel SLAVE | Linear profiles



type

Inox	**64648**	L1000 mm

Slave

To be completed with dedicated installation accessories and light unit

ACCESSORIES AND LAYOUT



64592
Closing cap
Stainless steel
2 pcs



64593
Junction cap
Stainless steel
1 pc

64569
Light unit
Led strip 14,4 W/m
3000 K
5 mt

89629
Connection cable
2 mt

99000
Extension cable
2 mt



99331
Driver ON/OFF
10 mt
IP 65



99332
Driver 1-10V
10 mt
IP 65



Compact. Rounded. Joe

Joe

Step-light, bollard and wall mounted series, defined by a sober and minimal design, suitable in every architectural context. Single or double emission, Led source with custom optics for grazing lighting, without upward loss. The aluminum structure holds the optics, case painted in high resistance polyester finish with surface protective pretreatment. Perfect for lighting urban spaces or signal paths.

+ RedDot award
+ wide range
+ controlled emission

reddot award 2015
winner

Joe

Optics design

The peculiar Joe emission derives by integrated optical group accurate studies. The high performance ArrayLED source combined with a sputtering metallized transparent polycarbonate special semi-circular reflector. The light chamber lower part is wrapped with a microcell pad in semi-glossy black polycarbonate, for the direct luminance perfect control.





Robust design

The special spherical cap shape of Joe profile makes this product particularly robust and resistant, ideal for both public and private outdoor applications. The total absence of raw edges makes it particularly safe for users.



Example of installation with 2 metre centre distance

Grazing light

The distribution of the light on the walking area creates an interesting shade effect, which is perfectly parallel to the walking direction. This effect can be used to outline night paths and highlight green areas with accent lighting.

Joe_1 | Bollards | 100-240 V | arrayLED 9,2 W 250 mA

IP65



type			colour			optics	
Grey	CRI 80	**59165**	3000 K	942 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**59166**	4000 K	942 lm	**N**		

Suggested accessories

14931

Pegs

Joe_1 | Bollards | 100-240 V | arrayLED 9,2 W 250 mA

IP65



type			colour			optics	
Grey	CRI 80	**59175**	3000 K	942 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**59176**	4000 K	942 lm	**N**		

Suggested accessories

59950

Pegs

Joe_2 | Bollards | 220-240 V | topLED 9 W 500 mA

IP65



type			colour			optics	
Grey	CRI 80	**64635**	3000 K	1060 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**64636**	4000 K	1124 lm	**N**		

Suggested accessories

14931

Pegs

Minimal. Urban. **Puro**

Puro



Neutral design

Its cylindrical column figures out the bollard archetype. A solid, strong, vandal-proof shape perfectly neutral for every urban space.
Two finishes, light and anthracite gray represents last design trends for outdoor projects.

Robust design

Aluminum column bollard, high resistance polyester coating and surface protective pretreatment. Extraclear glass diffuser, stainless steel brackets and screws.

Waterproof optics (IP66)

Pre-wired bollard head provided with a IP68 connector, allowing an easier installation and ensuring the maximum safe during electric connection.

Controlled emission

Extra pure aluminum internal diffuser was designed to maximize lighting uniformity and glare control; direct luminance was eliminated

Puro | Bollards | 198-264 V | topLED 18 W 700 mA

IK09 IP66



type			colour			optics	
Grey	CRI 80	**64700**	3000 K	2673 lm	**W**	radial	**00**
BK Grey	CRI 80	**64701**	4000 K	2832 lm	**N**		

Essential. Compact. **Pilos**

Pilos

Complete range of Led and compact fluorescent source bollard and poles. Diffusive and radial lighting, straight to ground. A Led source, with integrated driver, is placed in the fixture's head. The optics is incorporated in the aluminum structure, hold by four aluminum plates. The bollard is available in eight different versions and two options, with or without PMMA opal diffuser. Polyester high resistance coating with protective pretreatment for outdoor installation.

+ complete range
+ radial lighting emission
+ Led and compact fluorescent source

Pilos_2 | Bollards | 190-250 V | arrayLED 6,8 W 180 mA

IK06 IP65



type			colour			optics	
Grey	CRI 80	**60075**	3000 K	1015 lm	**W**	85°	**85**
			4000 K	1048 lm	**N**		

Suggested accessories

59950

Pegs

Pilos_2 | Bollards | 190-250 V | arrayLED 6,8 W 180 mA

IK06 IP65



type			colour			optics	
Grey	CRI 80	**60065**	3000 K	1015 lm	**W**	85°	**85**
			4000 K	1048 lm	**N**		

Suggested accessories

59950

Pegs

Pilos_1 | Bollards | 190-250 V | topLED 6 W 120 mA

IK09 IP65



type			colour			optics	
Grey	CRI 80	**61125**	3000 K	728 lm	**W**	diffused	**00**
			4000 K	755 lm	**N**		

Suggested acessories

59950 Pegs

58675 180° Shutter

Pilos_1 | Bollards | 190-250 V | topLED 6 W 120 mA

IK09 IP65



type			colour			optics	
Grey	CRI 80	**61115**	3000 K	728 lm	**W**	diffused	**00**
			4000 K	755 lm	**N**		

Suggested acessories



59950 Pegs

58675 180° Shutter

Pilos_1 | Bollards | 220-240 V | topLED 9 W 250 mA

IK09 IP65



type			colour			optics	
Grey	CRI 80	**61145**	3000 K	1456 lm	**W**	diffused	**00**
			4000 K	1510 lm	**N**		

Suggested acessories



59950 Pegs

58685 180° Shutter

Pilos_X | Bollards | 220-240 V | topLED 24 W 600 mA

IK09 IP65



type			colour			optics
Grey	CRI 80	**60073**	3000 K	3630 lm	**W**	diffused
			4000 K	3630 lm	**N**	

Suggested accessories

59950	**58695**
Pegs	180° Shutter

Pilos_X | Bollards | 220-240 V | topLED 24 W 600 mA

IK09 IP65



type			colour			optics
Grey	CRI 80	**60074**	3000 K	3630 lm	**W**	diffused
			4000 K	3630 lm	**N**	

Suggested accessories

59950	**58695**
Pegs	180° Shutter

Geometric. Essential. **Stalk**

Stalk

Series composed by many fixtures and height variations, for every living or urban space. Combining LED sources with its essential and contemporary design. Extruded aluminum rectangular section structure, with polyester coating with high resistance and surface protection pre-treatment. Diffusers in satin polycarbonate with anti-age treatment.

+ wide range
+ patented design
+ Dark Sky compliant versions

Wall light version

574

The importance of a broad matching range is fundamental for the management of any project, from the easiest one to the most detailed one. The diffusive light effect can be applied to lots of different solutions, from wall lights to bollards or poles.

Stalk_X | Bollards | 100-240 V | topLED 4 W

IK08 IP65



type			colour			optics	
Grey	CRI 80	**64650**	3000 K	414 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**64651**	4000 K	440 lm	**N**		

Stalk_1 | Bollards | 100-240 V | topLED 4 W

IK08 IP65



type			colour			optics	
Grey	CRI 80	**63455**	3000 K	414 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63456**	4000 K	440 lm	**N**		

Stalk_1 | Bollards | 180-264 V | topLED 8 W

IK08 IP65



type			colour			optics	
Grey	CRI 80	**63465**	3000 K	828 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63466**	4000 K	879 lm	**N**		

Suggested accessories

56990
Bracket

53890
Tie rods

Stalk_1 | Bollards | 180-264 V | topLED 8 W

IK08 IP65



type			colour			optics	
Grey	CRI 80	**63475**	3000 K	828 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63476**	4000 K	879 lm	**N**		

Suggested accessories

56990
Bracket

53890
Tie rods

Stalk_2 | Bollards | 100-240 V | topLED 4 W



type			colour			optics	
Grey	CRI 80	**63495**	3000 K	414 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63496**	4000 K	440 lm	**N**		

Stalk_2 | Bollards | 180-264 V | topLED 8 W



type			colour			optics	
Grey	CRI 80	**63505**	3000 K	828 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63506**	4000 K	879 lm	**N**		

Suggested accessories

56990
Bracket

53890
Tie rods

Stalk_2 | Bollards | 180-264 V | topLED 8 W



type			colour			optics	
Grey	CRI 80	**63515**	3000 K	828 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63516**	4000 K	879 lm	**N**		

Suggested accessories

56990
Bracket

53890
Tie rods

Stalk_3 | Pole | 180-264 V | topLED 16 W

IK08 IP65



type			colour			optics	
Grey	CRI 80	**63445**	3000 K	1656 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63446**	4000 K	1757 lm	**N**		

Suggested accessories

53890

Tie rods

Stalk_4 | Pole | 90-264 V | 24 x powerLED 41 W 1050 mA

IK08 IP65



type			colour			optics	
Grey Bk	CRI 80	**63785**	3000 K	4522 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63786**	4000 K	4757 lm	**N**		

Organic. Sinuous. **Twig**

Twig

Sinuous floor stem, Twig is noticeable for its organic and minimal design, suitable for every project context. Pole integrated base, peg accessory provided and ground bracket vandal proof. TopLED high luminosity source, protected by a satin diffuser for an optimized down lighting, no upward loss. Available in three heights and two finishes, for different lighting effects: step-light, bollard or pole.

+ patented design
+ organic aesthetics
+ diffused emission

Twig

Ideal for landscape and public areas

The essential character of the curved profile matched with the available well-refined finishes allow to use Twig in any outdoor situation. A neutral element that produces a bright and consistent light at night.

Design

Curvilinear, organic design, without sharp corners.
Fixture's aesthetics make it suitable for every contemporary landscape design. Stainless steel structure, electropolished treatment to increase corrosion resistance, or in corten finish.

Diffusive lighting

The light emission of Twig is soft and diffusive. Light allows to softly switch the stem on, thus outlining the product and keeping an excellent uniformity across the whole walking surface.



***Example of installation with a 3-metre centre distance**

Twig_1 | Bollards | 190-250 V | topLED 2,5 W 60 mA

IK05 IP65



type			colour			optics	
Inox	CRI 80	**64201**	3000 K	332 lm	**W**	80°	**80**
Cor-Ten	CRI 80	**64206**	4000 K	351 lm	**N**		

Suggested accessories

59960
Pegs

Twig_2 | Bollards | 190-250 V | topLED 5 W 120 mA

IK05 IP65



type			colour			optics	
Inox	CRI 80	**64211**	3000 K	663 lm	**W**	80°	**80**
Cor-Ten	CRI 80	**64216**	4000 K	702 lm	**N**		

Suggested accessories

59960
Pegs

59970
Bracket

Twig_3 | Bollards | 190-250 V | topLED 7,5 W 180 mA

IK05 IP65



type			colour			optics	
Inox	CRI 80	**64221**	3000 K	995 lm	**W**	80°	**80**
Cor-Ten	CRI 80	**64226**	4000 K	1053 lm	**N**		

Suggested accessories

59970
Bracket

Stick

Minimal and refined bollard, Led source single or dual emission. Aluminum case polyester high resistance coating with surface protective pretreatment and anti-crash PMMA satin diffuser. Stainless steel brackets and screws. Electronic power supply included. Available with total height centered emission or asymmetric along fixture's profile.

+ low consumption
+ three heights
+ minimal design

Wall light version

576

Stick

Stick_1 | Bollards | 180-264 V | stripLED 2,0 W

IK07 IP65



type			colour			optics	
Grey	CRI 80	**62305**	3000 K	130 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**62306**					

Suggested accessories

62190

Bracket

Stick_1 | Bollards | 180-264 V | stripLED 4 W

IK07 IP65



type			colour			optics	
Grey	CRI 80	**62325**	3000 K	260 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**62326**					

Suggested accessories

62190

Bracket

Stick_1 | Bollards | 180-264 V | stripLED 6 W

IK07 IP65



type			colour			optics	
Grey	CRI 80	**62345**	3000 K	390 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**62346**					

Suggested accessories

62190

Bracket

Stick_2 | Bollards | 180-264 V | stripLED 4 W

IK07 IP65



type			colour			optics	
Grey	CRI 80	**62315**	3000 K	260 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**62316**					

Suggested accessories

62190

Bracket

Stick_2 | Bollards | 180-264 V | LED 8 W

IK07 IP65



type			colour			optics	
Grey	CRI 80	**62335**	3000 K	520 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**62336**					

Suggested accessories

62190

Bracket

Stick_2 | Bollards | 180-264 V | LED 12 W

IK07 IP65



type			colour			optics	
Grey	CRI 80	**62355**	3000 K	780 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**62356**					

Suggested accessories

62190

Bracket

Stick_X1 | Bollards | 180-264 V | LED 6 W

IK07 IP65





type			colour			optics	
Grey	CRI 80	**62365**	3000 K	390 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**62366**					

Suggested accessories

62190

Bracket

Stick_X1 | Bollards | 180-264 V | LED 9 W

IK07 IP65



type			colour			optics	
Grey	CRI 80	**62385**	3000 K	585 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**62386**					

Suggested accessories

62190

Bracket

Stick_X2 | Bollards | 180-264 V | LED 12 W

IK07 IP65





type			colour			optics	
Grey	CRI 80	**62375**	3000 K	780 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**62376**					

Suggested accessories

62190

Bracket

Stick_X2 | Bollards | 180-264 V | LED 18 W

IK07 IP65





type			colour			optics	
Grey	CRI 80	**62395**	3000 K	1169 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**62396**					

Suggested accessories

62190

Bracket

Steel. Accent. **Ciclop**

Ciclop

Stylish design, refined cylindrical shape and Led technology defines Ciclop. Stainless steel AISI 316 polished or zinc metal or zirconium gray coating. Different versions: floor, ceiling or wall mounted and with single, dual or triple emission, guarantees specific beams to enrich the spaces.
Dual asymmetric emission for step or accent lighting.

+ three heights available
+ single, double or triple emission
+ structure in stainless steel AISI 316

Ciclop_1 | Bollards | 100-240 V | powerLED 2 W 450 mA

IK08 IP65



type			colour			optics	
Grey	CRI 80	**61505**	3000 K	144 lm	**W**	60°	**60**
Inox	CRI 80	**61501**					

Suggested accessories



61560 Pegs

61570 Pegs

Ciclop_1 | Bollards | 100-240 V | powerLED 2 W 450 mA

IK08 IP65

type			colour			optics	
Grey	CRI 80	**61525**	3000 K	144 lm	**W**	60°	**60**
Inox	CRI 80	**61521**					

Suggested accessories

61560 Pegs

61570 Pegs

Ciclop_2 | Bollards | 100-240 V | 2 powerLED 2 W | 4 W 450 mA

IK08 IP65



type			colour			optics	
Grey	CRI 80	**61515**	3000 K	288 lm	**W**	60°	**60**
Inox	CRI 80	**61511**					

Suggested accessories



61560 Pegs

61570 Pegs

Ciclop_3 | Bollards | 100-240 V | 3 powerLED 2 W | 18 W 450 mA

IK08 IP65



type			colour			optics	
Grey	CRI 80	**61585**	3000 K	432 lm	**W**	60°	**60**
Inox	CRI 80	**61581**					

Suggested accessories



57660 Pegs

14931 Pegs

Ciclop_3 | Bollards | 100-240 V | 3 powerLED 2 W | 18 W 450 mA



type			colour			optics	
Grey	CRI 80	**61595**	3000 K	432 lm	**W**	60°	**60**
Inox	CRI 80	**61591**					

Suggested accessories

57660
Pegs

14931
Pegs

I-Cube

design: RIGO

I-Cube provides simplicity and elegance.
A lighting fixture range for wall, ceiling and floor mounting whose distinguishing feature is a completely transparent glass.
A highly elegant and discrete soft lighting.

+ lead glass diffuser
+ fluorescent or Led source
+ fine finishes

Wall light version

582

I-Cube

Bollard available in two heights, simply charming and stylish. Available with compact fluorescent or Led Array, for different lighting effects. Extruded aluminum structure, with anti-oxidant treatment, and polyester powder coating. Lead glass diffuser, internal sandblasting treatment hiding the source and providing a very smooth lighting effect. The superior quality glass provides an extraordinary transparency and purity; these properties are enhanced by surface polished finishing, enrich this fixture.

I-Cube_1 | Bollards | 100-240 V | arrayLED 3,5 W 350 mA

IK05 IP65



type			colour			optics	
Grey	CRI 80	**53065**	3000 K	436 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**53066**	4000 K	449 lm	**N**		

I-Cube_2 | Bollards | 100-240 V | arrayLED 3,5 W 350 mA

IK05 IP65



type			colour			optics	
Grey	CRI 80	**53075**	3000 K	436 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**53076**	4000 K	449 lm	**N**		

Quality. Stone. **Rock**

Rock

Single or dual emission, case covered by agglomerate quartz and anodyzed internal structure. Available in three finishes: white, sand or gray, suitable for all living spaces. Led source integrated driver and diffuser in tempered glass.

+ graphic lighting effects
+ Led source
+ anti stain case

Wall light version

586

Rock

Rock series is very versatile, rigorous and minimal design: a series realized in agglomerated quartz, an extraordinary material, derived by Bretonstone®System technology. The Rock fixtures, available in three finishes, are perfect for every landscape or ourdoor project, thanks to their natural colors finish. Thanks to material peculiar properties, Rock series is very resistant to every weather condition.







Material

The quartz agglomerate is a material with extraordinary physical and chemical properties, realized with Bretonstone®System technology through a particular vibro- compaction vacuum process. Obtained by mixing siliceous sand or pure quartz (95%) with structural resin, polyester (5%) and UV rays stabilized colored pigments, this material maintains the original components physical-mechanical properties, resulting therefore shocks, abrasion and to chemical and atmospheric agents resistant, and also showing remarkable aesthetic qualities. These qualities are even more enhanced by the "Shield", a stain resistant treatment creating over material surface a non-absorbent silica thin film, ensuring high performance and long life and flawless appearance, even without using chemical cleaners.

Rock_1 | Bollard | 100-240 V | topLED 4 W 350 mA

IK05 IP55



type			colour			optics	
Grey	CRI 80	**59195**	3000 K	700 lm	**W**	diffused	**00**
Sand	CRI 80	**59194**	4000 K	661 lm	**N**		

Suggested accessories

60770

stirrup

Rock_2 | Bollard | 100-240 V | topLED 8 W 350 mA

IK05 IP55



type			colour			optics	
Grey	CRI 80	**59193**	3000 K	1461 lm	**W**	diffused	**00**
Sand	CRI 80	**59192**	4000 K	1370 lm	**N**		

Suggested accessories



60770

stirrup

Rock_3 | Bollard | 100-240 V | topLED 19 W 500 mA

IK05 IP55



type			colour			optics	
Grey	CRI 80	**59197**	3000 K	2514 lm	**W**	diffused	**00**
Sand	CRI 80	**59196**	4000 K	2297 lm	**N**		

Suggested accessories



60770

stirrup

bcc Banca di

Caraglio

D-Retta

design: RIGO

Light with a frontal diffusive light or an emission directed on the wall. Case in technic wood, teak veneer surface or aluminum gray smooth surface finish, available in two heights. Stainless steel fixing and PMMA satin diffuser. Strip LED source.

+ diffusive emission
+ technic wood
+ LED source

D-Retta_1 | Bollards | 180-260 V | topLED 5 W

IK05 IP65



type			colour			optics	
Grey	CRI 80	**64125**	3000 K	320 lm	**W**	diffused	**00**
Brown	CRI 80	**64120**					

D-Retta_2 | Bollards | 180-260 V | topLED 5 W

IK05 IP65



type			colour			optics	
Grey	CRI 80	**64135**	3000 K	320 lm	**W**	diffused	**00**
Brown	CRI 80	**64130**					

WOODN
SPECIES UNICA

Harmony between nature and humans also passes through smart lighting, both in terms of source selection and material selection. D-Retta offers a pure, yet affordable lighting, since it is LED-based and combined with a highly technological material, Woodn™ technical wood: chemical and physical strength, long lasting over time and environmentally friendly are the major assets of this material that, even though it is made from polymers, it has a natural and warm look, typical of wood. A pole whose aesthetics blends in perfectly well with a garden, in its wooden finish, but also with urban landscapes, in its grey finish.

Cu-Flex

Brown copper flexible and sinuous stems, ground fixed with a solid plastic base, with two, three or six LED sources, included driver. Modeling stems as you like. Small lighting heads with integrated and sealed diode, with a specific waterproof resin. Perfect for suggestive and invisible landscape compositions, as gardens or parks.

Brand new Bright versions

Cu-flex series is enhanced by new versions, with a peculiar opal diffuser, sealing every arm source. During the night, the lighting fixtures seems like micro luminous points, similar to fireflies, enhanching the landscape with its magical and romantic lighting.

Accent light

Its special body defines the product, it can be molded according to the project needs, illuminating different subjects with its accent lighting effect.



Cu-Flex_2 | Bollards | 100-240 V | 2 powerLED 1,5 W | 3 W 450 mA



type			colour			optics	
Copper	CRI 80	**61160**	3000 K	328 lm	**W**	diffused	**00**
			4000 K	346 lm	**N**		

Suggested accessories

14931

Pegs

Cu-Flex_3 | Bollards | 100-240 V | 3 powerLED 1,5 W | 4,5 W 450 mA



type			colour			optics	
Copper	CRI 80	**61170**	3000 K	492 lm	**W**	diffused	**00**
			4000 K	519 lm	**N**		

Suggested accessories

14931

Pegs

Cu-Flex_6 | Bollards | 100-240 V | 6 powerLED 1,5 W | 9 W 500 mA



type			colour			optics	
Copper	CRI 80	**61180**	3000 K	1080 lm	**W**	diffused	**00**
			4000 K	1140 lm	**N**		

Suggested accessories

14931

Pegs

Cu-Flex_2 bright | Bollards | 100-240 V | 2 powerLED 1,5 W | 3 W 450 mA



type			colour			optics	
Copper	CRI 80	**61161**	3000 K	328 lm	**W**	diffused	**00**
			4000 K	346 lm	**N**		

Suggested accessories

14931

Pegs

Cu-Flex_3 bright | Bollards | 100-240 V | 3 powerLED 1,5 W | 4,5 W 450 mA



type			colour			optics	
Copper	CRI 80	**61171**	3000 K	492 lm	**W**	diffused	**00**
			4000 K	519 lm	**N**		

Suggested accessories

14931

Pegs

Cu-Flex_6 bright | Bollards | 100-240 V | 6 powerLED 1,5 W | 9 W 500 mA



type			colour			optics	
Copper	CRI 80	**61181**	3000 K	1080 lm	**W**	diffused	**00**
			4000 K	1140 lm	**N**		

Suggested accessories

14931

Pegs

Wall + Ceiling

Wall + Ceiling

Cem

Cem_C

564

Cem_W1

564

Cem_W2

564

Cem_W3

564

Cem_W4

565

Cem_WF1

568

Cem_WF2

568

Peak

Peak-Maxi_W

571

Stalk

Stalk_W1

575

Stalk_W2

575

Stalk_W3

575

Stick

Stick_W

577

Dual Out

Dual Out_W1

579

Dual Out_W2

579

Dual Out_W3

579

I-Cube

I-Cube_S

583

I-Cube_W

583

Rock

Rock_W1

587

Rock_W2

587

Rock_W3

587

Rock_W4



587

Vision

Vision_S

591

Vision_W

591

Vision_WJ

591

Wall + Ceiling

Outdoor coordinated solutions

Perfect solutions to indicate linkages, entrances or to highlight precise architectural details. It's a coordinated and complete series able to customize outdoor spaces, with luminous lines or points perfectly integrated in the landscape architecture. Light enhances surfaces, materials and textures. Grazing, diffusive or concentrated lighting effects, suitable for every urban residential or hospitality context. An outdoor interpretation considering space perception and paths safety.





Innovative. Concrete. **Cem**

new

Cem

Material light

Concrete lamp available in five versions and three sizes, wall, stairs light and ceiling. Grazing and punctual lighting for paths and façades, warm white LED source. Tailor made lens defining precise light edges, avoiding leaks. Some color variations due to natural material, perfect for every outdoor space.

+ grazing and punctual lighting
+ concrete frame
+ LED source

Cem

Concept

Concrete reliability and strength is reinterpreted through new compact forms and smooth edges design. Cem exploits the latest generation LEDs potential technologies provoding graphics or diffusive lighting effects, allowing the outdoor space customization with a contemporary and unique sign.



Range

A complete range that includes wall or ceiling installation versions with grazing light effects and accent solutions for pathway lighting.



Harmony of gray

The Cem case is in real concrete.
Any surface discoloration or imperfection on case certifies that the production process quality is almost handmade.



Lighting effects

Smooth and border defined lighting is perfect to illuminate outdoor spaces.



Cem_W1 | Wall Lights | 100-240 V | arrayLED 6,5 W 700 mA



type			colour			optics	
Cement	CRI 80	**64561**	3000 K	884 lm	**W**	diffused	**00**
			4000 K	884 lm	**N**		

Cem_W2 | Wall Lights | 100-240 V | arrayLED 6,5 W 700 mA



type			colour			optics	
Cement	CRI 80	**64560**	3000 K	884 lm	**W**	diffused	**00**
			4000 K	884 lm	**N**		

Cem_W3 | Wall Lights | 180-264 V | topLED 14 W 350 mA





type			colour			optics	
Cement	CRI 80	**64562**	3000 K	1773 lm	**W**	diffused	**00**
			4000 K	1937 lm	**N**		

Cem_W4 | Wall Lights | 100-240 V | 1 x powerLED 2 W 500 mA



type			colour			optics	
Cement	CRI 80	**64563**	3000 K	144 lm	**W**	60°	**60**
			4000 K	180 lm	**N**		

Cem_C | Ceiling Lights | 220-240 V | arrayLED 7 W 700 mA





type			colour			optics	
Cement	CRI 80	**64564**	3000 K	760 lm	**W**	70°	**70**
			4000 K	760 lm	**N**		

Cem_WF1 | Wall Lights | 1 x powerLED 2 W 500 mA

C.C. IP65



type		colour		optics	
Cement CRI 80	**64506**	3000 K 144 lm	**W**	diffused	**00**

Suggested accessories

89422

ON/OFF
1-2 art.

89423

ON/OFF
2-3 art

65002

65002

Cem_WF2 | Wall Lights | TopLED 7,5 W 180 mA

C.C. IP65





type		colour		optics	
Cement CRI 80	**64505**	3000 K 975 lm	**W**	diffused	**00**

Suggested accessories



62427

SWITCH DIM
1 art.

65005

Outer casing

Peak-Maxi_W

Concept

An essential and compact element, which can be easily used in any situation. The pure shape of this appliance has been designed to be easily matched with any architectural style. Whether it is a historical city centre or a super modern area, PEAK allows to light up and enhance public places without being visible.

Peak / Peak-Maxi range

450

Peak-Maxi_W | Wall Lights | 100-240 V | PowerLED 24 W 350 mA

IK08 IP65



type			colour			optics	
Grey	CRI 80	**65080**	3000 K	2867 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**65081**	4000 K	3566 lm	**N**		
Cor-Ten	CRI 80	**65079**					

Peak-Maxi_W | Wall Lights | 100-240 V | PowerLED 36 W 550 mA

IK08 IP65



type			colour			optics	
Grey	CRI 80	**65084**	3000 K	4280 lm	**W**	Asym.	**07**
BK Grey	CRI 80	**65085**	4000 K	5323 lm	**N**		
Cor-Ten	CRI 80	**65083**					

Peak-Maxi_W



Breathability control

The exclusive TCS® system removes damp inside the heads of the pole, making them last for longer.



Optics

PMMA optics, highly resistant to temperature and UV rays.

Peak-Maxi_W 24W

The 24W versions are a good solution to light up pedestrian areas in the cities. The neutral design of the casing makes it invisible once it is installed on the wall.





***Example of installation with 15-metre centre distance, h 4.5 m.**

Peak-Maxi_W 35W

The 35W versions can be used under the eaves. When combined with special "road" lenses, they can light up both the wall and the walking area, thus producing a highly functional lighting effect inside the city.





***Example of installation with 15-metre centre distance, h 6 m.**

Stalk

Wall mounted fixture, anodized aluminum minimal design. Available in two versions and in four emissions typology: direct, indirect, lower and front. Allowing a great compositional freedom, for a decorative and suggestive lighting. Led or fluorescent source, for different lighting effects.

+ different emissions
+ LED source
+ minimum dimensions

Bollards

498

Stalk_W1 | Wall Lights | 180-264 V | topLED 8 W



type			colour			optics	
Grey	CRI 80	**63405**	3000 K	828 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63406**	4000 K	879 lm	**N**		

Stalk_W2 | Wall Lights | 180-264 V | topLED 8 W



type			colour			optics	
Grey	CRI 80	**63415**	3000 K	828 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63416**	4000 K	879 lm	**N**		

Stalk_W3 | Wall Lights | 180-264 V | topLED 8 W



type			colour			optics	
Grey	CRI 80	**63425**	3000 K	828 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**63426**	4000 K	879 lm	**N**		

Stick

Dual emission wall mounted fixture, with Led source. Grazing and diffusive lighting effect on the wall. Aluminum case with polyester coating for highest outdoor resistance, with a protective surface pretreatment. Anti-crash satin PMMA diffuser, stainless steel brackets and screws. Electronic power supply included.

+ diffusive emission
+ minimal design

Bollards

520

Stick_W | Wall Lights | 220 - 240 | stripLED 8 W



type		colour			optics	
White	**62404**	3000 K	512 lm	**W**	diffused	**00**
Grey	**62405**					
Cor-Ten	**62406**					

Dual Out

Wall mounted fixture with single or dual light emission, available with concentrating lens for a more scenographic lighting. Available with LED Array source for open beams or PowerLED for narrow beams. Integrated electronic power supply. Aluminum case minimal design, suitable for terraces and covered paths.

+ direct and indirect light
+ LED source
+ minimal design





Dual Out_W1 | Wall Lights | 220-240 V | arrayLED 9,5 W 250 mA



type			colour			optics	
Grey	CRI 80	**59385**	3000 K	1131 lm	**W**	60°	**60**
			4000 K	1214 lm	**N**		
Cor-Ten	CRI 80	**59386**	3000 K	1131 lm	**W**	60°	**60**
			4000 K	1214 lm	**N**		

Dual Out_W2 | Wall Lights | 220-240 V | arrayLED 19 W 500 mA



type			colour			optics	
Grey	CRI 80	**59365**	3000 K	2262 lm	**W**	60°	**60**
			4000 K	2428 lm	**N**		
Cor-Ten	CRI 80	**59366**	3000 K	2262 lm	**W**	60°	**60**
			4000 K	2428 lm	**N**		

Dual Out_W3 | Wall Lights | 100-240 V | PowerLed 4W 700mA UP+ arrayLED 9,5W 250mA DOWN



type			colour			optics	
Grey	CRI 80	**59375**	3000 K	1331 lm	**W**	3° + 60°	**36**
			4000 K	1414 lm	**N**		
Cor-Ten	CRI 80	**59376**	3000 K	1331 lm	**W**	3° + 60°	**36**
			4000 K	1414 lm	**N**		

I-Cube

design: RIGO

Ceiling and wall mounted spot with LED Array source, for different lighting effects. Extruded aluminum case, with antioxidative treatment and polyester powder coating, lead glass diffuser.

+ lead glass diffuser
+ LED source
+ minimum dimensions

Bollards

532

I-Cube_S | Ceiling Lights | 100-240 V | arrayLED 3,5 W 350 mA

IK05 IP65



type			colour			optics	
Grey	CRI 80	**53055**	3000 K	436 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**53056**	4000 K	449 lm	**N**		

I-Cube_W | Wall Lights | 100-240 V | arrayLED 3,5 W 350 mA

IK05 IP65



type			colour			optics	
Grey	CRI 80	**53045**	3000 K	436 lm	**W**	diffused	**00**
Cor-Ten	CRI 80	**53046**	4000 K	449 lm	**N**		



Quality. Stone. **Rock**

Rock_W

Wall lamp with single or dual emission realized in agglomerated quartz, an extraordinary material, derived by Bretonstone®System technology.
The Rock fixtures, available in three finishes, are perfect for every landscape or ourdoor project, thanks to their natural colors finish. Thanks to material peculiar properties, Rock is very resistant to every weather condition.

Bollards

538





Rock_W1 | Wall Lights | 100-240 V | arrayLED 3,2 W 350 mA

type			colour			optics	
White	CRI 80	**60794**	3000 K	436 lm	**W**	diffused	**00**
Grey	CRI 80	**60795**	4000 K	449 lm	**N**		
Sand	CRI 80	**60791**					

Rock_W2 | Wall light | 100-240 V | arrayLED 3,2 W 350 mA



type			colour			optics	
White	CRI 80	**60774**	3000 K	436 lm	**W**	diffused	**00**
Grey	CRI 80	**60775**	4000 K	449 lm	**N**		
Sand	CRI 80	**60771**					

Rock_W3 | Wall Lights | 190-250 V | arrayLED 6,4 W 350 mA



type			colour			optics	
White	CRI 80	**60714**	3000 K	872 lm	**W**	120°	**12**
Grey	CRI 80	**60715**	4000 K	898 lm	**N**		
Sand	CRI 80	**60711**					

Rock_W4 | Wall Lights | 220-240 V | topLED 9,5 W 250 mA



type			colour			optics	
White	CRI 80	**60734**	3000 K	1389 lm	**W**	diffused	**00**
Grey	CRI 80	**60735**	4000 K	1472 lm	**N**		
Sand	CRI 80	**60731**					

Vision

Adjustable wall or ceiling spot. Single or dual emission, natural aluminum case perfect for every living space, for an accent and punctual lighting. Available with fluorescent or LED source for different lighting effects on walls.

+ adjustable spot
+ coordinated range
+ LED source

Outdoor Spotlights

406

Vision_S | Ceiling Lights | 220 - 240 V | 1xGU10

IK06 IP65



type		source	optics
Grey	51495	1xGU10 35W Max	variable
Cor-Ten	51496		

LED

Vision_W | Wall Lights | 220 - 240 V | 2xGU10

IK06 IP65



type		source	optics
Grey	51385	2xGU10 35W Max	variable
Cor-Ten	51386		

LED

Vision_WJ | Outdoor spotlights | 220 - 240 V | 1xGU10

IK06 IP65



type		source	optics
Grey	51365	1xGU10 50W Max	variable
Cor-Ten	51366		

LED

Strip. **LED**

Ribbon Basic | LED strip | stripLED 4,8 W / m 24 V

C.V. IP20



1 m piece	CRI	colour	flux	5 m reel	CRI	colour	flux
98341	CRI 80	2500 K	270 lm	**98342**	CRI 80	2500 K	1350 lm
89106	CRI 80	2700 K	360 lm	**98011**	CRI 80	2700 K	1800 lm
98555	CRI 80	3000 K	365 lm	**98556**	CRI 80	3000 K	1825 lm
89975	CRI 80	4000 K	370 lm	**98012**	CRI 80	4000 K	1850 lm
89105	CRI 80	5000 K	390 lm	**98010**	CRI 80	5000 K	1950 lm

89408	89487	84829	99331	99332
ON/OFF	ON/OFF	ON/OFF	ON/OFF	1-10V
1 m	1 - 3 m	1 - 5 m	1 - 31 m	1 - 31 m

Ribbon Plus | LED strip | stripLED 3,6 W/m 24 V

C.V. IP20



1 m piece	CRI	colour	flux	5 m reel	CRI	colour	flux
98734	CRI 90	2700 K	370 lm	**98635**	CRI 90	2700 K	1850 lm
98735	CRI 90	3000 K	375 lm	**98636**	CRI 90	3000 K	1875 lm
98736	CRI 90	4000 K	380 lm	**98637**	CRI 90	4000 K	1900 lm

89408	89487	84829	99331	99332
ON/OFF	ON/OFF	ON/OFF	ON/OFF	1-10V
1 m	1 - 3 m	1 - 6 m	1 - 41 m	1 - 41 m

Made in Italy | 3 years warranty | CRI 90 hi-resolution | 28/35 LED hi-technology

Ribbon Hi-Flux | LED strip | stripLED 14,4 W / m 24 V

C.V. IP20





1 m piece	CRI	colour	flux	5 m reel	CRI	colour	flux
98347	CRI 80	2500 K	810 lm	**98348**	CRI 80	2500 K	4050 lm
89411	CRI 80	2700 K	1080 lm	**98035**	CRI 80	2700 K	5400 lm
98561	CRI 80	3000 K	1090 lm	**98562**	CRI 80	3000 K	5450 lm
89979	CRI 80	4000 K	1110 lm	**98036**	CRI 80	4000 K	5550 lm
89410	CRI 80	5000 K	1170 lm	**98034**	CRI 80	5000 K	5850 lm

84829	99331	99332
ON/OFF	ON/OFF	1-10V
1 m	1 - 10 m	1 - 10 m

Ribbon Plus Hi-Flux | LED strip | stripLED 12,5 W/m 24 V

C.V. IP20



1 m piece	CRI	colour	flux	5 m reel	CRI	colour	flux
98737	CRI 90	2700 K	1280 lm	**98638**	CRI 90	2700 K	6400 lm
98738	CRI 90	3000 K	1295 lm	**98639**	CRI 90	3000 K	6475 lm
98739	CRI 90	4000 K	1390 lm	**98640**	CRI 90	4000 K	6500 lm

89487	84829	99331	99332
ON/OFF	ON/OFF	ON/OFF	1-10V
1 m	1 - 2 m	1 - 13 m	1 - 13 m

Made in Italy | 3 years warranty | CRI 90 hi-resolution | 28/35 LED hi-technology | up to 1000 lm/m hi-efficiency

Ribbon 120 LEDs/m | LED strip | stripLED 9,6 W / m 24 V

C.V. IP20





1 m piece	CRI	colour	flux	5 m reel	CRI	colour	flux
98075	CRI 80	2700 K	720 lm	**98078**	CRI 80	2700 K	3600 lm
98567	CRI 80	3000 K	722 lm	**98568**	CRI 80	3000 K	3610 lm
98450	CRI 80	3500 K	725 lm	**98451**	CRI 80	3500 K	3625 lm
98074	CRI 80	4000 K	740 lm	**98077**	CRI 80	4000 K	3700 lm
98073	CRI 80	5000 K	780 lm	**98076**	CRI 80	5000 K	3900 lm

89487	84829	99331	99332
ON/OFF 1 m	ON/OFF 1 - 2 m	ON/OFF 1 - 15 m	1-10V 1 - 15 m

Ribbon 240 LEDs/m | LED strip | stripLED 19,2 W / m 24 V

C.V. IP20





1 m piece	CRI	colour	flux	5 m reel	CRI	colour	flux
98081	CRI 80	2700 K	1440 lm	**98084**	CRI 80	2700 K	7200 lm
98569	CRI 80	3000 K	1450 lm	**98570**	CRI 80	3000 K	7250 lm
98080	CRI 80	4000 K	1480 lm	**98083**	CRI 80	4000 K	7400 lm
98079	CRI 80	5000 K	1560 lm	**98082**	CRI 80	5000 K	7800 lm

84829	99331	99332
ON/OFF 1 m	ON/OFF 1 - 7 m	1-10V 1 - 7 m

Ribbon Dynamic | LED strip | stripLED 19,2 W 24 V

C.V. IP20





1 m p.	colour	flux	5 m r.	colour	flux
98547	3000-6000 K	585-620 lm	**98548**	3000-6000 K	2925-3100 lm

99077	99074	99278
N/O button	1-10V, DALI controller	DMX

Ribbon RGBW | LED strip | stripLED 19,2 W / m 24 V

C.V. IP20





1 m piece	colour	5 m reel	colour
98740	RGBW	**98651**	RGBW

99076	99278
IR Remote	DMX

Dropper Basic | LED strip | stripLED 4,8 W / m 24 V

C.V. IP50

1 m piece	CRI	colour	flux	5 m reel	CRI	colour	flux
98343	CRI 80	2500 K	270 lm	**98344**	CRI 80	2500 K	1350 lm
89399	CRI 80	2700 K	360 lm	**98019**	CRI 80	2700 K	1800 lm
98557	CRI 80	3000 K	365 lm	**98558**	CRI 80	3000 K	1825 lm
89976	CRI 80	4000 K	370 lm	**98020**	CRI 80	4000 K	1850 lm
89398	CRI 80	5000 K	390 lm	**98018**	CRI 80	5000 K	1950 lm

89408	89487	84829	99331	99332
ON/OFF 1 m	ON/OFF 1 - 3 m	ON/OFF 1 - 5 m	ON/OFF 1 - 31 m	1-10V 1 - 31 m

Dropper Hi-Flux | LED strip | stripLED 14,4 W / m 24 V

C.V. IP50





1 m piece	CRI	colour	flux	5 m reel	CRI	colour	flux
98349	CRI 80	2500 K	810 lm	**98350**	CRI 80	2500 K	4050 lm
89641	CRI 80	2700 K	1080 lm	**98092**	CRI 80	2700 K	5400 lm
98565	CRI 80	3000 K	1090 lm	**98566**	CRI 80	3000 K	5450 lm
98085	CRI 80	4000 K	1110 lm	**98091**	CRI 80	4000 K	5550 lm
89642	CRI 80	5000 K	1170 lm	**98090**	CRI 80	5000 K	5850 lm

84829	99331	99332
ON/OFF 1 m	ON/OFF 1 - 10 m	1-10V 1 - 10 m

Dropper 120 LEDs/m | LED strip | stripLED 9,6 W / m 24 V

C.V. IP50



1 m piece	CRI	colour	flux	5 m reel	CRI	colour	flux
98571	CRI 80	3000 K	722 lm	**98572**	CRI 80	3000 K	3610 lm
98573	CRI 80	4000 K	740 lm	**98574**	CRI 80	4000 K	3700 lm
98575	CRI 80	5000 K	780 lm	**98576**	CRI 80	5000 K	3900 lm

89487	84829	99331	99332
ON/OFF 1 m	ON/OFF 1 - 2 m	ON/OFF 1 - 15 m	1-10V 1 - 15 m

Dropper RGB | LED strip | stripLED 14,4 W / m 24 V

C.V. IP50





1 m piece	colour	5 m reel	colour
89416	RGB	**98025**	RGB

99076	99278
IR Remote	DMX

Silicone_F Basic | LED strip | stripLED 4,8 W / m 24 V

C.V. IP66



1 m piece	CRI	colour		5 m reel	CRI	colour	
65095	CRI >70	3000 K	310 lm	**62759**	CRI >70	3000 K	1550 lm

89179	89359	99332
ON/OFF 1 - 5 m	ON/OFF 1 - 10 m	1-10V 1 - 31 m

Silicone_F 120 LEDs/m | LED strip | stripLED 9,6 W / m 24 V

C.V. IP66





1 m piece	CRI	colour		5 m reel	CRI	colour	
65096	CRI >70	3000 K	620 lm	**62761**	CRI >70	3000 K	3100 lm

89179	89359	99332
ON/OFF 1 - 2,5 m	ON/OFF 1 - 5 m	1-10V 1 - 15 m

Silicone_F 180 LEDs/m | LED strip | stripLED 14,4 W / m 24 V

C.V. IP67



5 m reel	CRI	colour	
64569	CRI >80	3000 K	5500 lm

89179	89359	99332
ON/OFF 1 - 1,5 m	ON/OFF 1 - 3 m	1-10V 1 - 10 m

Electronics





Electronics

Over Voltage Protection

Defender

604

ON/OFF Control gears C.C.

Slim

605

Hans

605

Simon

605

Werner



606

Leon

606

Freeman

606

Hugo

606

Mini_Aqualed

608

Edmond

608

Control System C.C.

Boson

610

Ludwig

610

Photon

610

Andre

611

Argo

611

Serban

611

Lise

611

ON/OFF Control gears C.V.

Reson_150

612

Niels



612

Gustav



612

Ernest

613

Slim

613

Lingotto

613

Maxi_Aqualed

614

Giant_Aqualed

614

Control System C.V.

Reson_150

614

Nyquist

614

Bode

614

Erwin

614

Smith

615

Spectrum

615

Power Switching C.V.

Peta_Exa_75

616

Peta_Exa_150

616

Peta_Exa_240

616

Defender | Over Voltage Protection

T3 IP65



U_N	I_N	I_{MAX}	I_{TOT}	U_{OC}	U_P	
230V AC	5kA	10kA	20kA	10kV	≤ 1.5kV	**99341**

U_N	Nominal operating Voltage
I_N	Nominal impulse discharge current
I_{MAX}	Total impulse current (L+N+PE)
I_{TOT}	Max. total impulse current (L+N+PE)
U_{OC}	Surge protection level [L-N] [L+N-PE]
UP	Voltage protection level [L-N] [L/N-PE]

Surge arrester for T3 indirect strikes (CEI EN 61643-11/A11) with test class III (CEI EN 61643-11 Ed.1).
Multi-pole surge arrester with spark gap and varistors connected in series to active phases.
Combined construction with trigger with limitation.
No leakage current.
No follow mains current due to the varistor/spark gap combination.

INSTALLATION NOTICE

The installation of one surge arrester only on each line input may not ensure effective protection for the whole system.
Lighting fixtures installed at 10 m downstream the surge arrester are considered as 100% protected.
If the cable length between the surge arrester and the lighting fixtures exceeds 10 m, protection should be enhanced by placing another surge arrester near the lighting fixtures that need to be protected (within 10 m).
Maximum protection is achieved by installing the surge arresters as described above for each system line.





Slim | On/Off Driver 190~250V AC / 180~275V DC

F M M C.C. IP40



range	output	input	eff.	PF	surge	
1-2 W powerLED	350mA 6.6V	190~250V AC	80%	0.6 C	4 kV	**89144**
3-6 W powerLEDs	350mA 20V	190~250V AC	80%	0.6 C	4 kV	**89145**
1,5-3 W powerLEDs	500mA 6.6V	190~250V AC	80%	0.6 C	4 kV	**99195**
3-4,5 W powerLED	500mA 10V	190~250V AC	80%	0.6 C	4 kV	**89146**

Instantaneous output current limitation to protect LED upon switching on.
A switch may be installed along the output line.
Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.

Hans | On/Off Driver 220~240 V AC

F M M C.C. IP20



range	output	input	eff.	PF	surge	
2-8 W powerLEDs	700mA 14 V	220-240 V AC	-	0.95	0,5 kV	**62437**

Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.

Simon | On/Off Driver 180~300V AC

F M M C.C. IP40



range	output	input	eff.	PF	surge	
12,5 W arrayLED	350mA 38V	180~300V AC	89%	0.9 C	4 kV	**99126**
4,5-9 W powerLEDs	500mA 20V	180~300V AC	89%	0.9 C	4 kV	**99128**

Smartwave™: optimum efficiency, long life, surge protection, high PF.
Protection against overtemperature, overload, open circuits and short circuits on the output line.

Simon_Easy-Plug | On/Off Driver 180~300V AC

C.C. IP40



range	output	input	eff.	PF	surge	
8 W topLED	200mA 39V	180~300V AC	89%	0.9 C	4 kV	**99368**
12 W topLED	400mA 36V	180~300V AC	89%	0.9 C	4 kV	**99260**

Easy Plug connector included.
Smartwave™: optimum efficiency, long life, surge protection, high PF.
Protection against overtemperature, overload, open circuits and short circuits on the output line.

Werner | On/Off Driver 220~240 V AC

C.C. IP20



range	output	input	eff.	PF	surge	
7,5 W arrayLED	200mA 37 V	220~300V AC	80%	0.8 C	0,5 kV	**62423**
9,3 W arrayLED	250mA 37 V	220~240 V AC	83%	0.8 C	0,5 kV	**62424**

Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.

Freeman | On/Off Driver 220~240 V AC

C.C. IP20



range	output	input	eff.	PF	surge	
1-16 W powerLEDs	700mA 28 V	220~240 V AC	-	0.95	0,5 kV	**62438**

Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.

Hugo | On/Off Driver 220~240 V AC / 220~240 V DC

C.C. IP20



range	output	input	eff.	PF	surge	
12-24 powerLEDs	700mA 42 V	220~240 V AC	-	0.95	1 kV	**62439**

Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.

Leon | On/Off Driver 180~300V AC

C.C. IP40



range	output	input	eff.	PF	surge	
18 W arrayLED	500mA 37V	180~300V AC	91%	0.95	4 kV	**99106**

Smartwave™: optimum efficiency, long life, surge protection, high PF.
Protection against overtemperature, overload, open circuits and short circuits on the output line.

Leon_Easy-Plug | On/Off Driver 180~300V AC

C.C. IP40



range	output	input	eff.	PF	surge	
15 W arrayLED	400mA 37V	180~300V AC	91%	0.95	4 kV	**99113**
23 W topLED	630mA 36V	180~300V AC	91%	0.95	4 kV	**99261**
18 W topLED	500mA 36V	180~300V AC	91%	0.95	4 kV	**99162**
25 W arrayLED	720mA 37V	180~300V AC	91%	0.95	4 kV	**99112**
30 W arrayLED	840mA 37V	180~300V AC	91%	0.95	4 kV	**99093**

Easy Plug connector included.
Smartwave™: optimum efficiency, long life, surge protection, high PF.
Protection against overtemperature, overload, open circuits and short circuits on the output line.

Edmond | On/Off Driver Multi Power 90 - 264 V AC / 170 - 280V DC

F M M C.C. IP20



range	output	input	eff.	PF	surge	
7,5 W topLED	180mA 41,5 V	90 - 264 V AC	82%	0,64	2 kV	**62427**
2 x 7,5 W topLED*	360mA 41,5 V	90 - 264 V AC	0,82	0,64	2 kV	

* parallel connection is required in order to power two devices

Reset protection against over temperature, overload, open circuit and short circuit on the output line.

Mini_Aqualed | On/Off Driver 190~250V AC / 260~360V DC

F M M C.C. IP67



range	output	input	eff.	PF	surge	
1-2 powerLEDs	500mA 6.6V	190~250V AC	80%	0.6 C	0.5 kV	**89422**
2-3 powerLEDs	500mA 10V	190~250V AC	80%	0.6 C	0.5 kV	**89423**

Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.

Boson | N/O button 1-10V Multi Power 190~250V AC / 180~275V DC

F M M C.C. DIM 1-10V IP40



range	output	input	eff.	PF	surge	
12,5 W arrayLED	350mA 37V	190~250V AC	87%	0.6 C	4 kV	**99115**
15 W topLED	350mA 45V	190~250V AC	87%	0.6 C	4 kV	
18 W arrayLED	500mA 37V	190~250V AC	87%	0.6 C	4 kV	
1,5 - 18 W powerLEDs	500mA 37V	190~250V AC	87%	0.6 C	4 kV	
20 W arrayLED	630mA 33V	190~250V AC	87%	0.6 C	4 kV	
2-20 W powerLEDs	630mA 33V	190~250V AC	87%	0.6 C	4 kV	

Dedicated terminal for choosing the intensity of the output current.
Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.
Settings controlled via 1-10V interface, potentiometer or N.O. button.
Possibility of connecting up to 50 drivers (via Sync bus).

Boson_Easy-Plug | N/O button 1-10V Multi Power 190~250V AC / 180~275V DC



range	output	input	eff.	PF	surge	
8 W topLED	220mA 37V	190~250V AC	87%	0.6 C	4 kV	**99116**
12 W topLED	350mA 37V	190~250V AC	87%	0.6 C	4 kV	**99262**
18 W topLED	500mA 36V	190~250V AC	87%	0.6 C	4 kV	
23 W topLED	630mA 36V	190~250V AC	87%	0.6 C	4 kV	

Easy Plug connector included.
Dedicated terminal for choosing the intensity of the output current.
Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.
Settings controlled via 1-10V interface, potentiometer or N.O. button.
Possibility of connecting up to 50 drivers (via Sync bus).

Photon | Push and Simply Dim DALI Multi Power 190~250V AC / 180~275V DC



range	output	input	eff.	PF	surge	
12,5 W arrayLED	350mA 37V	190~250V AC	87%	0.6 C	4 kV	**99114**
1-15 W powerLEDs	350mA 45V	190~250V AC	87%	0.6 C	4 kV	
18 W arrayLED	500mA 37V	190~250V AC	87%	0.6 C	4 kV	
1,5 -18 W powerLEDs	500mA 37V	190~250V AC	87%	0.6 C	4 kV	
20 W arrayLED	630mA 33V	190~250V AC	87%	0.6 C	4 kV	
2-20 powerLEDs	630mA 33V	190~250V AC	87%	0.6 C	4 kV	

Settings controlled via DALI interface or Simply DIM.
Optimization of the DALI signal transmission (immunity to bursts up to 4 kV).
Dedicated terminal for choosing the intensity of the output current.
Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.

Photon_Easy-Plug | Push and Simply Dim DALI Multi Power 190~250V AC / 180~275V DC



range	output	input	eff.	PF	surge	
8 W topLED	220mA 37V	190~250V AC	87%	0.6 C	4 kV	**99131**
12 W topLED	350mA 36V	190~250V AC	87%	0.6 C	4 kV	**99163**
18 W topLED	500mA 36V	190~250V AC	87%	0.6 C	4 kV	
23 W topLED	630mA 36V	190~250V AC	87%	0.6 C	4 kV	

Easy Plug connector included.
Settings controlled via DALI interface or Simply DIM.
Optimization of the DALI signal transmission (immunity to bursts up to 4 kV).
Dedicated terminal for choosing the intensity of the output current.
Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.

Ludwig | Push 1-10 V Multi Power 110~240 V AC / 176~280 V DC

1-10V F M M C.C. IP20



range	output	input	eff.	PF	surge	
7,3 W arrayLED	220mA 37 V	220~240 V AC	87%	0.95	2 kV	**62431**
9,3 W arrayLED	250mA 37 V	220~240 V AC	87%	0.95	2 kV	

Reset protection against over temperature, overload, open circuit and short circuit on the output line.
Adjustable by 1-10V interface, potentiometer and push.

Andre | Push and Simply Dim 1-10 V Multi Power 220~240 V AC / 220~240 V DC

Simply DIM 1-10V F M M C.C. IP20



range	output	input	eff.	PF	surge	
7,3 W arrayLED	200mA 37 V	220~240 V AC	87%	0.96	2 kV	**62432**
9,3 W arrayLED	250mA 37 V	220~240 V AC	87%	0.96	2 kV	

Reset protection against over temperature, overload, open circuit and short circuit on the output line.
Dimming settings adjustable via DIP-SWITCH
Adjustment via interface 1-10 V, potentiometer, DALI and Push and Simply Dim.

Argo | Push and Simply Dim DALI Multi Power 190~250V AC / 180~275V DC

F M M C.C. Simply DIM DALI IP40



range	output	input	eff.	PF	surge	
1-12 w powerLEDs	350mA 39V	190~250V AC	87%	0.95	4 kV	**99344**
1,5-18 W powerLEDs	500mA 39V	190~250V AC	87%	0.95	4 kV	
2-24 W powerLEDs	630mA 39V	190~250V AC	87%	0.95	4 kV	

Settings controlled via DALI interface or Simply DIM.
Optimization of the DALI signal transmission (immunity to bursts up to 4 kV).
Dedicated terminal for choosing the current intensity.
Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.

Argo_Easy-Plug | Push and Simply Dim DALI Multi Power 190~250V AC / 180~275V DC

C.C. IP40



range	output	input	eff.	PF	surge	
25 W topLED	720mA 36V	190~250V AC	87%	0.95	4 kV	**99330**
30 W topLED	840mA 36V	190~250V AC	87%	0.95	4 kV	

Easy Plug connector included.
Settings controlled via DALI interface or Simply DIM.
Optimization of the DALI signal transmission (immunity to bursts up to 4 kV).
Dedicated terminal for choosing the current intensity.
Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.

Serban_Easy-Plug | Push and Simply Dim DALI 1-10V Multi Power 190~250V AC / 180~275V DC

C.C. IP40



range	output	input	eff.	PF	surge	
25 W arrayLED	720mA 37V	190~250V AC	86%	0.95	4 kV	**99188**
25 W topLED	720mA 36V	190~250V AC	86%	0.95	4 kV	
30 W arrayLED	840mA 37V	190~250V AC	86%	0.95	4 kV	**99187**
30 W topLED	840mA 36V	190~250V AC	86%	0.95	4 kV	

Easy Plug connector included.
Settings controlled via DALI interface, 1-10V, or Simply DIM.
Optimization of the DALI signal transmission (immunity to bursts up to 4 kV).
Possibility of choosing between linear or logarithmic dimming by means of a jumper.

Lise | Multi Power 100~240V AC / 180~275V DC

C.V. IP20



range	output	input	eff.	PF	surge	
2,5~70 W Bulbs Halo	12 V AC	230~240 V AC	91%	0.97	1 kV	**57350**
2,5~50 W Bulbs LED	12 V AC	230~240 V AC	91%	0.97	1 kV	

Reset protection against over temperature, overload, open circuit and short circuit on the output line.
Non-dimmable.
Max 4/5 LED lights.

Slim | On/Off Driver 190~250V AC / 180~275V DC 5 W

F M M C.V. IP40



range	output	input	eff.	PF	surge	
1-5 W stripLED	200mA 24V	190~250V AC	80%	0.6 C	4 kV	**89408**

Suitable to power constant-voltage LED strips, 5 mm LEDs and top LEDs.
Self-restoring protection against open circuits and short circuits on the output line.

Lingotto | On/Off Driver 190~250V AC / 180~275V DC 15 W

F M M C.V. IP40



range	output	input	eff.	PF	surge	
1-14,4 W stripLED	600mA 24V	190~250V AC	82%	0.6 C	0.5 kV	**89487**

Suitable to power constant-voltage LED strips, 5 mm LEDs and top LEDs.
Self-restoring protection against open circuits and short circuits on the output line.

Maxi_Aqualed | On/Off Driver 190~250V AC 24 W

F M M C.V. IP67



range	output	input	eff.	PF	surge	
1-24 W stripLED	1A 24V	190~250V AC	88%	0.8 C	2 kV	**89179**

Suitable to power constant-voltage LED strips, 5 mm LEDs and top LEDs.
Self-restoring protection against open circuits and short circuits on the output line.

Giant_Aqualed | On/Off Driver 90~264V AC / 127~370V DC 48 W

F M M C.V. IP67



range	output	input	eff.	PF	surge	
1-48 W stripLED	2A 24V	90~264V AC	89%	0.6 C	3 kV	**89359**

Suitable to power constant-voltage LED strips, 5 mm LEDs and top LEDs.
Self-restoring protection against open circuits and short circuits on the output line.

Niels | On/Off Driver 108~264 V AC / 120~288 V DC 35 W

F M M C.V. IP20



range	output	input	eff.	PF	surge	
35 W topLED	1,5A 24 V	120~240V AC	80%	0.91	1 kV	**62870**
35 W stripLED	1,5A 24 V	120~240V AC	80%	0.91	1 kV	

Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.
Suitable to power constant voltage StripLEDs and TopLEDs.

Gustav | On/Off Driver 108~264 V AC / 120~288 V DC 60 W

F M M C.V. IP20



range	output	input	eff.	PF	surge	
60 W topLED	2,5A 24 V	120~240V AC	80%	0.93	2 kV	**62880**
60 W stripLED	2,5A 24 V	120~240V AC	80%	0.93	2 kV	

Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.
Suitable to power constant voltage StripLEDs and TopLEDs.

Ernest | On/Off Driver 108~264 V AC / 120~288 V DC 150 W

F M M C.V. IP20



range	output	input	eff.	PF	surge	
150 W topLED	6,25A 24 V	120~240V AC	88%	0.95	2 kV	**62890**
150 W stripLED	6,25A 24 V	120~240V AC	88%	0.95	2 kV	

Self-restoring protection against overtemperature, overload, open circuits and short circuits on the output line.
Suitable to power constant voltage StripLEDs and TopLEDs.

Reson_150 | On/Off Driver 190~250V AC / 180~275V DC 150 W

F M M C.V. IP65



range	output	input	eff.	PF	surge	
1-150 W stripLED	6.25A 24V	190~250V AC	95%	0.98	5 kV	**99331**
1-150 W topLED	6.25A 24V	190~250V AC	95%	0.98	5 kV	

Suitable to power constant-voltage LED strips, 5 mm LEDs and top LEDs.
Self-restoring protection against open circuits and short circuits on the output line.
High efficiency, long life and high PF.

Reson_150_1-10V | 1-10V Multi Power 190~250V AC / 180~275V DC 150 W

F M M C.V. 1-10V IP65



range	output	input	eff.	PF	surge	
1-150 W stripLED	6.25A 24V	190~250V AC	95%	0.98	5 kV	**99332**
1-150 W topLED	6.25A 24V	190~250V AC	95%	0.98	5 kV	

Suitable to power constant-voltage LED strips, 5 mm LEDs and top LEDs.
Self-restoring protection against open circuits and short circuits on the output line.
High efficiency, long life and high PF.
Control via 1-10V interface, or potentiometer.

Ervin | Converter 24 V 120 W

DALI F M M III C.V. IP20 IP20



range	output	input	eff.	PF	surge	
1-120 W topLEDs	5A 24 V	24 V DC	95%	0.9 C	4 kV	**64576**

Suitable to power constant voltage StripLEDs and TopLEDs.
Adjustable via DALI interface.

Nyquist | N/O button Multi Channel 3ch. 24V DC 216 W

F M M III C.V. ERAL DIM IP40



range	output	input	eff.	
3ch. x (1-72 W stripLED/ch.)	3A 24V	24V DC	95%	**99077**
3ch. x (1-72 W topLED/ch.)	3A 24V	24V DC	95%	

Suitable to power constant-voltage LED strips, 5 mm LEDs and top LEDs.
0 to 100% dimming via N.O. button.
Each driver may be used as master or slave.
Possibility of connecting up to 20 drivers (via Sync bus).
Driver compatible with the power supply units of the Brain-Wave (99006) series.

Bode | DALI 1-10V Multi Channel 3ch. 24V DC 216 W

F M M III C.V. 1-10V DALI IP40



range	output	input	eff.	
3ch. x (1-72 W stripLED/ch.)	3A 24V	24V DC	95%	**99074**
3ch. x (1-72 W topLED/ch.)	3A 24V	24V DC	95%	

Suitable to power constant-voltage LED strips, 5 mm LEDs and top LEDs.
Control via DALI interface, 1-10V or potentiometer.

Smith | Telecomando e Ricevitore IR Multi Channel 3ch. 24V DC 216 W

F M M III C.V. IP40



range	output	input	eff.	
3ch. x (1-150 5mmLED/ch.)	3A 24V	24V DC	95%	**99076**
3ch. x (1-72 W stripLED/ch.)	3A 24V	24V DC	95%	
3ch. x (1-72 W topLED/ch.)	3A 24V	24V DC	95%	

Suitable to power constant-voltage LED strips, 5 mm LEDs and top LEDs.
3-channel device to control and manage RGB LED strips.
Interface with input for IR receiver and Sync bus.
Each driver may be used as master or slave.
A driver used in the master mode can control up to 20 slave devices.
Master driver setting via IR remote control only.
Driver compatible with the power supply units of the RGB System (99140) series.

99125
IR Remote

99024
IR sensor

99023
IR sensor

Spectrum | DMX Multi Channel 4ch. 24V DC 288 W

F M M III C.V. DMX 512 IP40



range	output	input	eff.	
4ch. x (1-144 5mmLED/ch.)	3A 24V	24V DC	95%	**99278**
4ch. x (1-72 W stripLED/ch.)	3A 24V	24V DC	95%	
4ch. x (1-72 W topLED/ch.)	3A 24V	24V DC	95%	

Suitable to power LED strips and 5 mm LEDs, also in RGB version.
The DMX address can be selected via 3 rotary selectors.
Compatible with USITT DMX 512-A protocol.
A maximum of 256 lighting fixtures can be installed on the same DMX bus.
DMX addressing: CH1 - CH512.
DMX line maximum length: 300 m.
Possibility to manage 3 or 4 DMX addresses/channels (RGB - RGBW – WRGB) through a jumper.

84895
Cable and connector

84994
Cable and connector

84885
Cable and connector

84869
Connector

84870
Connector

84865
Cable

Peta / Exa | Switching Driver 88~264V AC / 125~373V DC 75 W

C.V.



type	output	input	cooling	PF	
Peta	3.2A 24V	88~264V AC	Natural Convection	No PFC	**84700**

Self-restoring protection against open circuits and short circuits on the output line.

Peta / Exa | Switching Driver 88~264V AC / 248~373V DC 150 W

C.V.



type	output	input	cooling	PF	
Peta	6.5A 24V	88~264V AC	Natural Convection	No PFC	**84701**

Self-restoring protection against open circuits and short circuits on the output line.

Peta / Exa | Switching Driver 88~264V AC / 248~373V DC 24 W

C.V.



type	output	input	cooling	PF	
Peta	10A 24V	88~264V AC	Forced convection	0.95	**84702**

Self-restoring protection against open circuits and short circuits on the output line.

Emergency

Emergency

Escape Route

Fled_E

622

Fled_W

623

Fled_P

624

Fled_O

625

Escape Signals

Onsight_W

626

Onsight_SF

629

Onsight_RF

630

EMergy

632

Fled_E | Escape route | 220-240 V | powerLED 2 W 500 mA

EM IP40



type				colour		optic
Std.	White	CRI <70	**62504**	5000 K	166 lm	Elliptic
UPS	White	CRI <70	**64804**			

89373

Outer casing

Fled_E | Escape route | 220-240 V | powerLED 2 W 500 mA

EM IP40



type				colour		optic
Std.	White	CRI <70	**62514**	5000 K	166 lm	Elliptic
UPS	White	CRI <70	**64814**			

89373

Outer casing

EMERGENCY LIGHTING FOR ESCAPE ROUTES

Non-maintained self-contained emergency luminaire fitted with an optics specifically designed for application along escape routes, compliant with the European EN 1838 standard.
The FLED-E recessed version disappears into the false ceiling, perfectly integrating into the environment thanks to its 2 mm thickness and its compact dimensions. The surface-mounted version can be easily installed using the functional bracket and boasts a refined look with a soft silhouette that discreetly complements the ordinary lighting fixtures.
FLED-E features a nickel cadmium battery pack with 3 hour duration.



Fled_W | Escape route | 220-240 V | powerLED 2 W 500 mA

EM IP40



type				colour		optic
Std.	White	CRI <70	**62564**	5000 K	166 lm	Elliptic
UPS	White	CRI <70	**64864**			

62630

Outer casing

EMERGENCY LIGHTING FOR ESCAPE ROUTES

Non-maintained self-contained emergency luminaire fitted with an asymmetric optics specifically designed for application along escape routes, compliant with the European EN 1838 standard.
A recessed luminaire that disappears into plasterboard as well as masonry walls thanks to its specific outer casing.
FLED-W features a nickel cadmium battery pack with 3 hour duration.



Fled_P | Escape route | 220-240 V | powerLED 2 W 500 mA

EM IP40





type				colour		optic
Std.	White	CRI <70	**62524**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64824**			

89373

Outer casing

Fled_P | Escape route | 220-240 V | powerLED 2 W 500 mA

EM IP40





type				colour		optic
Std.	White	CRI <70	**62534**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64834**			

89373

Outer casing

ANTI-PANIC EMERGENCY LIGHTING

Non-maintained self-contained emergency luminaire fitted with an optics specifically designed for application in (anti-panic) open areas, compliant with the European EN 1838 standard.
The FLED-P recessed version disappears into the false ceiling, perfectly integrating into the environment thanks to its 2 mm thickness and its compact dimensions. The surface-mounted version can be easily installed using the functional bracket and boasts a refined look with a soft silhouette that discreetly complements the ordinary lighting fixtures.
FLED-P features a nickel cadmium battery pack with 3 hour duration.

Fled_O | Escape route | 220-240 V | powerLED 2 W 500 mA





type				colour		optic
Std.	White	CRI <70	**62544**	5000 K	166 lm	60°
UPS	White	CRI <70	**64844**			

89373

Outer casing

Fled_O | Escape route | 220-240 V | powerLED 2 W 500 mA





type				colour		optic
Std.	White	CRI <70	**62554**	5000 K	166 lm	60°
UPS	White	CRI <70	**64854**			

89373

Outer casing

EMERGENCY PUNCTUAL LIGHTING

Self-contained lighting fixture for non-permanent emergency lighting to highlight escape doors for emergency use, staircases, uneven floors, indicated emergency exits, changes in direction, intersections of corridors, landings outside the emergency exits, as well as fire-prevention devices, emergency call devices and first aid spots, pursuant to European standard EN 1838, with an optics specially designed to illuminate with precision.
The FLED-O recessed version disappears into the false ceiling, perfectly integrating into the environment thanks to its 2 mm thickness and its compact dimensions. The surface-mounted version can be easily installed using the functional bracket and boasts a refined look with a soft silhouette that discreetly complements the ordinary lighting fixtures.
FLED-O features a nickel cadmium battery pack with 3 hour duration.

Onsight_W | Escape signal | 220-240 V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62574.L**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64884.L**			

Onsight_W | Escape signal | 220-240 V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62574.R**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64884.R**			

Onsight_W | Escape signal | 220-240 V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62574.U**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64884.U**			

Onsight_W | Features

	Std.	UPS
Casing	die cast aluminium	die cast aluminium
Diffuser	PMMA	PMMA
Sign	silk-screened pictogram	silk-screened pictogram
Sign colour	white/green	white/green
Power supply (62574)	kit driver + 7.2 V 1600 mA/h NiCd battery pack	kit driver + 7.2 V 1600 mA/h NiCd battery pack
Power supply (62624)	kit driver + 4.8 V 1600 mA/h NiCd battery pack	kit driver + 4.8 V 1600 mA/h NiCd battery pack
Duration	1 hour (recharge period 12 hours) 3 hours (recharge period 24 hours)	1 hour (recharge period 12 hours) 3 hours (recharge period 24 hours)
Self-test	yes, with integrated LED light indicator	yes, with integrated LED light indicator
IP	40	40
Power	2 W	2 W

Onsight_W | Escape signal | 220-240 V | powerLED 4 W 350 mA



type				colour		optic
Std.	White	CRI <70	**62624.L**	5000 K	242 lm	Diff.+60°
UPS	White	CRI <70	**64874.L**			

Onsight_W | Escape signal | 220-240 V | powerLED 4 W 350 mA



type				colour		optic
Std.	White	CRI <70	**62624.R**	5000 K	242 lm	Diff.+60°
UPS	White	CRI <70	**64874.R**			

Onsight_W | Escape signal | 220-240 V | powerLED 4 W 350 mA



type				colour		optic
Std.	White	CRI <70	**62624.U**	5000 K	242 lm	Diff.+60°
UPS	White	CRI <70	**64874.U**			

Onsight_W | Features

	Std.	UPS
Casing	die cast aluminium	die cast aluminium
Diffuser	PMMA	PMMA
Sign	silk-screened pictogram	silk-screened pictogram
Sign colour	white/green	white/green
Power supply (62574)	kit driver + 7.2 V 1600 mA/h NiCd battery pack	kit driver + 7.2 V 1600 mA/h NiCd battery pack
Power supply (62624)	kit driver + 4.8 V 1600 mA/h NiCd battery pack	kit driver + 4.8 V 1600 mA/h NiCd battery pack
Duration	1 hour (recharge period 12 hours) up to 3 hours (recharge period 24 hours)	1 hour (recharge period 12 hours) 3 hours (recharge period 24 hours)
Self-test	yes, with integrated LED light indicator	yes, with integrated LED light indicator
IP	40	40
Power	2 W	2 W

Onsight_SF | Escape signal | 220-240 V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62584.L**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64904.L**			

Onsight_SF | Escape signal | 220-240 V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62584.R**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64904.R**			

Onsight_SF | Escape signal | - V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62584.U**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64904.U**			

Onsight_SF | Features

	Std.	UPS
Casing	die cast aluminium	die cast aluminium
Diffuser	PMMA	PMMA
Sign	silk-screened pictogram	silk-screened pictogram
Sign colour	white/green	white/green
Power supply (62574)	kit driver + 7.2 V 1600 mA/h NiCd battery pack	kit driver + 7.2 V 1600 mA/h NiCd battery pack
Power supply (62624)	kit driver + 4.8 V 1600 mA/h NiCd battery pack	kit driver + 4.8 V 1600 mA/h NiCd battery pack
Duration	1 hour (recharge period 12 hours) 3 hours (recharge period 24 hours)	1 hour (recharge period 12 hours) 3 hours (recharge period 24 hours)
Self-test	yes, with integrated LED light indicator	yes, with integrated LED light indicator
IP	40	40
Power	2 W	2 W

Onsight_SF | Escape signal | Ceiling luminaires | 220-240 V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62594.U**	5000 K	242 lm	Diff.+60°
UPS	White	CRI <70	**64894.U**			

Onsight_SF | Escape signal | Ceiling luminaires | 220-240 V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62594.S**	5000 K	242 lm	Diff.+60°
UPS	White	CRI <70	**64894.S**			

Onsight_SF | Features

	Std.	UPS
Casing	die cast aluminium	die cast aluminium
Diffuser	PMMA	PMMA
Sign	silk-screened pictogram	silk-screened pictogram
Sign colour	white/green	white/green
Power supply (62574)	kit driver + 7.2 V 1600 mA/h NiCd battery pack	kit driver + 7.2 V 1600 mA/h NiCd battery pack
Power supply (62624)	kit driver + 4.8 V 1600 mA/h NiCd battery pack	kit driver + 4.8 V 1600 mA/h NiCd battery pack
Duration	1 hour (recharge period 12 hours) up to 3 hours (recharge period 24 hours)	1 hour (recharge period 12 hours) 3 hours (recharge period 24 hours)
Self-test	yes, with integrated LED light indicator	yes, with integrated LED light indicator
IP	40	40
Power	2 W	2 W

Onsight_RF | Escape signal | 220-240 V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62614.L**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64924.L**			

89373

Outer casing

Onsight_RF | Escape signal | 220-240 V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62614.R**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64924.R**			

89373

Outer casing

Onsight_RF | Escape signal | 220-240 V | powerLED 2 W 500 mA



type				colour		optic
Std.	White	CRI <70	**62614.U**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64924.U**			

89373

Outer casing

Onsight_RF | Features

	Std.	UPS
Casing	die cast aluminium	die cast aluminium
Diffuser	PMMA	PMMA
Sign	silk-screened pictogram	silk-screened pictogram
Sign colour	white/green	white/green
Power supply (62574)	kit driver + 7.2 V 1600 mA/h NiCd battery pack	kit driver + 7.2 V 1600 mA/h NiCd battery pack
Power supply (62624)	kit driver + 4.8 V 1600 mA/h NiCd battery pack	kit driver + 4.8 V 1600 mA/h NiCd battery pack
Duration	1 hour (recharge period 12 hours) 3 hours (recharge period 24 hours)	1 hour (recharge period 12 hours) 3 hours (recharge period 24 hours)
Self-test	yes, with integrated LED light indicator	yes, with integrated LED light indicator
IP	40	40
Power	2 W	2 W

Onsight_RF | Wall light | Ceiling luminaires | 220-240 V | powerLED 2 W 500 mA

EM IP40



type				colour		optic
Std.	White	CRI <70	**62604.U**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64914.U**			

89373

Outer casing

Onsight_RF | Wall light | Ceiling luminaires | 220-240 V | powerLED 2 W 500 mA

EM IP40



type				colour		optic
Std.	White	CRI <70	**62604.S**	5000 K	166 lm	Diffused
UPS	White	CRI <70	**64914.S**			

89373

Outer casing

Onsight_RF | Features

	Std.	UPS
Casing	die cast aluminium	die cast aluminium
Diffuser	PMMA	PMMA
Sign	silk-screened pictogram	silk-screened pictogram
Sign colour	white/green	white/green
Power supply (62574)	kit driver + 7.2 V 1600 mA/h NiCd battery pack	kit driver + 7.2 V 1600 mA/h NiCd battery pack
Power supply (62624)	kit driver + 4.8 V 1600 mA/h NiCd battery pack	kit driver + 4.8 V 1600 mA/h NiCd battery pack
Duration	1 hour (recharge period 12 hours) up to 3 hours (recharge period 24 hours)	1 hour (recharge period 12 hours) 3 hours (recharge period 24 hours)
Self-test	yes, with integrated LED light indicator	yes, with integrated LED light indicator
IP	40	40
Power	2 W	2 W

Sepic | Emergency 230~240V AC

F M M EM IP40



range	output	input	eff.	PF	surge	
1-5 W stripLED	150mA 24V	230~240V AC	80%	0.55	1 kV	**99339**
1-4 W powerLEDs	350mA 14V	230~240V AC	80%	0.55	1 kV	

Switchable (on/off) with normal power supply by means of a switch on the L' and N' (switched line) input.
Automatic reset after replacing battery and/or LED lamp.
Supplied with Ni-MH 6 cell battery pack, "AA" series, 1600 mAh.

Boost | Emergency 190~250V AC / 260~360V DC

F M M EM C.C. IP40



range	output	input	eff.	PF	surge	
13 W topLED	350mA 36V	190~250V AC	86%	0.9	4 kV	**99085**
12-15 W powerLEDs	350mA 45V	190~250V AC	86%	0.9	4 kV	
15 W arrayLED	400mA 37V	190~250V AC	86%	0.9	4 kV	**99095**
18-22,5 W powerLEDs	500mA 45V	190~250V AC	86%	0.9	4 kV	**99089**
23 W topLED	630mA 36V	190~250V AC	86%	0.9	4 kV	**99086**
24-30 W powerLEDs	630mA 45V	190~250V AC	86%	0.9	4 kV	
25 W arrayLED	720mA 37V	190~250V AC	86%	0.9	4 kV	**99097**
30 W topLED	840mA 36V	190~250V AC	86%	0.9	4 kV	**99098**
30 W arrayLED	840mA 37V	190~250V AC	86%	0.9	4 kV	
30 W topLED	840mA 40V	190~250V AC	86%	0.9	4 kV	

Switchable (on/off) with normal power supply by means of a switch on the SL (switched line) input.
Automatic reset after replacing battery and/or LED lamp.
Electronic multi-level charging system.
Supplied with Ni-MH 6 cell battery pack, "AA" series, 1600 mAh.

98436

Cable and connector

Code index

code	family	page
14931	Accent	403 - 415
	Bollard + Poles	482 - 531 - 530 - 549 - 550
4740	Linear_1	255
4741	Linear_2	255
4742	Linear_3	255
4743	Linear_4	255
50370	Accessories	411
51234	Matrix-C30_3	334
51235	Matrix-C30_3	334
51244	Matrix-C30_4	334
51245	Matrix-C30_4	334
51254	Matrix-C30_1	334
51255	Matrix-C30_1	334
51365	Vision_WJ	591
51366	Vision_WJ	591
51385	Vision_W	591
51386	Vision_W	591
51395	Vision_2	411
51396	Vision_2	411
51405	Vision_3	411
51456	Vega-C30_3	336
51475	Vision_X	411
51495	Vision_S	591
51496	Vision_S	591
51535	Orion-C30	335
51545	Orion-C30_J	335
51585	Vision_1	409
51586	Vision_1	409
51635	Orion-C15_Q	348
51745-TR	Accessories	348
51755	Orion-C15_R	348
51770	Accessories	266
51780	Accessories	266
51790	Accessories	266
52601	Texo_R	420
52671	Texo_Q	420
52700	Accessories	420
52901	Texo_RJ	420
52951	Texo_QJ	420
53033	Accessories	362
53034	Accessories	362
53035	Accessories	362
53038	Accessories	362
53045	I-Cube_W	584
53046	I-Cube_W	584
53055	I-Cube_S	584
53056	I-Cube_S	584
53065	I-Cube_1	535
53066	I-Cube_1	535
53075	I-Cube_2	535
53076	I-Cube_2	535
53204	Accessories	339 - 352
53205	Accessories	339 - 352
53214	Accessories	339 - 352
53215	Accessories	339 - 352
53225	Accessories	339 - 352
53234	Accessories	362
53235	Accessories	362
53890	Accessories	502 - 503 - 506
54274	Matrix_P	321
54275	Matrix_P	321
54284	Matrix-C30_2	334
54285	Matrix-C30_2	334
56990	Accessories	502 - 503
57154	Mini-Dual	261
57155	Mini-Dual	261
57350	Electronics	611 - 085
57660	Accessories	531 - 530
58675	Accessories	494
58685	Accessories	494
58695	Accessories	495
59094	Mini-Outline_MF	153
59114	Orion-C15_J	348
59115	Orion-C15_J	348
59134	Matrix-C15	348
59135	Matrix-C15	348
59165	Joe_1	482
59166	Joe_1	482
59175	Joe_1	482
59176	Joe_1	482
59192	Rock_2	541
59193	Rock_2	541
59194	Rock_1	541
59195	Rock_1	541
59196	Rock_3	541
59197	Rock_3	541
59223	Halley-C15_2	350
59228	Halley-C15_2	350
59229	Halley-C15_2	350
59365	Dual Out_W2	579
59366	Dual Out_W2	579
59375	Dual Out_W3	579
59376	Dual Out_W3	579
59385	Dual Out_W1	579
59386	Dual Out_W1	579
59394	Mini-Outline_MF	152
59404	Plik_QX	233
59405	Plik_QX	233
59434	Plik_RX	232
59435	Plik_RX	232
59460	Mini-Outline_MF	152
59461	Mini-Outline_MF	152
59462	Mini-Outline_MF	152
59463	Mini-Outline_MF	152
59464	Mini-Outline_MF	152
59466	Mini-Outline_MF	153
59467	Mini-Outline_MF	153
59474	Mini-Outline_MF	152
59484	Mini-Outline_MF	153
59494	Mini-Outline_MF	152
59520	Point	263
59521	Point	263
59522	Point	263
59523	Point	263
59530	Point-C30	335
59531	Point-C30	335
59532	Point-C15	349
59533	Point-C15	349
59538	Point-C	359
59539	Point-C	359
59694	Mini-Outline_F	243
59734	Orient-C_4	358
59735	Orient-C_4	358
59744	Orient-C_2	358
59745	Orient-C_2	358
59754	Orient-C_1	358
59950	Accessories	482 - 492 - 494 - 495
59960	Accessories	516
59970	Accessories	516
60065	Pilos_2	492
60073	Pilos_X	495
60074	Pilos_X	495
60075	Pilos_2	492
60100	Outline_MF	184
60101	Outline_MF	184
60102	Outline_MF	184
60103	Outline_MF	184
60107	Accessories	185
60108	Accessories	185
60109	Accessories	185
60110	Outline_MF	184
60111	Outline_MF	184
60112	Outline_MF	185
60113	Outline_MF	185
60117	Accessories	185
60118	Accessories	185
60119	Accessories	185
60120	Outline_MF	184
60121	Outline_MF	184
60122	Outline_F	237
60123	Outline_F	237
60127	Accessories	030 - 185
60128	Accessories	185
60164	Accessories	185
60595	Gypsum_QC4	096
60680	Gypsum_WF3	128
60711	Rock_W3	587
60714	Rock_W3	587
60715	Rock_W3	587
60731	Rock_W4	587
60734	Rock_W4	587
60735	Rock_W4	587
60770	Accessories	541
60771	Rock_W2	587
60774	Rock_W2	587
60775	Rock_W2	587
60791	Rock_W1	587
60794	Rock_W1	587
60795	Rock_W1	587
60801	Gypsum_O1	076
60802	Gypsum_O1	077
60811	Gypsum_WR3	123
60813	Gypsum_WR1	122
60814	Gypsum_WRQ	122
60815	Gypsum_WR2	122
60816	Gypsum_WX	118
60817	Gypsum_W2	118
60819	Gypsum_W3	118
60821	Gypsum_O2	076
60822	Gypsum_O2	077
60824	Gypsum_O3	076
60827	Gypsum_O4	076
60828	Gypsum_Eye4	084
60830	Accessories	066 - 070 - 071 - 076 - 077 - 084 - 085 - 090 - 094 - 095 - 096 - 100 - 104 - 108 - 118 - 122 - 123 - 128 - 129
60834	Gypsum_W1	118
60837	Accessories	122 - 123
60839	Accessories	118
60840	Accessories	094 - 095
60841	Fylo curved	104
60843	Gypsum_III1	090
60844	Gypsum_III2	090
60845	Gypsum_III3	090
60848	Gypsum_SQ	114
60851	Gypsum_SR	114
60852	Gypsum_Eye_2	084
60853	Gypsum_Eye_3	084
60860	Accessories	070 - 071
60910	Gypsum_WRX	123
60920	Gypsum_WF1	128
60930	Gypsum_WF2	128
60940	Gypsum_WF4	129
60980	Gypsum_Eye1	085

code	family	page
60990	Gypsum_QC2	094
61115	Pilos_1	494
61125	Pilos_1	494
61145	Pilos_1	494
61160	Cu-Flex_2	549
61161	Cu-Flex_2 Bright	550
61170	Cu-Flex_3	549
61171	Cu-Flex_3 Bright	550
61180	Cu-Flex_6	549
61181	Cu-Flex_6 Bright	550
61210	Gypsum_QC2	094
61230	Gypsum_R2	071
61250	Gypsum_R1	071
61270	Accessories	128
61290	Accessories	129
61320	Gypsum_QCY	096
61330	Gypsum_R2	070
61340	Gypsum_Eye1	084
61350	Gypsum_R1	070
61360	Accessories	070
61370	Gypsum_EyeJ	085
61390	Gypsum_WF4	129
61410	Gypsum_QCY	096
61430	Gypsum_QRD	104
61450	Gypsum_QRD	104
61501	Ciclop_1	530
61505	Ciclop_1	530
61511	Ciclop_2	530
61515	Ciclop_2	530
61521	Ciclop_1	530
61525	Ciclop_1	530
61560	Accessories	530
61570	Accessories	530
61581	Ciclop_3	530
61585	Ciclop_3	530
61591	Ciclop_3	531
61595	Ciclop_3	531
61800	Gypsum_QC3	095
61814	Neox_P	318
61815	Neox_P	318
61824	Neox_FL	318
61825	Neox_FL	318
61834	Neox_FL	318
61835	Neox_FL	318
62160	Accessories	153
62161	Accessories	153
62180	Accessories	030 - 034 - 035 - 153
62190	Accessories	523 - 524 - 525
62305	Stick_1	523
62306	Stick_1	523
62315	Stick_2	523

code	family	page
62316	Stick_2	523
62325	Stick_1	523
62326	Stick_1	523
62335	Stick_2	524
62336	Stick_2	524
62345	Stick_1	523
62346	Stick_1	523
62355	Stick_2	524
62356	Stick_2	524
62365	Stick_X1	524
62366	Stick_X1	524
62375	Stick_X2	525
62376	Stick_X2	525
62385	Stick_X1	525
62386	Stick_X1	525
62395	Stick_X2	525
62396	Stick_X2	525
62404	Stick_W	577
62405	Stick_W	577
62406	Stick_W	577
62423	Electronics	070 - 076 - 084 094 - 095 - 096 104 - 114- 606
62424	Electronics	100 - 606
62427	Electronics	608
62430	Gypsum_QC4	096
62431	Electronics	094 - 095 - 096 - 100 - 104 114 - 070 - 076 - 084 - 609
62432	Electronics	070 - 076 - 084 - 094 - 095 - 096 - 100 104 - 114 - 610
62437	Electronics	066 - 198 - 605
62438	Electronics	066 - 198 - 607
62439	Electronics	066 - 198 - 607
62480	Gypsum_QC3	095
62504	Fled_E	622
62514	Fled_E	622
62524	Fled_P	624
62534	Fled_P	624
62544	Fled_O	625
62554	Fled_O	625
62564	Fled_W	623
62574.L	Onsight_W	626
62574.R	Onsight_W	626
62574.U	Onsight_W	626
62584.L	Onsight_SF	628
62584.R	Onsight_SF	628
62584.U	Onsight_SF	628
62594.S	Onsight_SF	629
62594.U	Onsight_SF	629
62604.S	Onsight_RF	631
62604.U	Onsight_RF	631

code	family	page
62614.L	Onsight_RF	630
62614.R	Onsight_RF	630
62614.U	Onsight_RF	627
62624.L	Onsight_W	627
62624.R	Onsight_W	627
62624.U	Onsight_W	627
62630	Accessories	623
62660	Gypsum_R3	070
62706-1	Fylo curved	054
62757	Accessories	380 - 384
62758	Accessories	380 - 384
62759	Silicone_F	599
62761	Silicone_F	599
62870	Electronics	026 - 040 - 048 - 054 - 380 - 384 - 613
62880	Electronics	026 - 040 - 048 - 054 - 380 - 384 - 613
62890	Electronics	026 - 040 - 048 - 054 - 380 - 384 - 614
62900	Accessories	016 - 038 - 040 - 046 - 048 - 054
62911	Pool_S1	224
62912	Pool_S2	224
62915	Pool_S3	225
62916	Pool_P1	292
62921	Pool_P2	292
62922	Pool_S2	224
62923	Pool_S1	224
62925	Pool_S3	225
62926	Pool_P1	292
62927	Pool_CR2	222
62928	Pool_CR1	222
62931	Pool_C1	218
62934	Pool_C1	218
62932	Pool_C2	218
62935	Pool_C2	218
62933	Pool_C3	219
62936	Pool_C3	219
63100	Accessories	167 - 171 - 177
63101	Accessories	167 - 171 - 177
63102	Accessories	167 - 171 - 177
63103	Accessories	167 - 171 - 177
63106	Shore_MP	166
63107	Shore_MP	166
63110	Shore_MS	176
63111	Shore_MS	176
63112	Accessories	167 - 171 - 177
63113	Accessories	167 - 171 - 177
63116	Shore_MP	170
63117	Shore_MP	170
63120	Shore_MP	166
63121	Shore_MP	166

code	family	page
63122	Accessories	167 - 171 - 177
63123	Accessories	167 - 171 - 177
63126	Shore_MS	176
63127	Shore_MS	176
63128	Accessories	167 - 171 - 177
63130	Shore_MP	170
63131	Shore_MP	170
63132	Accessories	167 - 171 - 177
63133	Accessories	167 - 171 - 177
63134	Shore_P	305
63136	Shore_MP	166
63137	Shore_MP	166
63140	Shore_MS	176
63141	Shore_MS	176
63142	Accessories	167 - 171 - 177
63143	Accessories	167 - 171 - 177
63144	Shore_P	305
63146	Shore_MP	170
63147	Shore_MP	170
63150	Shore_MP	166
63151	Shore_MP	166
63153	Accessories	177
63156	Shore_MS	176
63157	Shore_MS	176
63160	Shore_MP	170
63161	Shore_MP	170
63166	Shore_MP	167
63167	Shore_MP	167
63170	Shore_MS	177
63171	Shore_MS	177
63176	Shore_MP	171
63177	Shore_MP	171
63180	Shore_MP	167
63181	Shore_MP	167
63186	Shore_MS	177
63187	Shore_MS	177
63190	Shore_MP	171
63191	Shore_MP	171
63196	Accessories	171 - 177
63197	Accessories	167 - 171
63198	Accessories	167 - 171
63199	Accessories	171 - 177
63254	Hive_P	314
63264	Hive_FL	314
63274	Hive_FL	314
63294	Hive_W	253
63405	Stalk_W1	575
63406	Stalk_W1	575
63415	Stalk_W2	575
63416	Stalk_W2	575
63425	Stalk_W3	575
63426	Stalk_W3	575

Code index

code	family	page
63445	Stalk_3	506
63446	Stalk_3	506
63455	Stalk_1	502
63456	Stalk_1	502
63465	Stalk_1	502
63466	Stalk_1	502
63475	Stalk_1	502
63476	Stalk_1	502
63495	Stalk_2	503
63496	Stalk_2	503
63505	Stalk_2	503
63506	Stalk_2	503
63515	Stalk_2	503
63516	Stalk_2	503
63601	Accessories	034 - 035
63605	Fylo+ Direct_3	020 - 021 - 034
63615	Fylo+ Direct_3	020 - 021 - 034
63625	Fylo+ Direct_3	020 - 021 - 034
63635	Fylo+ Direct_3	020 - 021 - 035
63645	Fylo+ Direct_3	020 - 021 - 035
63674	Wall_1	266
63684	Wall_2	266
63694	Wall_3	266
63785	Stalk_4	506
63786	Stalk_4	506
63820	Gypsum_QD2	100
63830	Gypsum_QD1	100
64001	Mini-Outline_MFY	154
64002	Mini-Outline_MFY	154
64003	Mini-Outline_MFY	154
64004	Mini-Outline_MFY	154
64014	Mini-Outline_MFY	154
64024	Mini-Outline_MFY	154
64120	D-Retta_1	545
64125	D-Retta_1	545
64130	D-Retta_2	545
64135	D-Retta_2	545
64180	Accessories	128
64201	Twig_1	516
64206	Twig_1	516
64211	Twig_2	516
64216	Twig_2	516
64221	Twig_3	516
64226	Twig_3	516
64234	Orient_S	249
64235	Orient_S	249
64244	Orient-C_3	358
64245	Orient-C_3	358
64251	Khono_1	415
64261	Khono_2	415
64500	Gypsum_QC1	094
64501	Gypsum_D1	108
64502	Gypsum_D2	108
64503	Gypsum_DX	108
64504	Gypsum_D3	108
64505	Cem_WF2	568
64506	Cem_WF1	568
64511	Dual_W1	259
64512	Dual_W1	259
64520	Vuelta_1	402
64521	Vuelta_1	402
64522	Vuelta_Y1	402
64523	Vuelta_Y1	402
64524	Vuelta_X1	402
64525	Vuelta_X1	402
64528	Vuelta_2	403
64529	Vuelta_2	403
64530	Vuelta_Y2	403
64531	Vuelta_Y2	403
64532	Accessories	403
64533	Accessories	403
64534	Accessories	403
64536	Accessories	403
64537	Accessories	403
64538	Accessories	403
64539	Accessories	403
64540	Cell_1	198
64541	Cell_1	198
64542	Cell_2	198
64543	Cell_2	198
64544	Cell_3	198
64545	Cell_3	198
64546	Gypsum_Cell1	066
64547	Gypsum_Cell1	066
64548	Gypsum_Cell2	066
64549	Gypsum_Cell2	066
64550	Gypsum_Cell3	066
64551	Gypsum_Cell3	066
64560	Cem_W2	564
64561	Cem_W1	564
64562	Cem_W3	564
64563	Cem_W4	564
64564	Cem_C	565
64569	Silicone_F	473 - 474 - 599
64570	Tour_PD1	283
64571	Tour_PD2	283
64572	Tour_PD3	283
64573	Tour_PD4	283
64574	Accessories	286
64575	Accessories	286
64576	Electronics	283 - 285 - 615
64577	Tour_P11	284
64578	Accessories	286
64579	Tour_P12	284
64580	Accessories	286
64581	Tour_P13	284
64582	Accessories	286
64583	Tour_PU1	285
64584	Tour_PU2	285
64585	Tour_PU3	285
64586	Accessories	286
64587	Tour_PU4	285
64588	Accessories	286
64589	Accessories	473
64590	Dirigo_FL1 Steel	470
64591	Dirigo_M1 Steel	474
64592	Accessories	474
64593	Accessories	474
64594	Dirigo_FL2 Aluminium	470
64595	Dirigo_M2 Aluminium	473
64597	Dirigo_M2 Aluminium	473
64598	Dual_W2	259
64599	Dual_W2	259
64635	Joe_2	482
64636	Joe_2	482
64640	Accessories	473
64641	Accessories	473
64642	Dirigo_FL2 Aluminium	470
64643	Dirigo_FL2 Aluminium	470
64644	Dirigo_M2 Aluminium	473
64645	Dirigo_M2 Aluminium	473
64646	Dirigo_M2 Aluminium	473
64647	Dirigo_M2 Aluminium	473
64648	Dirigo_M1 Steel	474
64650	Stalk_X	502
64651	Stalk_X	502
64661	Accessories	473
64662	Accessories	473
64663	Accessories	473
64664	Dirigo_M2	472
64665	Dirigo_M2	472
64666	Dirigo_M2	472
64667	Dirigo_M2	472
64668	Dirigo_M2	472
64669	Dirigo_M2	472
64670	Accessories	286
64671	Accessories	286
64672	Accessories	286
64673	Accessories	286
64674	Accessories	286
64675	Accessories	286
64676	Accessories	286
64677	Accessories	286
64678	Accessories	286
64679	Accessories	286
64680	Accessories	286
64681	Accessories	286
64682	Tour_PU1	285
64683	Tour_PU1	285
64684	Tour_PU1	285
64685	Tour_PU1	285
64686	Tour_PU2	285
64687	Tour_PU2	285
64688	Tour_PU2	285
64689	Tour_PU2	285
64690	Tour_PU3	285
64691	Tour_PU3	285
64692	Tour_PU3	285
64693	Tour_PU3	285
64694	Tour_PU4	285
64695	Tour_PU4	285
64696	Tour_PU4	285
64697	Tour_PU4	285
64700	Puro	487
64701	Puro	487
64709	Self-C15_R	346
64710	Self-C15_RJ	346
64711	Bob18_2	436
64712	Bob18_2	436
64713	Trix-C30	332
64715	Bob18_1	436
64716	Bob18_1	436
64721	Ryo_1	444
64722	Ryo_2	444
64723	Ryo_1	444
64724	Ryo_2	446
64726	Ryo_1	444
64727	Ryo_2	446
64728	Ryo_1	444
64729	Ryo_2	446
64731	Self-C15_R	346
64732	Self-C15_RJ	346
64733	Trix-C30	332
64734	Ryo_1	444
64735	Ryo_2	446
64736	Ryo_1	444
64737	Ryo_2	446
64738	Plik_R1	232
64739	Plik_Q1	233
64740	Plik_Q2	233
64741	Baton_P1	300
64742	Baton_P1	300
64743	Baton_P2	300
64744	Baton_P2	300
64745	Plik_Q1	233
64746	Plik_Q2	233
64747	Plik_R1	232
64748	Plik_R2	232

code	family	page
64749	Plik_R1	232
64750	Plik_R2	232
64751	Plik_R2	232
64754	Baton_P1	300
64755	Baton_P2	300
64756	Plik_Q1	233
64757	Plik_Q2	233
64758	Accessories	444 - 446
64759	Ryo_1	444
64760	Ryo_1	444
64761	Ryo_1	444
64762	Ryo_2	446
64763	Ryo_2	446
64764	Ryo_2	446
64765	Mini-Outline_MP	146
64766	Mini-Outline_MP	146
64767	Mini-Outline_MS	146
64768	Mini-Outline_MS	146
64769	Mini-Outline_MPS	146
64770	Mini-Outline_MPS	146
64771	Mini-Outline_MPS	147
64772	Mini-Outline_MPS	146
64773	Mini-Outline_MPS	146
64774	Mini-Outline_MPS	147
64775	Accessories	147
64776	Accessories	147
64777	Accessories	147
64778	Mini-Outline_P	307
64779	Mini-Outline_P	307
64780	Mini-Outline_S	243
64781	Mini-Outline_S	243
64782	Baton_P4	300
64783	Baton_P4	300
64784	Baton_P4	300
64785	Baton_P3	300
64786	Baton_P3	300
64787	Baton_P3	300
64788	Peak_L	454
64789	Peak_L	454
64790	Peak_L	454
64791	Peak_2	454
64792	Peak_2	454
64793	Peak_2	454
64794	Peak_1	454
64795	Peak_1	454
64796	Peak_1	454
64804	Fled_E	622
64814	Fled_E	622
64824	Fled_P	624
64834	Fled_P	624
64844	Fled_O	625
64854	Fled_O	625

code	family	page
64864	Fled_W	623
64874.L	Onsight_W	627
64874.R	Onsight_W	627
64874.U	Onsight_W	627
64884.L	Onsight_W	626
64884.R	Onsight_W	626
64884.U	Onsight_W	626
64894.S	Onsight_SF	629
64894.U	Onsight_SF	629
64904.L	Onsight_SF	628
64904.R	Onsight_SF	628
64904.U	Onsight_SF	628
64914.S	Onsight_RF	631
64914.U	Onsight_RF	631
64924.L	Onsight_RF	630
64924.R	Onsight_RF	630
64924.U	Onsight_RF	630
65000	Fylo+ Direct_1	020 - 021 - 038
65001	Fylo+ Direct_1	020 - 021 - 038
65002	Accessories	568
65003	Fylo+ Recessed_3	020 - 021 - 038
65004	Fylo+ Recessed_3	020 - 021 - 038
65005	Accessories	568
65006	Fylo+ Recessed_2	020 - 021 - 038
65007	Fylo+ Recessed_2	020 - 021 - 038
65008	Accessories	046
65009	Fylo+ Recessed_4	020 - 021 - 040
65010	Fylo+ Recessed_4	020 - 021 - 040
65011	Accessories	046
65012	Fylo+ Recessed_5	020 - 021 - 040
65013	Fylo+ Recessed_5	020 - 021 - 040
65014	Accessories	046
65015	Fylo+ Surface_1	020 - 021 - 046
65016	Fylo+ Surface_1	020 - 021 - 046
65017	Accessories	384
65018	Fylo+ Surface_2	020 - 021 - 046
65019	Fylo+ Surface_2	020 - 021 - 046
65020	Accessories	384
65021	Fylo+ Surface_3	020 - 021 - 046
65022	Fylo+ Surface_3	020 - 021 - 046
65023	Accessories	380
65024	Fylo+ Surface_4	020 - 021 - 048
65025	Fylo+ Surface_4	020 - 021 - 048
65026	Accessories	380
65027	Fylo+ Recessed_1	020 - 021 - 038
65028	Fylo+ Recessed_1	020 - 021 - 038
65029	Fylo+ Direct_1	026
65030	Fylo+ Out Surface_S	374 - 375 - 384
65031	Fylo+ Out Surface_S	374 - 375 - 384
65032	Fylo+ Recessed_1	038
65033	Fylo+ Out Surface_W	374 - 375 - 384
65034	Fylo+ Out Surface_W	374 - 375 - 384

code	family	page
65035	Accessories	380
65036	Fylo+ Out Recessed_S	374 - 375 - 380
65037	Fylo+ Out Recessed_S	374 - 375 - 380
65038	Accessories	380
65039	Fylo+ Out Recessed_W	374 - 375 - 380
65040	Fylo+ Out Recessed_W	374 - 375 - 380
65042	Fylo+ Direct_2	020 - 021 - 030
65043	Fylo+ Direct_2	020 - 021 - 030
65044	Accessories	030
65045	Fylo+ Recessed_2	038
65046	Fylo+ Recessed_3	038
65047	Fylo+ Recessed_4	040
65048	Fylo+ Recessed_5	040
65049	Fylo+ Surface_1	046
65050W	Inflex	026 - 040 - 048
65051W	Inflex	026 - 040 - 048
65052W	Inflex	026 - 040 - 048
65053	Fylo+ Surface_2	046
65054	Accessories	026 - 040 - 046 - 048
65055	Accessories	026 - 040 - 046 - 048
65056	Accessories	030
65057	Accessories	030
65058	Fylo+ Surface_3	046
65059	Fylo+ Surface_4	048
65060	Peak-Maxi_1	460
65061	Peak-Maxi_1	460
65062	Peak-Maxi_1	460
65063	Peak-Maxi_L2	460
65064	Peak-Maxi_L2	460
65065	Peak-Maxi_L2	460
65066	Peak-Maxi_D2	461
65067	Peak-Maxi_D2	461
65068	Peak-Maxi_D2	461
65069	Peak-Maxi_FR	461
65070	Peak-Maxi_FR	461
65071	Peak-Maxi_FR	461
65072	Peak-Maxi_L1	460
65073	Peak-Maxi_L1	460
65074	Peak-Maxi_L1	460
65075	Accessories	460 - 461
65076	Accessories	460 - 461
65077	Accessories	460 - 461
65078	Accessories	460 - 461
65079	Peak-Maxi_W	571
65080	Peak-Maxi_W	571
65081	Peak-Maxi_W	571
65082	Accessories	454
65083	Peak-Maxi_W	571
65084	Peak-Maxi_W	571
65085	Peak-Maxi_W	571
65090	Fylo+ Out Recessed_S	380

code	family	page
65091	Fylo+ Out Surface_S	384
65092	Fylo+ Out Surface_W	384
65093	Fylo+ Out Recessed_W	380
65094	Accessories	380 - 384
65095	Silicone_F	599
65096	Silicone_F	599
65100	Tour_PI1	284
65101	Tour_PI1	284
65102	Tour_PI1	284
65103	Tour_PI1	284
65104	Tour_PI2	284
65105	Tour_PI2	284
65106	Tour_PI2	284
65107	Tour_PI2	284
65108	Tour_PI3	284
65109	Tour_PI3	284
65110	Tour_PI3	284
65111	Tour_PI3	284
65112	Tour_PD1	283
65113	Tour_PD1	283
65114	Tour_PD1	283
65115	Tour_PD1	283
65116	Tour_PD2	283
65117	Tour_PD2	283
65118	Tour_PD2	283
65119	Tour_PD2	283
65120	Tour_PD3	283
65121	Tour_PD3	283
65122	Tour_PD3	283
65123	Tour_PD3	283
65124	Tour_PD4	283
65125	Tour_PD4	283
65126	Tour_PD4	283
65127	Tour_PD4	283
65128	Tour_PD1	283
65129	Tour_PD2	283
65130	Tour_PD3	283
65131	Tour_PD4	283
65132	Tour_PI1	284
65133	Tour_PI2	284
65134	Tour_PI3	284
65135	Tour_PU1	285
65136	Tour_PU2	285
65137	Tour_PU3	285
65138	Tour_PU4	285
65139	Accessories	286
65140	Accessories	286
65141	Accessories	286
65142	Accessories	286
65143	Accessories	286
65144	Accessories	286
65145	Accessories	286

Code index

code	family	page
65146	Accessories	286
65147	Accessories	286
65148	Accessories	286
65149	Accessories	286
65150	Accessories	286
65151	Accessories	286
65152	Accessories	286
65153	Accessories	286
65154	Accessories	286
65155	Accessories	286
65156	Accessories	286
65157	Accessories	286
65158	Accessories	286
65159	Accessories	286
65160	Accessories	286
65161	Accessories	286
84700	Electronics	282 - 283 - 284 - 285 - 616
84701	Electronics	283 - 285 - 616
84702	Electronics	026 - 040 - 048 - 054 - 380 - 384 - 617
84829	Electronics	596 - 597 - 598
89105	Ribbon	596
89106	Ribbon	596
89144	Electronics	122 - 123 - 128 - 608
89145	Electronics	122 - 123 - 128 - 608
89146	Electronics	605
89179	Electronics	599 - 614
89359	Electronics	599 - 614
89373	Accessories	622 - 624 - 625 - 630 - 631
89398	Dropper	598
89399	Dropper	598
89408	Electronics	596 - 598 - 613
89410	Ribbon	596
89411	Ribbon	596
89416	Dropper	598
89422	Electronics	568 - 608
89423	Electronics	608
89487	Electronics	596 - 597 - 598 - 613
89629	Accessories	473 - 474
89641	Dropper	598
89642	Dropper	598
89975	Ribbon	596
89976	Dropper	598
89979	Ribbon	596
91229	Illuminator_3	091
91232	Illuminator_3	091
91990	Rada_R01	207
91991	Rada_R01	207
91992	Rada_R1	206

code	family	page
91993	Rada_R1	206
91994	Rada_R02	207
91995	Rada_R02	207
91996	Rada_R2	206
91997	Rada_R2	206
91998	Rada_R03	208
91999	Rada_R03	208
92000	Rada_R3	206
92001	Rada_R3	206
92002	Rada_R04	208
92003	Rada_R04	208
92004	Rada_R4	206
92005	Rada_R4	206
92432	Rada_Q1	208
92433	Rada_Q1	208
92434	Rada_Q2	208
92435	Rada_Q2	208
93854	Rada_R5	207
93855	Rada_R5	207
93862	Rada_R6	207
93863	Rada_R6	207
97476	Illuminator_1	091
97482	Illuminator_1	091
97485	Illuminator_2	091
97491	Illuminator_2	091
98010	Ribbon	596
98011	Ribbon	596
98012	Ribbon	596
98018	Dropper	598
98019	Dropper	598
98020	Dropper	598
98025	Dropper	599
98034	Ribbon	596
98035	Ribbon	596
98036	Ribbon	596
98071	Accessories	091
98072	Accessories	091
98073	Ribbon	597
98074	Ribbon	597
98075	Ribbon	597
98076	Ribbon	597
98077	Ribbon	597
98078	Ribbon	597
98079	Ribbon	597
98080	Ribbon	597
98081	Ribbon	597
98082	Ribbon	597
98083	Ribbon	597
98084	Ribbon	597
98085	Dropper	598
98090	Dropper	598
98091	Dropper	598

code	family	page
98092	Dropper	598
98341	Ribbon	596
98342	Ribbon	596
98343	Dropper	598
98344	Dropper	598
98347	Ribbon	596
98348	Ribbon	596
98349	Dropper	598
98350	Dropper	598
98436	Accessories	632
98450	Ribbon	597
98451	Ribbon	597
98507	Accessories	091
98508	Accessories	091
98509	Accessories	091
98547	Ribbon	597
98548	Ribbon	597
98555	Ribbon	596
98556	Ribbon	596
98557	Dropper	598
98558	Dropper	598
98561	Ribbon	596
98562	Ribbon	596
98565	Dropper	598
98566	Dropper	598
98567	Ribbon	597
98568	Ribbon	597
98569	Ribbon	597
98570	Ribbon	597
98571	Dropper	598
98572	Dropper	598
98573	Dropper	598
98574	Dropper	598
98575	Dropper	598
98576	Dropper	598
98635	Ribbon	596
98636	Ribbon	596
98637	Ribbon	596
98638	Ribbon	596
98639	Ribbon	596
98640	Ribbon	596
98651	Ribbon	597
98734	Ribbon	596
98735	Ribbon	596
98736	Ribbon	596
98737	Ribbon	596
98738	Ribbon	596
98739	Ribbon	596
98740	Ribbon	596
99000	Accessories	473 - 474
99023	Electronics	616
99024	Electronics	616

code	family	page
99074	Electronics	026 - 040 - 048 054 - 282 - 283 284 - 285 380 - 384 597 - 615
99076	Electronics	597 - 599 - 616
99077	Electronics	026 - 040 - 048 - 054 - 283 - 284 - 380 - 384 - 579 - 615
99085	Boost	632
99086	Boost	632
99089	Boost	632
99093	Electronics	091 - 607
99095	Boost	632
99096	Boost	632
99097	Boost	632
99098	Boost	632
99099	Electronics	207
99101	Electronics	207
99106	Electronics	070 - 076 - 606
99112	Electronics	091 - 206 - 207 - 607
99113	Electronics	091 - 607
99114	Electronics	066 - 070 - 076 - 084 - 094 - 100 - 122 - 123 - 128 - 198 - 609
99115	Electronics	066 - 070 - 076 - 084 - 094 - 100 - 122 - 123 - 128 - 198 - 608
99116	Electronics	091 - 206 - 207 - 609
99125	Electronics	616
99126	Electronics	084 - 100 - 605
99128	Electronics	094 - 605
99131	Electronics	206 - 207 - 208 - 604
99163	Electronics	091 - 206 - 207 - 601
99187	Electronics	091 - 611
99188	Electronics	206 - 207 - 208 - 610
99195	Electronics	094 - 605
99260	Electronics	091 - 206 - 207 - 611
99261	Electronics	207 - 208
99262	Electronics	206 - 207- 208 - 609
99278	Electronics	597 - 599 - 616
99330	Electronics	091 - 206 - 611
99331	Electronics	473 - 474 - 596 - 612
99332	Electronics	474 - 614
99339	Sepic	632
99341	Electronics	604
99344	Electronics	066 - 198 - 610
99368	Electronics	206 - 207 - 606

code	family	page
E41017	Accessories	420
E41025	Accessories	420
TR4000-3	Vega-C30_1	336
TR4000-48	Vega-C30_1	336
TR4000-5	Vega-C30_1	336
TR4000-9	Vega-C30_1	336
TR4008-5	Modular-C30_4	336
TR4014-3	Vega-C30_2	336
TR4014-48	Vega-C30_2	336
TR4014-5	Vega-C30_2	336
TR4100-3	Accessories	338
TR4100-5	Accessories	338
TR4100-8	Accessories	338
TR4101-3	Accessories	339
TR4101-4	Accessories	339
TR4101-5	Accessories	339
TR4101-8	Accessories	339
TR4101-9	Accessories	339
TR4102-3	Accessories	338
TR4102-48	Accessories	338
TR4102-5	Accessories	338
TR4102-9	Accessories	338
TR4103-3	Accessories	339
TR4103-4	Accessories	339
TR4103-48	Accessories	339
TR4103-5	Accessories	339
TR4103-9	Accessories	339
TR4104-3	Accessories	340 - 353
TR4104-8	Accessories	353
TR4105-3	Accessories	340
TR4105-5	Accessories	340
TR4105-8	Accessories	340
TR4106-3	Accessories	339
TR4106-48	Accessories	339
TR4106-5	Accessories	339
TR4107-3	Accessories	338
TR4107-48	Accessories	338
TR4107-5	Accessories	338
TR4107-9	Accessories	338
TR4108-3	Accessories	338
TR4108-5	Accessories	338
TR4108-8	Accessories	338
TR4109-3	Accessories	338 - 352
TR4109-4	Accessories	338 - 352
TR4109-5	Accessories	338 - 352
TR4109-5	Accessories	338 - 352
TR4109-8	Accessories	338 - 352
TR4109-9	Accessories	338 - 352
TR4110-3	Accessories	338 - 352
TR4110-4	Accessories	338 - 352
TR4110-5	Accessories	338 - 352
TR4110-8	Accessories	338 - 352

code	family	page
TR4110-9	Accessories	338 - 352
TR4111-3	Accessories	362
TR4111-4	Accessories	362
TR4111-5	Accessories	362
TR4111-8	Accessories	362
TR4111-9	Accessories	362
TR4112-3	Accessories	362
TR4112-4	Accessories	362
TR4112-5	Accessories	362
TR4112-8	Accessories	362
TR4112-9	Accessories	362
TR4113-3	Accessories	353
TR4113-4	Accessories	353
TR4113-5	Accessories	353
TR4113-8	Accessories	353
TR4113-9	Accessories	353
TR4114-3	Accessories	363
TR4114-4	Accessories	363
TR4114-5	Accessories	363
TR4114-8	Accessories	363
TR4114-9	Accessories	363
TR4115-3	Accessories	352
TR4115-48	Accessories	352
TR4115-9	Accessories	352
TR4116-3	Accessories	352
TR4116-48	Accessories	352
TR4116-9	Accessories	352
TR4117-3	Accessories	363
TR4117-8	Accessories	363
TR4117-9	Accessories	363
TR4118-3	Accessories	362
TR4118-48	Accessories	362
TR4118-9	Accessories	362
TR4119-3	Accessories	363
TR4119-4	Accessories	363
TR4119-48	Accessories	363
TR4119-5	Accessories	363
TR4119-9	Accessories	363
TR4120-3	Accessories	363
TR4120-8	Accessories	363
TR4121-3	Accessories	353
TR4121-5	Accessories	353
TR4121-8	Accessories	353
TR4121-9	Accessories	353
TR4122-3	Accessories	353
TR4122-48	Accessories	353
TR4123-3	Accessories	362
TR4123-48	Accessories	632
TR4124-3	Accessories	340 - 353
TR4124-8	Accessories	340 - 353
TR4150	Accessories	340 -354
TR4150-10	Accessories	340 - 353

code	family	page
TR4150-15	Accessories	340 - 353
TR4150-20	Accessories	340 - 353
TR4150-25	Accessories	340 - 353
TR4150-30	Accessories	340 - 353
TR4150-5	Accessories	340 - 353
TR4150-50	Accessories	340 - 353
TR4151	Accessories	340 - 354 - 363
TR4151-10	Accessories	340 - 354 - 363
TR4151-15	Accessories	340 - 354 - 363
TR4151-20	Accessories	340 - 354 - 363
TR4151-25	Accessories	340 - 354 - 363
TR4151-30	Accessories	340 - 354 - 363
TR4151-5	Accessories	340 - 354 - 363
TR4151-50	Accessories	340 - 354 - 363
TR4152	Accessories	340 - 354 - 363
TR4152-10	Accessories	340 - 354 - 363
TR4152-15	Accessories	340 - 354 - 363
TR4152-20	Accessories	340 - 354 - 363
TR4152-25	Accessories	340 - 354 - 363
TR4152-30	Accessories	340 - 354 - 363
TR4152-5	Accessories	340 - 354 - 363
TR4152-50	Accessories	340 - 354 - 363
TR4200-3	Halley-C15_1	350
TR4200-48	Halley-C15_1	350
TR4200-9	Halley-C15_1	350
TR4201-3	Halley-C15_J1	350
TR4201-48	Halley-C15_J1	350
TR4201-9	Halley-C15_J1	350
TR4202-3	Halley-C15_J2	350
TR4202-48	Halley-C15_J2	350
TR4202-9	Halley-C15_J2	350
TR4217-9	Bell-C15	351
TR4302-3	Tek-C_1	360
TR4302-48	Tek-C_1	360
TR4302-9	Tek-C_1	360
TR4303-3	Andromeda-C_2	360
TR4303-48	Andromeda-C_2	360
TR4303-9	Andromeda-C_2	360
TR4304-3	Andromeda-C_1	360
TR4304-48	Andromeda-C_1	360
TR4304-9	Andromeda-C_1	360
TR4307-3	Tek-C_2	360
TR4307-48	Tek-C_2	360
TR4307-9	Tek-C_2	360
TR4310-3	Virgo-C	361
TR4310-48	Virgo-C	361
TR4317-9	Bell-C	361

How to...

Product name

Product description

new

Cell

Luce invisibile

Spot multiottica predisposto per installazione
in controsoffitti, disponibile in tre versioni a luce diretta: rettangolare 3
e 6 spot, quadrata 9 spot.
Cornice in alluminio verniciato bianco opaco.
Ideale per illuminazione d'accento. Speciali celle cut-off garantiscono
il massimo comfort visivo per l'utente.
Sorgente LED arretrata e schermata.

+ incasso ultra compatto
+ luminanza controllata
+ sorgente LED
+ doppia finitura del vano ottico

640 ARCHITECTURAL LIGHTING 1.0

Versioni Gypsum
56

Wall + Ceiling 640

Product information

Family

Composition table:
code / colour / optics



Code composition: type + colour + optics

Cell_1 | Downlights | 3 powerLED 2 W | 6 W 700 mA

113 x 40

type			colour			optics	
White	CRI 90	64541	3000 K	747 lm	W	15°	15
Black	CRI 80	64540	4000 K	795 lm	N	30°	30

Suggested electronics

62437	62439	99115	99114	99344
ON/OFF 1 art.	ON/OFF 3-4 art.	1-10V/PUSH 1-3 art.	DALI/PUSH 1-3 art.	DALI/PUSH 1-4 art.

Cell_2 | Downlights | 6 powerLED 2 W | 12 W 700 mA

217 x 40

type			colour			optics	
White	CRI 90	64543	3000 K	1494 lm	W	15°	15
Black	CRI 80	64542	4000 K	1590 lm	N	30°	30

Suggested electronics

62438	62439	99115	99114	99344
ON/OFF 1 art.	ON/OFF 2 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.	DALI/PUSH 1-4 art.

Cell_3 | Downlights | 9 powerLED 2 W | 18 W 700 mA

113

type			colour			optics	
White	CRI 90	64545	3000 K	2241 lm	W	15°	15
Black	CRI 80	64544	4000 K	2385 lm	N	30°	30

Suggested electronics

62439	99115	99114
ON/OFF 1 art.	1-10V/PUSH 1 art.	DALI/PUSH 1 art.

641

Wall + Ceiling

641

Product detail

Dimensioned technical drawing

Recommended accessories and electronics

Finishes

White | RAL 9003 embossed

Grey | RAL 9006 embossed

Black Grey | RAL 7021 embossed

Black | RAL 9005 embossed

Anodized aluminium

Chrome

Steel

Brushed Nickel



Cor-Ten | Finish

Gold | Warm & Chic

Copper

Rust | Finish



Bronze

Rose gold

Cement

Concrete



White | Quartz agglomerate

Sand | Quartz agglomerate



Grey | Quartz agglomerate

Brown | Wood Finish

Grey | Wood Finish

Symbols

- Indoor installation
- Outdoor installation
- Wall mounting
- Ground mounting
- Ceiling mounting
- Wall or ground mounting
- Ceiling or wall mounting
- Ceiling, wall or ground mounting
- Ceiling or ground mounting
- Stainless steel
- IP-- Protection class (IEC 60529) against foreign bodies and water
- IP-- O.C. Protection index on the optical compartment
- IK-- Protection degrees (IEC 62262) against external mechanical impacts
- Directional light beam
- Tilting light beam
- Walk-over lighting fixture
- Drive-over lighting fixture
- Power supply cable included
- Class I - IEC protection class
- Class II - IEC protection class
- Class III - IEC protection class
- Driver included
- Driver not included

- T3 Over Voltage Protection
- Article protected by resin potting
- EM Available in emergency version
- Round installation hole
- Quadrangular installation hole
- Single emission luminaire
- Double emission luminaire
- M M Device suitable to be mounted on furniture
- F Device suitable to be mounted on normally flammable surfaces (EN 60598)
- P Device with integrated thermal protection
- Simply DIM Simply Dim
- Push DIM Push Dim
- 1-10V 1-10 V
- DMX 512 DMX 512
- DALI DALI
- C.C. Constant Current
- C.V. Constant Voltage
- P.I.R. sensor
- R.F. remote control
- Infrared
- Dimming Dimming
- LED Compatible with LED bulbs
- Asymmetric emission

All articles belong to energy class A++.
The lumens indicated refer to the light source emission.
The connection diagrams for electronics articles are included in the technical documentation.

Credits

Acqua Minerale San Benedetto SpA
Venice (Italy)

Project
Arch. Gianni Rigo

Photography
Corrado Covre

Amelie toy library
Rome (Italy)

Photography
Fabio Gambina

Auto Ikaro Showroom
Bolzano (Italy)

Project
EOS Luce

Photography
Matteo De Stefano

Ascom
Bergamo (Italy)

Photography
Antonio Buonsante

BCC Bank of Caraglio
Cuneo (Italy)

Project & Photography
Studio Kuadra



Bill&Coo
Mykonos (Greece)

Project
IFI Group
Pavlov Ninios

Photography
Yannis Kontos Photojournalist

Bisatti pharmacy
Pordenone (Italy)

Project
Linea Light Group

Photography
Corrado Covre

Caffè degli Artisti
Nuoro (Italy)

Project
Studio Tondo

De Amicis Primary School
Arezzo (Italy)

Project
FABBRICANOVE Architetti
Studio Tecnico Associato Santi

Photography
Andrea Badoni

Doulgerakis Residence
(Greece)

Project
IFI Group

Photography
Yannis Kontos Photojournalist

Ekipe Sports Center
Catania (Italy)

Project
Arch. Salvatore Puleo

Photography
Fabio Gambina

Emfietzoglou Museum
Athens (Greece)

Project
IFI Group
Arch. Katerina Diakomidou & Nikos Haritos

Endress+Hauser
Milan (Italy)

Project
Arch. Roberto Frizzi

Photography
Andrea Badoni

FerroWine
Treviso (Italy)

Project
Arch. Bernardino Baesso
Studio Frasson & Fanton

Photography
SlowPhoto

Formentini Lab
Milan (Italy)

Project
Alterstudio Partners

Photography
Andrea Badoni



Glyfada Residence
(Greece)

Project
IFI Group

Horizon House
Aberdeen (Scotland)

Project
Cumming & Co.

Intesa SanPaolo Bank
Turin (Italy)

Photography
Fabio Gambina

Iran Pavillion
EXPO 2015 Milan (Italy)

Project
Arch. Asghar Firouzabadi
RPA Srl

Photography
Andrea Badoni



Itop SpA
Rome (Italy)

Photography
Fabio Gambina

Katsouris Residence
(Greece)

Project
IFI Group

Photography
Yannis Kontos Photojournalist



Kypriotis
Athens (Greece)

Project
IFI Group
Karagiannis architects

Photography
Yannis Kontos Photojournalist



Light+building 2016
Linea Light Group stand
Frankfurt (Germany)

Project
Linea Light Group
Studio Gherardi

Photography
Notorious Communication Lab

Locate Varesino
public square
Como (Italy)

Photography
Andrea Badoni

Neues Gymnasium
Bochum (Germany)

Project
Arch. Hascher & Jehle
Eng. Büro Krawinkel Krefeld

Photography
Ali Moshiri



Private Studio
Catania (Italy)

Project
Gildo Meucci
3D Light & Design Srl

Photography
Fabio Gambina

Private House
Cuneo (Italy)

Project
i-Light
Arch. Alessandro Verney
Arch. Alfio Tomatis

Photography
Arch. Simona Cosentino

Private Villa
(Italy)

Photography
Luigi De Nadai

Private House
Ivrea (Italy)

Photography
Arch. Rosa Amato

Private Villa
Porto Cheli (Greece)

Project
IFI Group
GEM Architects

Photography
Yannis Kontos Photojournalist

Private Villa
Treviso (Italy)

Project
TEC-LIGHT
Arch. Francesco Stimamiglio

Private House
(Spain)

Photography
J. Perez Curbelo

Roveda Srl shoe factory
Milan (Italy)

Photography
Andrea Badoni



Sirene Beach Hotel
Rhodes (Greece)

Project
IFI Group

Photography
Yannis Kontos Photojournalist

Toylan Jumbo
Mykonos (Greece)

Project
IFI Group

Photography
Yannis Kontos Photojournalist

Villa Contarini Nenzi
Treviso (Italy)

Project
Arch. Francesco Di Nisio

Photography
Luigi De Nadai

Wignacourt Museum
Malta

Project
Arch. Francesco Di Nisio

Photography
Luigi De Nadai

Private Villa
San Teodoro (Italy)

Project & Photography
Arch. Enrico Campus

Addresses

Linea Light S.r.l. Italy
via della Fornace, 59 z.i.
31023 Castelminio di Resana (TV) - Italy
Phone: +39 0423 78 68
Fax: +39 0423 78 69 00
info@linealight.com

LightVillage Milano - Exhibition Area Only
via Morimondo, 26 int. 17G
20143 Milano
Phone: +39 02 36750915
Fax: +39 02 36750915
milano@lightvillage.it

Linea Light France
Z.A. Heiden Est, 12 rue des Pays-Bas
68310 Wittelsheim - France
Phone: +33 389 75 52 23
Fax: +33 389 75 59 07
info@linealight.fr

Linea Light UK Ltd
Suite 109 - Business Design Centre
52 Upper Street - Islington N10QH - London - UK
Phone: +44 0203 6371983
info@linealight-uk.com

Linea Light Deutschland GmbH
Aktienstraße 214
45473 Mülheim a.d. Ruhr - Germany
Phone: +49 208 299979-0
Fax: +49 208 299979-10
service@linealight.de

Linea Light GCC - Middle East & Gulf Countries
Jumeirah Lake Towers
JBC2 - 35th Floor Office 02 - Dubai - UAE
P.O. Box 125902
Phone: +971 4 4218275
Fax: +971 4 4218274
info@linealight.ae

Linea Light Polska Sp. z.o.o.
ul. Wiosenna, 47
41253 Czeladz - Poland
Phone: +48 32 265 11 21
Fax: +48 32 265 04 42
biuro@linealight.com.pl

Linea Light Russia
Luzhnetskaya nab., 2/4, str. 3, of. 304
119270 Moscow - Russian Federation
Phone: +7 495 639 99 41
info@linealight.ru

Linea Light USA | Inter Lux
3741 Commerce Drive
Suites 306-308
Baltimore, MD 21227 - USA
Phone: +1 410 381 1497
Fax: +1 410 381 1589
answers@inter-lux.com

Linea Light Asia-Pacific Ltd
YuXiang Industrial Area
528478 HengLan Town, ZhongShan City,
GuangDong Province, China
Phone: +86 760 87618355
Fax: +86 760 87553990
info@linealight.cn

linea light group

linealight.com

The drawings, dimensions, materials and information shown in this catalogue are merely indicative.

In the customers' interest, the Company reserves the right to modify the models at any time without notice.

Art direction, rendering, still life pictures, proposed project drawings
Linea Light Group - Marketing Dept.
Linea Light Group - Product Technical Dept.
Lifestyle sets
Photo retouching
SYB

Printed by
Gualdani Art Graphics Srl

Printed in
April 2017

linea light group

Your Light | Future Proof